

APPLICATION FOR SUBMITTAL OF POST-APPROVAL DOCUMENT

This application is for submittal of documents, after the initial approval of the project (post-approval documents), that require Division of the State Architect (DSA) review and approval. This form shall be completed by the Design Professional in General Responsible Charge of the project, in accordance with California Code of Regulations, Title 24, Part 1, Sections 4-317, 4-323 and 4-338 and in compliance with DSA IR A-6: Construction Change Document Submittal and Approval Process.

DSA documents reference	ed within this form are available	on the DSA Fo	orms or DSA Public	cations webpages.		
1. SUBMITTAL TYPE:	(Is this a resubmittal? Yes□	No □)				
Deferred Submittal □	d Submittal □ Addendum Number: Revisio			CCD Nur	nber:	Category A \square or B \square
2. PROJECT INFORM	ATION:					
School District/Owner:					DSA File Nun	nber:
Project Name/School:					DSA Applicat	ion Number:
3. APPLICANT INFOR	MATION:					
Date Submitted:			Attached Pages?	No □ Yes □ Num	per of pages?	
Firm Name:			Contact Name:			
Work Email:			Work Phone:			
Firm Address:			City:		State:	Zip Code:
4. REASON FOR SUB	MITTAL: (Check applicable be	oxes)				
☐ For revision or adden	dum prior to construction.			□ For a	project currentl	y under construction.
☐ For a project that has a 90-Day Letter issue		of Requireme	nt for Certification,	DSA 301-P: Posted	l Notification of	Requirement for Certification or
☐ To obtain DSA appro	val of an existing uncertified bui	ilding or buildin	gs.			
☐ For Category B CCD	this is: □ a voluntary submittal,	□ a DSA requi	ired submittal (atta	ch DSA notice requ	ring submissio	 n).
5. DESIGN PROFESS	ONAL IN GENERAL RESPON	SIBLE CHAR	GE:			
Name of the Design Pro	fessional In General Responsib	ole Charge:				
Professional License Nu	ımber:		Discipline:			
and appear to meet the	appropriate requirements of Title instruction of the project. DESIGN PROFESSION	le 24, California	a Code of Regulation	ons and the project	specifications.	They are acceptable for
6. CONFIRMATION, D	ESCRIPTION AND LISTING O	F DOCUMENT	S:			
Design Professional liste Use of Construction Doo	or CCDs: CHECK THIS BOX ed on form DSA 1: Application for cuments Prepared by Other Pro cable, for signature and seal red	or Approval of fessionals, and	Plans and Specific	ations for this projec	ct. (For <i>Deferre</i>	d Submittals, refer to IR A-18:
Provide a brief description	on of construction scope for this	post-approval	document (attach	additional sheets if	needed):	
List of DSA-approved dr	awings affected by this post-ap	proval docume	nt:			
		-	SA USE ONLY			
		U	SA USE UNLT	Returned		DSA STAMP
SSSD	ate	Disapproved 🗆	Not Required	Pate:		
	ate □Approved □	Disapproved □		Ву:		
Comments:						
ACSD Comments:	ate □Approved □]Disapproved □	Not Required			
OUTITIONS						ļ



June 6, 2024

ADDENDUM 1

To the Contract Documents for the New Parking Lot

Grand Terrace Elementary School Colton Joint Unified School District SGH Architects Project Number: 22-12105-04 DSA A#04-122929

It is intended that all work affected by the following provisions shall conform to the original Plans and Specifications dated <u>April 19, 2024 (DSA Approval date)</u>. Delete or modify each of the following items wherever appearing on the Drawings and/or Specifications. Acknowledge receipt of this Addendum in the space provided on the Contractor's Proposal. Failure to do so may subject the bidder to disqualification.

GENERAL:

ITEM #1.1: The following is a revision to the bid date:

A. The bid due date has been extended. Sealed bids shall be submitted to the Colton Joint Unified School District Facilities Planning and Construction office located at 325 Hermosa Street, Building 5, Colton, CA 92324 prior to 2:00 pm on June 17, 2024.

PRE-BID RFI'S:

ITEM #1.2: The following are responses to pre-bid RFI's:

1. Specs 328400/3.02D shows sleeve for mainline is two pipe sizes larger. However, detail Sleeve trenching on sheet L1.02 shows sleeve is 2 times the diameter of pipe or wire. Please clarify.


Response: 2X

2. Specs 329300/3.03E shows planting pit is 2 times of root ball. However, detail Tree planting on sheet L2.01 shows planting pit is 3 times of root ball. Please clarify.

Response: 3X

3. There are some decomposed granite areas shown on sheet A1.12 but not shown on sheet L2.01. Please clarify.

Response: Decomposed granite shall be placed per sheet L2.01, and as noted on this RFI.




4. On sheet L1.01 irrigation distribution device legend shows irrigation controller is new. However, spec 328400/2.01 F shows existing controller. Please clarify.

Response: Furnish and install new Leit Irrigation Controller per Irrigation Legend.

5. Quick coupler valve is shown on irrigation distribution device legend/L1.01. However, it is not shown on plan. Please clarify.

Response: Furnish and install three (3) new Quick Couplers per irrigation Legend at locations noted on this RFI.



- 6. Requested Clarification:
 - a. When is the tentative date?
 - b. How much is the engineer's estimate?
 - c. Is there an allowance?
 - d. How many days for completion of work?

Response:

- a. Start ASAP.
- b. 1.5 Mil
- c. 100K (In the bid documents)
- d. 150 Days

GEOTECHNICAL RECOMMENDATION:

ITEM #1.3: The following letter is added for "Recommendations for Pavement Structural Sections":

A. MTGL letter dated May 28, 2024, Recommendations for Pavement Structural Sections, Grand Terrace Elementary School (Attachment 1)

HAZARDOUS MATERIALS SURVEY:

(PREPARED BY OTHER DISTRICT CONSULTANT AND NOT PREPARED BY SGH ARCHITECTS)

ITEM #1.4: The following letter is added for "Limited Asbestos and Lead Paint Survey":

A. B2 Environmental letter dated June 5, 2024, Limited Asbestos and Lead Paint Survey, Grand Terrace Elementary School – Buildings B, C, D Exteriors (Attachment 2)

SPECIFICATIONS:

ITEM #1.5: The following Table of Contents are re-issued:

A. Table of Contents a. Revised page 2 of 3 to add new specification section. (Attachment 3)

ITEM #1.6: The following Specification Sections are added:

A. 09 91 13 Exterior Painting (Attachment 4)

DRAWINGS:

ITEM #1.7: The following Drawings are re-issued:

A. Sheet G0.00 - Title Sheet

(Attachment 5)

- a. Added to Sheet Index new sheet A0.11 Project Phasing Plan and revised sheet count.
- b. Added to Sheet Index new sheet P2.01 Details and revised sheet count.
- c. Revised Sheet Index total sheet count.
- B. Sheet C-2.1 Topographic Map

(Attachment 6)

- a. Revised alignment of limits of removal due to storm drain revisions.
- C. Sheet C-2.2 Topographic Map

(Attachment 7)

- a. Revised alignment of limits of removal due to storm drain revisions.
- b. Included water line to be removed.
- c. Adjusted demolition limits of water lines.
- D. Sheet C-3.1 Precise Grading Plan

(Attachment 8)

- a. Shifted retention basin headwall to align with new storm drain layout.
- b. Revised limits of grading to match new storm drain layout.
- c. Addition of future improvements in the background for reference.
- E. Sheet C-3.2 Precise Grading Plan

(Attachment 9)

- a. Relocated manhole to avoid conflicts with existing tree.
- b. Revised limits of grading to match new storm drain layout.
- c. Revised sawcut scope to match new storm drain layout.
- d. Addition of future improvements in the background for reference.
- e. Addition of several protect in place/adjust to existing grade notes to several existing items.
- f. Provided new graded swale and planter drain North of parking lot.
- g. Showing existing posts that are to be protected in place.
- F. Sheet C-4.1 Composite Utility Plan

(Attachment 10)

- a. Revised storm drain layout to clear future building by 10'.
- b. Changed size of storm drain line.
- c. Addition of future improvements in the background for reference.
- d. Addition of water line data table.
- G. Sheet C-4.2 Composite Utility Plan

(Attachment 11)

- a. Changed sizes of various storm drain pipes.
- b. Revised layout of storm drain pipes within parking lot.
- c. Relocated manhole to avoid conflicts with existing tree.
- d. Addition of future improvements in the background for reference.
- e. Addition of new water line replacement
- f. Addition of water line notes
- g. Addition of water line data table

- i. Addition of connection to new planter drain.
- H. Sheet C-5.1 Horizontal Control Plan

(Attachment 12)

- a. Adjusted dimensions for limits of grading.
- b. Revised Horizontal Control Table data.
- c. Addition of future improvements in the background for reference.
- I. Sheet C-5.2 Horizontal Control Plan

(Attachment 13)

- a. Adjusted dimensions for limits of grading.
- b. Revised Horizontal Control Table data.
- c. Relocated various sawcut control points to match new site plan changes.
- d. Addition of future improvements in the background for reference.
- J. Sheet A0.10 Overall Site Plan

(Attachment 14)

- a. Corrected illegible keynote #5.
- b. Added dimensions to bioswale located at South/West corner of property.
- c. Added new chain-link fence and double service gates to enclose bio swale.
- d. Added new gate numbered G-5 to gate schedule for bio swale enclosure.
- e. Changed keynote #5 to #6 @ baseball backstop adjacent to bioswale.
- Revised layout of underground drainpipe and manhole from West of Building E to bioswale.
- g. Shifted bioswale headwall to align with underground drainpipe layout.
- h. Added and keynoted #4 existing trees near bioswale.
- i. Removed existing electrical pull boxes North of Building F, and West of Buildings C, F, S, E. Revised location of existing electrical pull box West of Building S.
- Removed underground electrical lines and concrete paving work West of Building E.
- k. Added note for contractor staging area located at North/East corner of property.
- K. Sheet A1.11 Site Plan-Enlarged Demolition

(Attachment 15)

- a. Revised keynote #37 to remove existing gas riser @ canopy post near South/East corner of Building B.
- b. Added keynote #44 to remove (2) mechanical room existing exterior doors to be replaced with new on East wall of Building E.
- c. Added keynote #45 to remove (1) existing exterior door threshold to be replaced with new on East wall of Building E.
- d. Corrected misaligned building wall at South/West corner of Building D.
- e. Removed underground electrical lines and concrete paving work West of Building E.
- f. Revised paving sawcut line to align with underground drainpipe layout near North/West corner of Building E and South of Building B.
- L. Sheet A1.12 Site Plan-Enlarged Remodel

(Attachment 16)

- a. Added keynote 12 to see City of Grand Terrace Street Improvement Plans.
- b. Added to keynote #30 to see City of Grand Terrace Street Improvement Plans.
- c. Revised keynote #32 to paint covered walkway and to be more specific of areas and components to be painted.
- d. Added keynote #32 to covered walkways between Buildings B, C, D and E.
- e. Revised keynote #33 to paint building and to be more specific of areas and components to be painted.

- f. Added keynote #33 under names of Buildings B, C, D and E.
- g. Added keynote #40 to replace (2) exterior doors with new on East wall of Building E.
- h. Added keynote #41 to paint (3) doors on East wall of Building E.
- i. Added keynote #42 to provide new door thresholds at (3) doors on East wall of Building E.
- Added keynote #43 to note electrical conduits near North/East corner of Building B.
- k. Added keynote #44 to note gas riser near South/East corner of Building B.
- I. Added keynote #45 to scrape off the finish plaster coat and provide new finish coat on East wall of Building B.
- m. Added general note #10.
- n. Added general note #11.
- o. Corrected misaligned building wall at South/West corner of Building D.
- p. Removed underground electrical lines and concrete paving work West of Building E.
- q. Added portion of West sides of Buildings B and C and keynote #33.
- r. Revised paving line to align with underground drainpipe layout near North/West corner of Building E and South of Building B.

M. Sheet A1.23 - Site Details-Fencing

(Attachment 17)

- a. Added new Chain-link Double Service Gates detail #14.
- b. Added new Door Threshold detail #15.

N. Sheet E0.10 - Electrical Site Plan

(Attachment 18)

- a. Revised Single Line Diagram to show backfeed of Building E.
- b. Provided routing of new and existing conduit for backfeed of Building E.
- c. Revised Single Line Diagram Plan Note 1.
- d. Revised Plan Notes 13 through 18.
- e. Added Plan Notes 19 through 21.
- f. Revised conduit callout for future EV Chargers from 2" C.O. to 1 1/4" C.O.
- g. Revised routing of EV Charger conduit and lighting conduits to go under canopy at Building B to panel DSB.

O. Sheet P0.01 - Legends and Notes

(Attachment 19)

a. Details 1, 2 and 3 were removed from this sheet and relocated to the newly added sheet P2.01 - Details.

P. Sheet P0.10D - Plumbing Site Demolition plan

(Attachment 20)

- a. Added demolition scope for existing gas pipe running over canopy.
- b. Added demolition scope for existing gas pipe serving existing building E.

Q. Sheet P0.10 - Plumbing Site plan

(Attachment 21)

- a. Added new gas pipe to come up next to building and up to existing canopy cover for new point of connection.
- b. Added a 1" branch from 2" underground gas to serve existing Building E.

ITEM #1.8: The following New Drawings are issued:

A. Sheet P2.01 - Details

(Attachment 22)

- a. Details 1, 2 and 3 from sheet P0.01 were relocated to this sheet.
- b. Added details 4 5 and 6 to cover re-route of new gas pipes and underground installation.
- B. Sheet 1 of 2 Street Improvement Plan

(Attachment 23)

- a. Off-site Improvement Plans for work within the public Right of Way.
- b. The contractor shall be responsible for obtaining permits from the City of Grand Terrace.
- c. The contractor shall be responsible for scheduling off-site inspections with the City of Grand Terrace.
- C. Sheet 2 of 2 Street Improvement Plan (Attachment 24)
 - a. Drawing showing off-site improvements.

MISCELLANEOUS:

Item 1.9: See added Items:

A. Project Phasing Plan

(Attachment 25)

- a. Phasing Plan shows what work is to be completed prior to school starting (August 1, 2024).
- B. GTES Util-Locate Subsurface Utility Map (Attachment 26)
- C. 2023 Summer Exterior Paint Remodel at Grand Terrace Elementary School Rendering

 a. School rendering is to be used to specify exterior paint colors.
 (Attachment 27)
- D. CJUSD 2023-24 Academic Calendar (Attachment 28)

ATTACHMENTS TO ADDENDUM:

Attachment 1 - MTGL letter dated May 28, 2024, Recommendations for Pavement Structural Sections

Attachment 2 - Hazardous Materials Survey

Attachment 3 – Table of Contents (Page 2 of 3)

Attachment 4 - Specification Section 09 91 13 Exterior Painting

Attachment 5 - Sheet G0.00 - Title Sheet

Attachment 6 - Sheet C-2.1 - Topographic Map

Attachment 7 - Sheet C-2.2 - Topographic Map

Attachment 8 - Sheet C-3.1 - Precise Grading Plan

Attachment 9 - Sheet C-3.2 - Precise Grading Plan

Attachment 10 - Sheet C-4.1 - Composite Utility Plan

Addendum 1 Grand Terrace ES – New Parking Lot Page 8 of 8

Attachment 11 - Sheet C-4.2 - Composite Utility Plan Attachment 12 - Sheet C-5.1 - Horizontal Control Plan Attachment 13 - Sheet C-5.2 - Horizontal Control Plan Attachment 14 - Sheet A0.10 - Overall Site Plan Attachment 15 - Sheet A1.11 - Site Plan-Enlarged Demolition Attachment 16 - Sheet A1.12 - Site Plan-Enlarged Remodel Attachment 17 - Sheet A1.23 - Site Details-Fencing Attachment 18 - Sheet E0.10 - Electrical Site Plan Attachment 19 - Sheet PO.01 - Legends and Notes Attachment 20 - Sheet P0.10D - Plumbing Site Demolition Plan Attachment 21 - Sheet PO.10 - Plumbing Site Plan Attachment 22 - Sheet P2.01 - Legends and Notes Attachment 23 - Sheet 1 of 2 - Street Improvement Plan Attachment 24 - Sheet 2 of 2 - Street Improvement Plan Attachment 25 - Sheet A0.11 - Project Phasing Plan Attachment 26 - GTES Util-Locate Subsurface Utility Map Attachment 27 - 2023 Summer Exterior Paint Remodel at Grand Terrace Elementary School Rendering Attachment 28 - CJUSD 2024-25 Academic Calendar

End of Addendum 1

SGH Architects

Michael J. Stephens, AIA, NCARB Managing Partner Architect C-26450





GEOTECHNICAL ENGINEERING CONSTRUCTION INSPECTION MATERIALS TESTING ENVIRONMENTAL

OFFICE LOCATIONS

ORANGE COUNTY
CORPORATE BRANCH

2992 E. La Palma Avenue Suite A Anaheim, CA 92806

Tel: 714.632.2999 Fax: 714.632.2974

SAN DIEGO IMPERIAL COUNTY

6295 Ferris Square Suite C San Diego, CA 92121

Tel: 858.537.3999 Fax: 858.537.3990

INLAND EMPIRE

14467 Meridian Parkway Building 2A Riverside, CA 92518

Tel: 951.653.4999 Fax: 951.653.4666

OC/LA/INLAND EMPIRE
DISPATCH

800.491.2990

SAN DIEGO DISPATCH

888.844.5060

www.mtglinc.com



May 28, 2024

Kenny Porter Colton Joint Unified School District 1212 Valencia Drive Colton, California 92324 MTGL Project No. 1773A03 MTGL Log No.: 24-0173

MTGL Branch: Riverside

Subject: RECOMMENDATIONS FOR PAVEMENT STRUCTURAL SECTIONS

1

Grand Terrace Elementary School – Southeastern Parking Lot

12066 Vivienda Avenue

Grand Terrace, California 92313

Dear Kenny,

In accordance with your request, pavement structural sections have been prepared for the subject project. Previous laboratory testing of samples obtained by our representative from the site indicate that the subgrade soils have a Resistance (R) Value of 21 (MTGL, 2023). The results of our laboratory tests are attached to this report.

Recommended pavement structural sections are based on the procedures outlined in the design procedures for pavements of the Highway Design Manual, California Transportation Department. This procedure uses the principle that the pavement structural section must be of adequate thickness to distribute the load from the design traffic (TI) to the subgrade soils in such a manner that the stresses from the applied loads do not exceed the strength of the soil (R value). The recommended structural sections are as follows:

ASPHALT PAVEMENT STRUCTURAL SECTIONS

Pavement Area	Traffic Index	Asphalt (inches)	Aggregate Base (inches)
Parking Areas	5.0	4	5
Driveways	6.0	4	9
Truck/Fire Access Lanes	7.0	4	12

Project No. 1773A03 MTGL Log No. 24-0173 May 28, 2024

PORTLAND CEMENT CONCRETE (PCC) PAVEMENT STRUCTURAL SECTION

Pavement	Traffic	PCC Pavement (inches)	Aggregate Base
Area	Index		(inches)
Concrete Pavement (min f'c = 4,500 psi)	5.0 – 8.0	7½	4

Areas beneath proposed pavements will require a minimum depth of 12 inches of removal and recompaction to 95% relative compaction in accordance with ASTM D1557. The exposed excavation bottom should be scarified to a minimum depth of 6 inches, moisture conditioned, and recompacted to 90% relative compaction. Any soft or yielding areas should be removed and replaced with compacted fill or aggregate base.

The aggregate base course should conform to the latest "Greenbook" Standard Specifications for Public Works Construction for crushed aggregate base or crushed miscellaneous base, or to the latest Caltrans Standard Specifications for class II aggregate base. All aggregate base should be compacted to at least 95% relative compaction. Aggregate base should have an R-value of not less than 78. All materials and methods of construction should conform to good engineering practices.

The findings, conclusions, and recommendations contained in this report are based on the site conditions as they existed at the time of our investigation, and further assume that the subsurface conditions encountered during our investigation are representative of conditions throughout the site. Should subsurface conditions be encountered during construction that are different from those described in this report, this office should be notified immediately so that our recommendations may be re-evaluated.

We appreciate this opportunity to be of continued service to you on this project. Should you have any questions regarding this report, please do not hesitate to contact us at your convenience.

Greg Wilson, P.G., C.E.G.

Senior Geologist

Respectfully Submitted,

MTGL, Inc.

Isaac Chun, P.E., G.E.

Vice President

Attachments:

Appendix A – References

Appendix B – Laboratory Test Results

Distribution: Addressee via email: <u>kenneth_porter@cjusd.net</u>

Owen Chang via email: owen-chang@cjusd.net

APPENDIX A

REFERENCES

MTGL Project No. 1773A03 MTGL Log No. 24-0173 May 28, 2024

APPENDIX A


REFERENCES

- 1. MTGL, Inc., 2023, Pavement Investigation, Grand Terrace Elementary School, MTGL Project No. 7575A01, MTGL Log No. 23-0241, dated July 24.
- 2. SGH Architects, 2024, Plans for Grand Terrace Elementary School New Parking Lot, Colton Joint Unified School District, 12066 Vivienda Avenue, Grand Terrace, CA, DSA #04-122929, dated April 19.

APPENDIX B

LABORATORY TEST RESULTS





Resistance R-Value and Expansion Pressure - ASTM D2844

No.	Compact. Pressure psi	Density pcf	Moist. %	Expansion Pressure psi	Horizontal Press. psi @ 160 psi	Sample Height in.	Exud. Pressure psi	R Value	R Value Corr.
1	200	115.8	15.2	0.06	95	2.60	257	19	20
2	250	119.9	13.8	0.03	90	2.58	338	21	22
3	300	123.3	11.9	0.06	60	2.53	678	36	36

Test Results	Material Description		
R-value at 300 psi exudation pressure = 21	Sandy SILT (ML) - Brown (Sandy		
Exp. pressure at 300 psi exudation pressure = 0.04 psi	Loam)		
Project No.: 7575A01	Tested by: JAG		
Project: GRAND TERRACE E.S.	Checked by: I. CHUN		
Location: B5 @ 1/2'-3'	Remarks:		
Sample Number: 23-8805 Depth: 1/2'-3'	SAMPLED BY JAY ROWERDINK		
Date: 7/13/2023			
R-VALUE TEST REPORT			
MTGL, Inc.	23-8805		



June 5, 2024

Kenneth Porter via email: kenneth_Porter@cjusd.net
Project Manager Facilities, Planning, and Construction
Colton Joint Unified School District
325 Hermosa Avenue, Building 5
Colton, CA 92324

RE:

Limited Asbestos and Lead Paint Survey
Grand Terrace Elementary School – Buildings B, C, D - Exteriors
12066 Vivienda Avenue
Grand Terrace, California 92313
B2 Environmental Project #40007.0043

Dear Mr. Porter:

B2E was retained by the Colton Joint Unified School District to conduct a limited asbestos and lead materials survey of suspect asbestos-containing materials (ACM) and suspect lead paint, at the Grand Terrace Elementary School located at 12066 Vivienda Avenue, Grand Terrace, California. The asbestos and lead materials survey was limited to the exteriors of Buildings B, C, D, that will be impacted by the Exterior Modernization project.

Survey Summary – Asbestos

On May 16, 2024, B2E inspector Richard Garcia, a California Certified Site Surveillance Technician (CSST# 96-1908) under the direction of Raul Garcia, California Certified Asbestos Consultant (CAC# 05-3783) collected twenty-nine (29) asbestos bulk samples (including layers) from the exterior of buildings B, C, D.

Prior to sampling, B2E's inspector walked the exterior building areas, to verify which areas/materials would need to be investigated and sampled. B2E's inspector then identified homogeneous areas to facilitate a sampling strategy. Homogeneous area means an area of surfacing material, thermal system insulation material, or miscellaneous material that is uniform in color and texture. The actual number of samples collected from each homogeneous sampling area varies, dependent upon material type and the professional judgment of the inspector.

B2E's sampling strategy incorporated the Asbestos Hazard Emergency Response Act (AHERA) requirements, quantities of the suspect material, and the inspector's judgment to aid in the identification of the suspect asbestos-containing material (ACM).

B2E's sampling strategy was to identify and collect the accessible suspect ACM in accordance with the AHERA (40 CFR, Part 763, Subpart E) sampling protocols. Actual collection of a bulk asbestos sample involves physically removing approximately one square inch (1 in²) or more of the material and placing it in an airtight sample container marked with a unique identification number.

The current asbestos investigation and bulk sampling performed was limited to those buildings and areas which may be impacted by the current scheduled Exterior Modernization project.

Micron Environmental Labs, Inc. (NVLAP #200294-0) located at 3565 Lexington Avenue, El Monte, California (626 454-4782) analyzed the asbestos bulk samples using polarized light microscopy (PLM). PLM analysis utilizes dispersion staining techniques (ref.: USEPA Method 600/R-93/116) to determine the asbestos content of the bulk samples collected at the site.

The following table is a summary of the suspect ACM that have been determined, through laboratory analysis and/or assumed, to contain asbestos:

GRAND TERRACE ELEMENTARY SCHOOL 12066 VIVIENDA AVE., GRAND TERRACE, CA EXTERIOR MODERNIZATION PROJECT

ASBESTOS CONTAINING MATERIALS

MATERIAL	LOCATION	SAMPLE NUMBERS	SCAQMD CLASS	CAL/OSHA CLASS	FRIABLE	ASBESTOS CONTENT
Exterior Texture Coat (on Concrete Walls)	Building C – Exterior Concrete Walls	N/A	ı	I	NF/F	PACM
Exterior Texture Coat (on Concrete Walls)	Building D – Exterior Concrete Walls	N/A	I	I	NF/F	PACM

SF = Square Feet, NA = Not Applicable, LF = Linear Feet

F=Friable NF=Non-Friable NF/F=Currently Non-Friable but becomes Friable when disturbed

PACM - Presumed Asbestos-Containing Material - Presumed ACM until sample results prove otherwise.

Actual Impact Quantities are unknown and need to be verified by the scope of work in the bid drawings.

In accordance with the South Coast Air Quality Management District (SCAQMD) Rule 1403, any material that contains greater than one percent (1.0%) asbestos is considered an asbestoscontaining material (ACM) and is categorized as either friable ACM or non-friable ACM. There are two categories of non-friable materials: Class I non-friable ACM and Class II non-friable ACM.

- Class I non-friable ACM is any asbestos-containing material that, when dry, can be broken, crumbled, pulverized, or reduced to powder in the course of demolition or renovation activities. Actions which may cause material to be broken, crumbled, pulverized, or reduced to powder include physical wear and disturbance by mechanical force, such as, but not limited to, sanding, sandblasting, cutting or abrading, improper handling or removal or leaching of matrix binders. Class I nonfriable asbestos-containing material includes, but is not limited to, fractured or crushed asbestos cement products, transite materials, mastic, roofing felts, roofing tiles, cement water pipes and resilient floor covering.
- Class II non-friable ACM is all other material containing more than one percent (1%) asbestos that is neither friable nor Class I non-friable.

⁽¹⁾ Friable-The classification is based upon the existing material condition and/or the potential condition of the material to change when disturbed in accordance with applicable regulatory definitions.

Cal/OSHA assigns classes of work to materials, and activities in order to differentiate between the required work practices and engineering controls, including operations and maintenance, and custodial activities performed on or around ACM.

- Class I: activities involving the removal of TSI and surfacing ACM.
- Class II: activities involving the removal of ACM which is not TSI or surfacing material.
- Class III: repair and maintenance operations, in which ACM (including TSI, surfacing, and miscellaneous materials) is likely to be disturbed.
- Class IV: maintenance and custodial activities during which employees contact, <u>but</u> do not disturb ACM and activities to clean up dust, waste, and debris resulting from Class I, II, and III activities.

Any material that contains greater than one tenth of one percent (0.1%) but less than or equal to one percent (1.0%) asbestos (>0.1% $x \le 1.0$ %) is considered by CAL/OSHA as an asbestos containing construction material (ACCM). ACCM is to be handled by California DOSH asbestos registered contractors, employing asbestos certified workers, and supervisors, using the minimum engineering controls as required by OSHA/Cal-OSHA.

The following table is a summary of the suspect ACM that have been determined, through laboratory analysis, to <u>not</u> contain asbestos:

GRAND TERRACE ELEMENTARY SCHOOL 12066 VIVIENDA AVE., GRAND TERRACE, CA EXTERIOR MODERNIZATION PROJECT NON-ASBESTOS CONTAINING MATERIALS						
MATERIAL	LOCATION	SAMPLE NUMBERS				
Exterior Stucco – Gray Stucco (Basecoat) / Beige, Peach, Green Finish Coat / Brown Barrier Paper	Building B – Exterior Walls	S01 to S07				
Black Window Putty (with Residual White Paint)	Building B - Exterior Windows	WP01 to WP05				
Black Window Putty (with Residual White Paint)	Building C – Exterior Windows	WP06 to WP10				

Conclusions/Recommendations - Asbestos

Black Window Putty (with

Residual White Paint)

As a result of the current survey no asbestos-containing materials, or asbestos-containing construction materials (ACCM) were identified at the buildings/areas surveyed, within the defined scope of work, however the exterior texture coating (on concrete walls) at Buildings C and D is presumed to contain asbestos until sample results are received.

Building D – Exterior Windows

WP11 to WP15

B2E recommends sampling of any suspect asbestos-containing material that may potentially be disturbed by the Exterior Modernization project that has not been identified in this report or was not part of our scope of work.

B2E recommends that all asbestos-containing materials identified in this report that will be impacted or have the potential for being impacted by the Exterior Modernization project activities be properly abated in accordance with all federal, state, and local asbestos regulations, prior to the renovation/demolition activities.

Survey Summary - Lead

Lead paint sampling was conducted to assist with compliance with the CAL/OSHA regulations for lead (CCR Title 8 Section 1532.1), by verifying the presence or absence of elemental lead materials which may be present, involved in, or impacted by any scheduled renovation/demolition activities. The lead paint sampling was conducted for Cal-OSHA compliance purposes in order to provide information on the presence and content of elemental lead-containing paint which could lead to potential personal exposure during renovation/demolition activities. In addition, the lead paint sampling was also conducted to assist in eliminating the potential creation of lead hazards associated with any renovation/demolition activities.

The suspect lead samples were collected on May 16, 2024, by B2E inspectors Armando Garcia, a California Department of Public Health Lead Sampling Technician (LRC-00007469) and Yaritzie Moreno, a California Department of Public Health Lead Sampling Technician (LRC-00011842).

The suspect lead samples were collected using wet methods and a cutting/scraping method. The sample tool was wet wiped after each sampling process. The suspect lead paint samples were placed into pre-labeled sample bags and sealed. The samples were then sent to an independent third-party laboratory, Micron Environmental Labs, Inc. located at 3565 Lexington Avenue, El Monte, California, for analysis utilizing EPA Method SW 846 3050B/7420 for lead.

The following table presents the components identified as being coated with lead-based paint and/or lead-containing paint:

GRAND TERRACE ELEMENTARY SCHOOL 12066 VIVIENDA AVE., GRAND TERRACE, CA EXTERIOR MODERNIZATION PROJECT LEAD PAINT MATERIALS								
MATERIAL / COMPONENT	COLOR(S)	Sample PPM 9/ Pv						
LBP - Wood Window Frames	Beige	Building B – Exterior Window Frames	IT	Pb-01	17751	1.775		
LCP – Stucco Walls	Beige	Building B – Exterior Walls	LD	Pb-02	113	0.011		
LCP – Concrete Walls	Beige	Building C – Exterior Concrete Walls	LD	Pb-04	1494	0.149		
LBP – Metal Fascia	Blue	Building C – Exterior Fascia	LD	Pb-06	61186	6.119		

GRAND TERRACE ELEMENTARY SCHOOL 12066 VIVIENDA AVE., GRAND TERRACE, CA EXTERIOR MODERNIZATION PROJECT

LEAD PAINT MATERIALS

MATERIAL / COMPONENT	COLOR(S)	LOCATION	Condition	Sample #	PPM (mg/kg)	% By Wt.
LCP – Concrete Walls	Beige	Building D – Exterior Concrete Walls	LD	Pb-08	1940	0.194
LBP – Wood Window Frames	Beige	Building D – Exterior Window Frames	IT	Pb-09	10763	1.076
LBP – Metal Fascia	Blue	Building D – Exterior Fascia	LD	Pb-11	57962	5.796
PLB – Door Frames	Beige	Buildings B, C, D – Exterior Door Frames	ΙΤ	N/A	N/A	N/A
PLB – Metal A/C Units	Beige	Building B, C, D – Exterior A/C Units	ΙΤ	N/A	N/A	N/A
PLB –Wood Fascia	Blue	Buildings C& D - Upper Roof level Fascia	LD	N/A	N/A	N/A
PLB - Wood Overhang Panels	Beige	Buildings C & D – Exterior Upper Overhangs	IT	N/A	N/A	N/A
PLB – Metal Posts and Downspouts	Blue, Yellow	Buildings C & D – Exterior	ΙΤ	N/A	N/A	N/A
PLB – Metal Electrical Conduits	Beige	Buildings B, C, D – Exterior at Walls	ΙΤ	N/A	N/A	N/A
PLB - Metal Corrugated Overhang and Framing	Beige	Buildings C & D – Exterior Lower Overhangs	LD	N/A	N/A	N/A
PLB - Metal Fascia	Blue	Building B – Upper Roof Level Fascia	LD	N/A	N/A	N/A
PLB – Metal/Concrete Panels	Beige	Buildings C, D – Exterior	IT	N/A	N/A	N/A
PLB - Metal Panels	Blue	Buildings C, D – Exterior by Posts	IT	N/A	N/A	N/A

PPM = Parts Per Million % By Wt. = Percent by Weight

Actual Impact Quantities are unknown and need to be verified by the scope of work in the bid drawings

The following table is a summary of the suspect Lead Paint that has been determined, through laboratory analysis, to be below the detection limit for lead:

⁽¹⁾ **Materials/Components -** LBP=Lead-Based Paint (≥5,000 ppm), PLB=Presumed Lead-Based, LCP=Lead-Containing Paint (<5,000 ppm), PLC=Presumed Lead-Containing Paint

IT - Intact DF - Defective LD - Localized Damage

GRAND TERRACE ELEMENTARY SCHOOL 12066 VIVIENDA AVE., GRAND TERRACE, CA EXTERIOR MODERNIZATION PROJECT

NON-LEAD MATERIALS (LESS THAN DETECTION LIMIT)

	(
SUBSTRATE	COLOR(S)	COMPONENT	COMPONENT LOCATION				
Metal	Blue	Door	Building B – Exterior Doors	Pb-03			
Wood	Beige	Window Frame	Building C - Exterior Window Frames	Pb-05			
Metal	Blue	Door	Building C – Exterior Doors	Pb-07			
Metal	Blue	Door	Building D – Exterior Doors	Pb-10			

Conclusions/Recommendations - Lead

B2E recommends sampling of any suspect lead paint material that may be disturbed by the Exterior Modernization project activities that has not been identified in this report or was not part of our scope of work.

B2E recommends that surfaces/components with detectable lead levels identified in this report that have the potential for being impacted by the Exterior Modernization project activities, and which may cause occupational exposures to lead, and/or create a potential lead hazard, be properly removed (e.g., paint removal, component removal) and/or stabilized in accordance with federal, state and local lead regulations. Additionally, B2E recommends that all loose & flaky paint be properly stabilized prior to the Exterior Modernization project activities.

Lead waste generated by renovation or demolition activities must be profiled and disposed of properly as required by the California Department of Toxics Substance Control, CCR Title 22, Division 4.5 (CA DTSC). Chemical Profile Tests, Total Threshold Limit Concentration (TTLC), Soluble Threshold Limit Concentration (STLC) and/or Toxic Characteristic Leaching Procedure (TCLP) are to be performed on the waste containing lead generated by lead-related construction activities or assumed to be a federal hazardous waste.

The results, findings, conclusions, and recommendations expressed in this report are based solely on conditions noted during B2E's inspection of the site. As the user of this report, the Client and respective contractors are advised of the following limitations on the information presented in this report.

- This report is intended for the sole use of the Client. The scope of services performed in execution of this evaluation may not be appropriate to satisfy the needs of other users and use or re-use of this document or the findings, conclusions, or recommendations is at the risk of said user.
- 2. B2E did not perform destructive sampling -- it was not within B2E's scope of work to remove surface materials to investigate portions of the structure or materials that may lay beneath the surface -- thus, any materials that could not be visually identified on the surface were not inspected and would not be noted in this report.

- 3. The asbestos and lead sampling was performed in a manner consistent with the level of care and skill ordinarily exercised by environmental professionals practicing contemporaneously under similar conditions in the area of the project in question. No other warranty, express or implied, is given and all other warranties are hereby expressly disclaimed. This report does not warrant against future operations or conditions, nor does it warrant against operations or conditions present of a type or at a location not investigated.
- 4. This report is not a comprehensive site evaluation and should not be construed as such. Only the materials to be impacted by the current scheduled Exterior Modernization project in the buildings/areas surveyed are included in this report.

Thank you for this opportunity to be of service to the Colton Joint Unified School District. If you have any questions, please feel free to contact us at (626) 507-7161.

Sincerely,

B2 Environmental, Inc.

Raul Garcia

Regional Manager

California CAC #05-3783

Appendix A – Asbestos Laboratory Analytical Results

Appendix B - Lead Bulk Analytical Results

Appendix C - Sample Location Maps

Appendix D - Qualifications

APPENDIX A

ASBESTOS LABORATORY ANALYTICAL RESULTS



Micron Environmental Labs, Inc.

3565 Lexington Ave • El Monte, California 91731 • Phone (626) 454-4782 • Fax (626) 602-9661

Report Date: May 21, 2024

B2 Environmental Attn: Raul Garcia 1773 W San Bernardino Rd, Ste B28 West Covina, CA 91790

Subject: PLM Report for Analysis of Bulk Samples

Laboratory Report #: 11724048

Client Reference: 40007.0043/Colton Joint Unified School District/Grand Terrace E.S.

12066 Vivienda Avenue, Grand Terrace, CA 92313

Dear B2 Environmental,

This report is a summary of the analytical results for 29 bulk sample(s) received by the laboratory on 5/20/2024.

The analyses were conducted using polarized light microscopy (PLM) in accordance with EPA Test Method 600/M4-82-020 as of The Determination of Asbestos in Bulk Insulation Samples as presented in 40 CFR Appendix E to Subpart E of Part 763 (7-01-07 Edition) and EPA Interim Test Method 600/R-93/116 (July 1993). Quantification of percent content is by Calibrated Visual Estimation (CVES) expressed in units of percent area. Samples that contain distinct separable layers are analyzed by layer unless a composite has been requested. The laboratory analyzes samples submitted according to the customer submitted sample log and will analyze additional layers (when observed) upon request. CVES are calibrated using standard reference materials as part of the laboratory's internal and external quality control and proficiency programs. Micron Environmental recommends the use of Transmission Electron Microscopy (TEM) for samples comprised of non-friable organic binder when asbestos is not detected by PLM, as fibers may exist in these matrices but below the resolution capability of the polarized light microscope.


Micron Environmental labs, Inc. is accredited by the NIST National Voluntary Laboratory Accreditation Program (NVLAP), laboratory code 200294-0 and California's Environmental Laboratory Accreditation Program (Waterboards), laboratory code 2297, International Accreditation Service (IAS) 2016 TNI-2 for this analysis. Micron Environmental Labs, Inc. is responsible for the accuracy in this report, but is not liable for the accuracy of sample information supplied to us by the customer or for the interpretation of this report. Samples are tested in as-received condition and may be affected by external factors and/or handling prior to submittal to Micron. Unless otherwise noted, samples were received in acceptable condition. Samples are retained for a period of thirty days unless otherwise specified or requested by the customer.

This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, IAS or any agency of the US Government. Micron Environmental Laboratories, Inc. is committed to customer confidentiality and will not share information regarding this report or related affiliations to a third party without express approval from the customer, unless required to do so by law. In the event we are legally required to share confidential information, the customer will be notified of the specific information that was shared.

Should you have any questions regarding the reported results or analytical methods used to derive them, please feel free to contact the laboratory at (626) 454-4782. Thank you for choosing Micron Environmental Labs, Inc. for your testing needs.

Sincerely,

Daniel Gamez Laboratory Director



Micron Environmental Labs, Inc.

El Monte, CA 91731 FAX: 626-602-9661

Reference Analytical Methods: 40CFR763 App E to Subpart E EPA 600/R-93/116 NIST-NVLAP Lab Code No. 200294-0 California ELAP Waterboards Cert. No. 2297

Microscopist: Rasha Abdelmalak

100% Mineral Filler

IAS No. ELP-327

Χ

Χ

Χ

Test Report Bulk Asbestos by PLM

<u>Micron Report No.</u> 11724048 *Report Date:* May 21, 2024

Cust. Project: 40007.0043/Colton Joint Unified School District/Grand Terrace E.S.

12066 Vivienda Avenue, Grand Terrace, CA 92313

12000 tillonaa tilonao, otaha 1011aoo, otto2010

Customer: Raul Garcia Date Collected: 5/16/2024

B2 Environmental Date Received: 5/20/2024
1773 W San Bernardino Rd, Ste B28 Date Analyzed: 5/21/2024

West Covina, CA 91790 No. of Samples: 29

Cust ID No. Asbestos

Micron ID No. Sample Description and Location Detected? Analytical Results QC'd?

S 01 Grey Stucco No

1061938 Building B Exterior Wall N Throughout Exterior Walls Of Building B

Layer#:1 Building B

Comments:

Sample Color: grey

S 01 Beige, Peach, & Green Finish Coat No 100% Mineral Filler

1061938 Building B Exterior Wall N Throughout Exterior Walls Of

Layer#: 2 Building B

Sample Color: green,beige

Comments:

\$ 01 Brown Barrier Paper No 100% Cellulose

1061938 Building B Exterior Wall N Throughout Exterior Walls Of

Layer#: 3 Building B

Sample Color: brown

Comments:

S 02 Grey Stucco No 100% Mineral Filler

1061939 Building B Exterior Wall E Throughout Exterior Walls Of

Layer#:1 Building B

Sample Color: grey

Comments:

S 02 Beige, Peach, & Green Finish Coat No 100% Mineral Filler

2 of 6

1061939 Building B Exterior Wall E Throughout Exterior Walls Of

Layer#: 2 Building B

Sample Color: green,beige

Comments: No barrier paper found.

Report_MEL_A009 Rev. 3, 08/31/2020

Report Date: May 21, 2024

Microscopist: Rasha Abdelmalak

Cust ID No. Micron ID No.	Sample Description and Location	Asbestos Detected?	Analytical Results	QC'd?
S 03 1061940 Layer#:1	Grey Stucco Building B Exterior Wall SE Throughout Exterior Walls Of Building B	No	100% Mineral Filler	
Sample Color:	grey			
Comments:				
S 03 1061940 Layer#:2	Beige, Peach, & Green Finish Coat Building B Exterior Wall SE Throughout Exterior Walls Of Building B	No	100% Mineral Filler	
Sample Color:	green,beige			
Comments:				
S 03 1061940 Layer#:3	Brown Barrier Paper Building B Exterior Wall SE Throughout Exterior Walls Of Building B	No	100% Cellulose	
Sample Color:	brown			
Comments:				
S 04 1061941 Layer#:1	Grey Stucco Building B Exterior Wall SW Throughout Exterior Walls Of Building B	No	100% Mineral Filler	
Sample Color:	grey			
Comments:				
S 04 1061941 Layer#:2	Beige, Peach, & Green Finish Coat Building B Exterior Wall SW Throughout Exterior Walls Of Building B	No	100% Mineral Filler	
Sample Color:	green,beige			
Comments:				
S 04 1061941 Layer#:3	Brown Barrier Paper Building B Exterior Wall SW Throughout Exterior Walls Of Building B	No	100% Cellulose	
Sample Color:	brown			
Comments:				
S 05 1061942 Layer#:1	Grey Stucco Building B Exterior Wall W Throughout Exterior Walls Of Building B	No	100% Mineral Filler	
Sample Color:	grey			
Comments:				

of 6

Report_MEL_A009 Rev. 3, 08/31/2020

Report Date: May 21, 2024

Microscopist: Rasha Abdelmalak

Cust ID No. Micron ID No.	Sample Description and Location	Asbestos Detected?	Analytical Results	QC'd?
S 05 1061942 Layer#:2	Beige, Peach, & Green Finish Coat Building B Exterior Wall W Throughout Exterior Walls Of Building B	No	100% Mineral Filler	
Sample Color:	green,beige			
Comments				
S 05 1061942 Layer#:3	Brown Barrier Paper Building B Exterior Wall W Throughout Exterior Walls Of Building B	No	100% Cellulose	
Sample Color:	brown			
Comments				
WP 01 1061943 Layer#:	Black Window Putty On Wood Window Frame Bldg. B Exterior Wall N N & S Exterior Walls Of Bldg. B	No	20% Cellulose 80% Organic Binders	
Sample Color:	black			
Comments				
WP 02 1061944 Layer#:	Black Window Putty On Wood Window Frame Bldg. B Exterior Wall S N & S Exterior Walls Of Bldg. B	No	20% Cellulose 80% Organic Binders	
Sample Color:	black			
Comments				
WP 03 1061945 Layer#:	Black Window Putty On Wood Window Frame Bldg. B Exterior Wall SW N & S Exterior Walls Of Bldg. B	No	20% Cellulose 80% Organic Binders	
Sample Color:	black			
Comments				
WP 04 1061946 Layer#:	Black Window Putty On Wood Window Frame Bldg. B Exterior Wall NW N & S Exterior Walls Of Bldg. B	No	20% Cellulose 80% Organic Binders	
Sample Color:	black			
Comments				
WP 05 1061947 Layer#:	Black Window Putty On Wood Window Frame Bldg. B Exterior Wall NE N & S Exterior Walls Of Bldg. B	No	20% Cellulose 80% Organic Binders	
Sample Color:	black			
Comments				

Report Date: May 21, 2024

Microscopist: Rasha Abdelmalak

Cust ID No. Micron ID No.	Sample Description and Location	Asbestos Detected?	Analytical Results	QC'd?
WP 06 1061948	Black Window Putty On Wood Window Frame Bldg. C Exterior Wall N Bldg. C Exterior N Wall	No	20% Cellulose 80% Organic Binders	
Layer#:				
Sample Color:	black			
Comments	:			
WP 07	Black Window Putty On Wood Window Frame	No	20% Cellulose	
1061949	Bldg. C Exterior Wall E Bldg. C Exterior N Wall		80% Organic Binders	
Layer#:				
Sample Color:	black			
Comments	:			
WP 08	Black Window Putty On Wood Window Frame	No	20% Cellulose	
1061950	Bldg. C Roof Lvl. Ext. Wall SE Corner Bldg. C Ext. SE		80% Organic Binders	
Layer#:	Corner On S Wall Roof LvI			
Sample Color:	black			
Comments	:			
WP 09	Black Window Putty On Wood Window Frame	No	20% Cellulose	
1061951	Bldg. C Roof Level Ext. Wall SE Center Bldg. C Ext. SE		80% Organic Binders	
Layer#:	Corner On S Wall Roof Level			
Sample Color:	black			
Comments	:			
WP 10	Black Window Putty On Wood Window Frame	No	20% Cellulose	
1061952	Bldg. C Exterior Wall NW Bldg. C Exterior N Wall		80% Organic Binders	
Layer#:				
Sample Color:	black			
Comments	:			
WP 11	Black Window Putty On Wood Window Frame	No	20% Cellulose	
1061953	Bldg. D Exterior Wall NW Corner Bldg. D Exterior N Wall		80% Organic Binders	
Layer#:				
Sample Color:	black			
Comments	:			
WP 12	Black Window Putty On Wood Window Frame	No	20% Cellulose	
1061954	Bldg. D Exterior Wall NW Center Bldg. D Exterior N Wall		80% Organic Binders	
Layer#:				
Sample Color:	black			
Comments	:			

Report Date: May 21, 2024

Microscopist: Rasha Abdelmalak Micron Report No.: 11724048

Cust ID No. Micron ID No.	Sample Description and Location	Asbestos Detected?	Analytical Results	QC'd?
WP 13 1061955	Black Window Putty On Wood Window Frame Bldg. D Exterior Wall N Bldg. D Exterior N Wall	No	20% Cellulose 80% Organic Binders	
Layer#:				
Sample Color:	black			
Comments:				
WP 14	Black Window Putty On Wood Window Frame	No	20% Cellulose	
1061956	Bldg. D Exterior Wall NE Center Bldg. D Exterior N Wall		80% Organic Binders	
Layer#:				
Sample Color:	black			
Comments:				
WP 15	Black Window Putty On Wood Window Frame	No	20% Cellulose	
1061957	Bldg. D Exterior Wall NE Corner Bldg. D Exterior N Wall		80% Organic Binders	
Layer#:				
Sample Color:	black			
Comments:				

The limit of detection for this test method is less than one percent (<1%) asbestos by calibrated visual area estimate.

1/724048 **23**

Page 1 of 2

ASBESTOS BULK SAMPLE SHEET / COC

Client Name: Colton Joint Unified School District

Project Location: 12066 Vivienda Avenue, Grand Terrace, CA 92313 - Grand Terrace E.S.

Date: 05/16/2024 Sampled By: Richard G/Armando G/Yaritzie M

Project Number: 40007.0043 Priority: 24 HR X 72 HR

Analytical Method: PLM: X TEM: Other: Email to: Richard@b2e.com

HA NUMBER	SAMPLE NUMBER	MATERIAL DESCRIPTION (Size/Color)	SAMPLE LOCATION	MATERIAL LOCATION	Friable/ Non- Friable	QUANTITY
S	01	grey stullo wl'beige, peach and green layered paint, and brown barrier paper	Building B exterior wall, N	throughout exterior walls of Building B.	NF	approx. ~2,240 sqft.
(0)	02		Building B exterior wall, E			
	03		Building B exterior wall, SE			
	04		Building B exterior wall, SW			
\	05	<u></u>	Building B exterior wall, W			
WP	01	black window putty on wood window frame w/residual white paint.	Building B, exterior wall, N	N and S exterior walls of Brilding B.		approx. ~500 ft.
	02		Building B, exterior Wall, S			
	03		Brilding B, exterior WAII, SN			
	04		Brilding B, exterior wall, NW			
1	05	1	Building B, exterior	1	1	

Relinquished By	Varitzie Moreno	Date 5/17/24	Time 17:09
Received By	Brianna Games	Date 5/20/24	Time 8:00 am
Relinquished By		Date	Time
Received By		Date	Time

ASBESTOS BULK SAMPLE SHEET / COC



Client Name: Colton Joint Unified Scho	pol District
Project Location: 12066 Vivienda Ave	enue, Grand Terrace, CA 92313 - Grand Terrace E.S.
Date: 05/16/2024	Sampled By: Richard G/Armando G/Yaritzie M
Project Number: 40007.0043	Priority:
Analytical Method: PLM: X TEM: _	Other: Email to: Richard@b2e.com

HA NUMBER	SAMPLE NUMBER	MATERIAL DESCRIPTION (Size/Color)	SAMPLE LOCATION	MATERIAL LOCATION	Friable/ Non- Friable	QUANTITY
WP	06	black window putty on wood window frame wy residual white paint	Brilding C exterior Wall, N	Building C, exterior N wall		approx.
	07		Building C exterior wall, E			
	08		Building L roof level extenor wall, SE corner	Building (, exterior se writer on swall roof level)		
	09		Brilding (roof level exterior mall, SE			
	10		Building Lextenor	Brilding C, extenor		
	11		Building D exterior wall, NW corner	Building D exterior N Wall		approx. ~510ft.
	12		Building D exterior wall, NW center			
	13		Building D extenur wall, N			
	14		Building D extenor wall, NE center			
	15		Brilding D exteror Wall, NE wrner	1	V	

Relinquished By	Varitzie Moveno	Date 5/17/24	Time 1709
Received By	Brianna Gamez	Date 5/20/24	Time 8:00 am
Relinquished By		Date	Time
Received By		Date	Time

APPENDIX B

LEAD BULK ANALYTICAL RESULTS



El Monte, CA 91731

Prep and Analytical Method: EPA SW846-3050B, EPA 7420

ERA No: M088869

CA ELAP Certificate No.: 2297

IAS #: ELP-327

Micron Environmental Labs, Inc.

Micron Ref. No.: 11724049 3565 Lexington Av. Date: 5/21/2024

Lead (Pb) in Paint - Summary Results

Project: 40007.0043 - Grand Terrace E.S. Analyst: Joseph Facundo

12066 Vivienda Ave, Grand Terrace, CA 92313

Name: B2 Environmental Date Collected: 5/17/2024
Address: 1773 W. San Bernardino Rd., Date Analyzed: 5/21/2024

City, State, Zip: West Covina, CA 91790 No. of samples: 11

Sample	Sample	Sample	Vol.	Dil.	Conc.	Res	ults
No.	Description	Mass (g)	(ml)	Factor	(mg/L)	mg/kg (ppm)	% weight
Pb-01	NE Ext. Wall Wind. Frame Bldg. B	0.1134	25	10	8.05	17751	1.775
Pb-02	E Ext. Wall, Bldg. B	0.1027	25	1	0.47	113	0.011
Pb-03	N Center Door, Bldg. B	0.1006	25	1	< 0.40	< 100	< 0.010
Pb-04	S Ext. Wall Bldg. C	0.1464	25	1	8.75	1494	0.149
Pb-05	NW Corner Ext. Wall Wind. Frame Bldg. C	0.1288	25	1	< 0.40	< 100	< 0.010
Pb-06	S Center Fascia Bldg. C	0.1036	25	19	13.35	61186	6.119
Pb-07	NE, N Wall Door Bldg. C	0.0882	25	1	< 0.40	< 113	< 0.011
Pb-08	S Ext. Wall Bldg. D	0.1387	25	1	10.76	1940	0.194
Pb-09	N Ext. Wall Wind. Frame Bldg. D	0.1359	25	9	6.50	10763	1.076
Pb-10	NE Corner Door Bldg. D	0.1338	25	1	< 0.40	< 100	< 0.010
Pb-11	S Center Roof Level Fascia Bldg. D	0.1047	25	19	12.78	57962	5.796

Analyst Signature

Daniel Gamez, Laboratory Director

ppm = parts per million. Reporting Limit = 0.400mg/L or 10ug for a sample volume of 25mL. Method Detection Limit = 0.100mg/L or 2.5ug for a sample volume of 25mL. Reporting limit is volume and mass dependent. Laboratory Control Sample (LCS) = 82.29%/ Accepted.

LEAD BULK SAMPLE LOG

1773 W. SAN BERNARDINO RD, STE B28 WEST COVINA, CA 91790 TEL 626.507.7161 FAX 626.465.0235

CLIENT: Colton Joint Unified School District

DATE:__05/16/2024

LOCATION: Grand Terrace E.S. - 12066 Vivienda Ave, PROJECT NUMBER: 40007.0043

Grand Terrace, CA 92313

SAMPLED BY: Armando Garcia/Yaritzie Moreno

CDPH NO: 1/A/M/ST - LPC - 00011842

				000	VIU
SAMPLE NUMBER	SAMPLE LOCATION	SUBSTRATE / COMPONENT	Color(s)	Location	QUANTITY (SF/LF/EA)
Pb-01	NE exterior wall window frame bidg.	wood window fame	beige	Nands exterior walls of brilding B	
Pb-02	E exterior wall, bldg. B.	exteror stucco	V	throughout exterior wall of Building B	approx. ~2250
Pb-03	N cener door, bldg. B	metal door	blue	Nands side of building B.	npprux. ~ 300 saft
Pb-04	s exterior wall bldg. C.	exterior concrete Wall	beige	throughout exterior walls of Building C	approx. ~4,335
Pb-05	NW corner extenor wall window frame	word window frame		throughout Nextenor wall and SE, S wall of Building C.	approx. ~450ft.
Pb-06	S center fascia building C.	metal fascia	blue	throughout building	
Pb-07	NE, N Wall door building C.	metal door		l	approx. ~370 saf
Pb-08	S extexior wall bldg. D.	extenor concrete wall	beige	throughout exterior	1pprox. ~2,950
Pb-09	- 	wood window frame	V	N side of Brilding	approx ~ 530 ft
Pb-10	NE corner door bldg.D.	metal door	blue	N and S side of Building D.	aporux. ~ 200 saft.

	انتيال حسبيا					
)	NE corner door bldg.D.	metal door	blue	N and S s Building i		apprux. ~ 200 saft
	NALYTICAL METHOD: LEAURINAROUND TIME; SAM			STLC TCL	.P	
D	ATA TO: E-MAIL: RAUL@B	2E.COM AND LAPAPER	WORK@B2E.C	OM PHONE' 6	26 264 2024	
SF	PECIAL INSTRUCTIONS: HAIN OF CUSTODY:	also Email: sstorer@	B2E.com &	Richard@b2e.	com	
1.	MMH. N TRANSFER SIGNAT	URE YAVIKI	e Moveno	5	117/24 - 1 DATE/TIME	709
2.	To famely TRANSFER SIGNATION	URE Britanna PRINTED N		5/	120/24 - 8. DATE/TIME	:00am
3. Pa	TRANSFER SIGNATI	URE PRINTED NA	AME		DATE/TIME	

2量 B2 ENVIRONMENTAL

LEAD BULK SAMPLE LOG

1773 W. SAN BERNARDINO RD, STE B28 WEST COVINA, CA 91790 TEL 626.507.7161 FAY 626 465 0235

TEL 626.507.7161
FAX 626.465.0235

CLIENT: Colton Joint Unified School District

DATE: 05/16/2024

LOCATION: Grand Terrace E.S. - 12066 Vivienda Ave, Project Number: 40007.0043

Grand Terrace, CA 92313

SAMPLED BY: Armando Garcia/Yaritzie Moreno

CDPH No: I/A/M/ST - UPU - 00 011842

SAMPLE SUBSTRATE / QUANTITY SAMPLE LOCATION Color(s) LOCATION NUMBER COMPONENT (SF/LF/EA) Scenter rooflevel throughout brilding metal fascia approx. blue fascia bldg. D. ~315 ft.

		100						
Ti Di Si	ANALYTICAL METHOD: LEAD: FLAME AA TT'LC STLC TCLP TURNAROUND TIME: SAME DAY 24HR 48 HR 3 DAY DATA TO: E-MAIL: RAUL@B2E.COM AND LAPAPERWORK@B2E.COM PHONE: 626.264.3024 SPECIAL INSTRUCTIONS: also Email: sstorer@B2E.com & Richard@b2e.com							
1.	1. Varitzie Moverio 5/17/24-1709 TRANSFERSIGNATURE PRINTED NAME SITURDAME SITURDAME SITURDAME							
3.	Britans Britans Britans PRINTED N TRANSFER SIGNATURE PRINTED N	AME		5/20/24 - 8 DATE/1	· <i>Wgn</i> > TIME			
P	AGE2of2							

APPENDIX C

SAMPLE LOCATION MAPS



E0.10D

11724049

PLAN NOTES:

- - EXISTING UNCERGROUND PEDESTAL MOUNTED PANELBOARDS AND EXISTING TRANSFORMER TO BE DISCONNECTED AND REMOVED, VERIFY EXACT LOCATION FIELD

APP: 04-122929 INC: REVIEWED FOR
SS D FLS D ACS D
DATE: 04/19/2024

IDENTIFICATION STAMP DIV. OF THE STATE ARCHITE

tkisc

11870 Pierce Street, Suite 160 Riverside, California 92505 951.299.4160 www.lk1sc.com

SITE PLAN GENERAL NOTES:

- CONTRACTOR SHALL EXERCISE EVITEME CAUTION IN EXCAVATING AND TRENCHANG ON THE SITE TO AVOID EXISTING DUCTS. PIPING OR CONOUTS. ETC., AND TO PREVENT HAZARDS TO PRESONED, ANOOFR COMMER TO EXIST HE EXPLAINED, ANOOFR COMMER TO EXIST HISTALLED BY ANY OTHER CONTRACTS. THE ENGINEER IS NOT RESPONSIBLE FOR THE LOCATION OF UNDERSONOUN UTILITIES OR STRUCTURES WHETHER OR NOT SHOWN OR DETAILED AND INSTALLED BY ANY OTHER CONTRACTS. TO CONTRACTOR SHALL IMMEDIATELY NOTIFY THE ENGINEER SHOULD BY CONTRACTOR SHALL IMMEDIATELY NOTIFY THE ENGINEER SHOULD BY LINKEN FROM THE CONTRACT OF THE SECONDARY OF THESE DOWNING AND AND THE CONTRACTOR SHOWN OF THE SECONDARY OF THE SECONDARY OF THE CONTRACTOR SHOWN ON SETTING.

- ALL SITE BRANCH CRUITS SHALL INCLUDE AN EOLIPMENT GROUND CONCUCTOR THAT, AT MINIMUM, MATCHES THE SIZE OF THE ASSOCIATED BRANCH CIRCUIT CONDUCTOR, WHERE MULTIPLE BRANCH CIRCUITS ARE BOUTENCROUNDED TOGETHER, THE EOLIPMENT GROUNDING CONDUCTOR SHALL MATCH THE SIZE OF THE LARGEST BRANCH CIRCUIT CONDUCTOR INGROUP.

GENERAL DEMOLITION NOTES:

- THE ELECTRICAL DRAWINGS ARE DIAGRAMMATIC ONLY. DO NOT SCALE THE ELECTRICAL DRAWINGS TO DETERMINE THE LOCATION OF EQUIPMENT OR OUTLETS. SEE ARCHITECTURAL PLANS, WHERE PROVIDED ON PROJECT, FOR EXTENT OF CEMOLITION.
- THE EXISTING CONDITIONS SHOWN ARE FROM AVAILABLE RECORD DRAWING AND SHOWN FOR REFERENCE ONLY. CONTROLTOR SHALL VERIFY ACTUAL ALTERATION, EXPENSION, RELOCATION, REPUBLIFIED AND AVERAGE OF THE INCLUDED IN CONTRACT, NO ADDITIONAL ALLOWANCE OR CHANGE ORGERS WALL BE ACCEPTED.

- CAREFULLY PROTECT ALL WALLS, TRIM, PLOORS, EQUIPMENT, UTILITY LINES AND MATERIALS. WHEN WORKING ON PINISHED SURFACES, LIMIT OAMAGE TO THE SMALLER RALE PROSPIEL AND RESTORE TO THE GRIMLAR COMOTION ALL SURFACES WHICH ARE OAMAGED BECAUSE OF THE INSTALLATION OF THIS WORK.

- ALL REMOVED MATERIALS AND EOUPMENT WHICH IS SALVAGED MATERIALS SHALL REMOVED MATERIALS AS SHALL REMOVED MATERIALS AS SHALL REMOVED MATERIALS AS SHALL REMOVED MATERIALS AND EOUPMENT ON THE PREMISES AS SINGERCIFE OR YOWNER AND MATERIALS MADERIAL PREMA MAD PROFILE THOM ADMACED. DISPOSE OF ALL PLOADCOUS MATERIAL PER GUIDELINE OF THE STATE OF COLUPTION OF THE ATTERIAL OF THE OF COLUPTION OF THE ATTERIAL PROFILE OF THE STATE OF COLUPTION OF THE ATTERIAL PROFILE OF THE STATE OF COLUPTION OF THE ATTERIAL PROFILE OF THE STATE OF COLUPTION OF THE ATTERIAL PROFILE OF THE STATE OF COLUPTION OF THE ATTERIAL PROFILE OF THE STATE OF COLUPTION OF THE ATTERIAL PROFILE OF THE STATE OF COLUPTION OF THE ATTERIAL PROFILE OF THE STATE OF THE ATTERIAL PROFILE OF THE ATTERIAL
- CONTRACTOR SHALL FIELD VERIFY EXISTING CONDUITMIRING RUNS, REUSE AS REQUIRE AND REMOVED ALL UNUSED CONQUITMIRING. UNUSED CONDUIT IN INACCESSIBLE LOCATIONS (WALLS TO REMAIN) CAN BE ABANCONED IN PLACE, REMOVE UNUSED WIRING.
- CONTRACTOR TO VERIFY CIRCUIT NUMBER AND LOADS FOR ALL EXISTING EQUIPMENT PRIOR TO INSTALLATION OF NEW OR RELOCATED ELECTRICAL EQUIPMENT, REASSION CIRCUITS AND LOADS ACCORONALLY, PROVIDE COMPLETE 'AS BUILT' CRAWINGS AND TYPEWRITTEN DIRECTORIES FOR PA
- REFER TO ARCHITECTURAL DEMOLITION DRAWING FOR DEMOLITION AREAS, THE SCOPE OF THE CEMOLITION SHALL INCLUDE ALL LABOR, ENSTING ELECTRICAL EQUIPMENT, VERIFY EXACT SCOPE PRIOR TO COMMERCING WORK, REFER TO CEMO PLAN FOR SPECIFIC AREAS NOT IN SCOPE THE SCOPE INCLUCES, BUT IN OFT LAINED TO THE FOLLOWING.
- A. LIGHTING: EXISTING LIGHTING TO REMAIN, U.O.N.
- 8. POWER: EXISTING POWER SHALL REMAIN, U.O.N.
- C. ALL EXISTING ELECTRICAL SWITCHGEAR, PANELBOARDS, PULLBOXES, EYC. SHALL REMAIN, U.O.N.
- D. SIGNAL: EXISTING SIGNAL SYSTEMS (CLOCKS, DATA OUTLETS, TELEPHON OUTLETS, TELEVISION OUTLETS, SPEAKERS, ETC.) TO REMAIN, U.O.N.
- E. FIRE ALARM: EXISTING FIRE ALARM DEVICES TO REMAIN, U.O.N.

 E. FIRE ALARM: EXISTING FIRE ALARM DEVICES TO REMAIN, U.O.N.

 CONTROLS TO REMAIN, U.O.N.
- G. EXTERIOR POWER, SIGNAL AND FIRE ALARM: EXISTING EXTERIOR POWER, SIGNAL AND FIRE ALARM DEVICES TO REMAIN, U.O.N.

- RELOCATE EXISTING CONDUITS ANO/OR CONDUCTORS/CABLING ROUTING THROUGH AREAS WHERE NEW/REMOVED WALLS ARE SPECIFIED.
- RELOCATION AND/OR REMOVAL OF EXISTING EQUIPMENT, DEVICES, OUTLETS BOXES, CONDUT, WRING, ETC. MAY AFFECT THE OPERATION OF EXISTING REMAINING ELECTRICAL EQUIPMENT/DEVICES, THE CONTRACTOR SHALL PROVIDE ADDITIONAL MATERIALS AS RESTRICTED ADDITIONAL MATERIALS AS RESTRICTED TO ADDITIONAL MATERIALS AS RESTRICTED TO ADDITIONAL MATERIALS AS RESTRICTED TO EXISTING REMAINING ELECTRICAL/DEVICES.

NEW PARKING LOT GRAND TERRACE ELEMENTARY SCHOOL COLTON JOINT UNIFIED SCHOOL DISTRICT 12066 VIVIENDA AVENUE, GRAND TERRACE, C







PROJECT:
PROJECT:
PROJECT:
PROJECT:
REVISION:

E0.10D

APPENDIX D

QUALIFICATIONS

State of California Division of Occupational Safety and Health Certified Site Surveillance Technician

Richard Isaac Garcia



Name
Certification No. 96-1908
Expires on 11/08/24

This certification was issued by the Division of Occupational Safety and Health as authorized by Sections 7180 et seq. of the Business and Professions Code.

State of California Division of Occupational Safety and Health **Certified Asbestos Consultant**



Certification No. 05-3783

Expires on ______05/19/25

This certification was issued by the Division of Occupational Safety and Health as authorized by Sections 7180 et seq. of the Business and Professions Code.



STATE OF CALIFORNIA DEPARTMENT OF PUBLIC HEALTH



LEAD-RELATED CONSTRUCTION CERTIFICATE

INDIVIDUAL:

CERTIFICATE TYPE:

NUMBER:

EXPIRATION DATE:



Lead Sampling Technician

LRC-00011842

10/9/2024

Yaritzie Moreno

Disclaimer: This document alone should not be relied upon to confirm certification status. Compare the individual's photo and name to another valid form of government issued photo identification. Verify the individual's certification status by searching for Lead-Related Construction Professionals at www.cdph.ca.gov/programs/clppb or calling (800) 597-LEAD



STATE OF CALIFORNIA DEPARTMENT OF PUBLIC HEALTH



LEAD-RELATED CONSTRUCTION CERTIFICATE

INDIVIDUAL: CERTIFICATE TYPE:

EXPIRATION DATE:

9

Lead Sampling Technician

LRC-00007469

NUMBER:

6/1/2024

Armando Garcia

Disclaimer: This document alone should not be relied upon to confirm certification status. Compare the individual's photo and name to another valid form of government issued photo identification. Verify the individual's certification status by searching for Lead-Related Construction Professionals at www.cdph.ca.gov/programs/clppb or calling (800) 597-LEAD

DIVISION 08 - OPENINGS

08 71 00 - DOOR HARDWARE

DIVISION 09 - FINISHES

09 90 00 - PAINTING 1 09 91 13 - EXTERIOR PAINTING

DIVISION 10 - SPECIALTIES

10 14 53 - TRAFFIC, PARKIKNG AND SITE SIGNAGE 10 14 63 - ELECTRONIC MESSAGE SIGN (MARQUEE)

DIVISION 22 - PLUMBING

22 05 00 – COMMON WORK RESULTS FOR PLUMBING 22 11 10 – FACILITY NATURAL-GAS PIPING

DIVISION 26 - ELECTRICAL AND LIGHTING

26 00 00 - GENERAL ELECTRICAL

DIVISION 31 - EARTHWORK

31 10 00 - SITE CLEARING

31 22 00 - GRADING

31 23 16 - EXCAVATOIN

31 23 16.13 - TRENCHING

31 23 23 - FILL

31 32 11 - SOIL SURFACE EROSION CONTROL

DIVISION 32 - EXTERIOR IMPROVEMENTS

32 11 23 - AGGREGATE BASE COURSES

32 12 16 - ASPHALT PAVING

32 13 13 - CONCRETE PAVING

32 17 13 - PARKING BUMPERS

32 17 23.13 - PAINTED PAVEMENT MARKINGS

32 17 26 - DETECTABLE WARNING PAVERS

32 31 13 - CHAIN LINK FENCES AND GATES

32 31 19 - DECORATIVE METAL FENCES AND GATES

32 84 00 - IRRIGATION SYSTEMS

32 93 00 - PLANTING OPERATIONS

DIVISION 33 - SITE UTILITIES

33 05 13 - MANHOLES AND STRUCTURES

33 41 11 - SITE STORM DRAINAGE SYSTEM



SECTION 09 91 13 - EXTERIOR PAINTING

PART 1 - GENERAL

1.1 SECTION INCLUDES

- A. Surface preparation.
- B. Field application of paints.
- C. Scope: Finish exterior surfaces exposed to view, unless fully factory-finished and unless otherwise indicated, including the following:
 - 1. Exposed overhangs, beams, rafters, fascia, etc.
 - 2. Exposed surfaces of steel posts/lintels and ledge angles.
 - 3. Doors and window frames (all surfaces).
 - 4. Roof flashings
 - 5. Mechanical, Electrical, and Plumbing:

Paint equipment that is exposed to weather or to view, including factory-finished materials, conduits, plumbing.

D. Do Not Paint or Finish the Following Items:

- 1. Items factory-finished unless otherwise indicated; materials and products having factory-applied primers are not considered factory finished.
- 2. Items indicated to receive other finishes.
- 3. Items indicated to remain unfinished.
- 4. Fire rating labels, equipment serial number and capacity labels, and operating parts of equipment.
- 5. Non-metallic roofing and flashing.
- 6. Stainless steel, anodized aluminum, bronze, terne coated stainless steel, zinc, and lead.
- 7. Floors, unless specifically indicated.
- 8. Brick, Architectural concrete, and Cast stone.
- 9. Glass.
- 10. Concrete masonry units in utility, mechanical, and electrical spaces.
- 11. Concealed pipes, ducts, and conduits.

1.2 RELATED REQUIREMENTS

- A. Section 05 50 00 Metal Fabrications: Shop-primed items.
- B. Section 09 91 23 Interior Painting.

1.3 DEFINITIONS

A. Comply with ASTM D16 for interpretation of terms used in this section.

1.4 REFERENCE STANDARDS

- A. AHRI 340/360 Standard Specification for Corrugated Polyethylene Pipe, 300- to 1500 MM (12- to 60-in.) Diameter; 2013.
- B. ASTM D16 Standard Terminology for Paint, Related Coatings, Materials, and Applications; 2016.
- C. CARB (SCM) Suggested Control Measure for Architectural Coatings; California Air Resources Board; 2007.
- D. SCAQMD 1113 Architectural Coatings; 1977 (Amended 2016).
- E. SSPC-SP 1 Solvent Cleaning; 2015, with Editorial Revision (2016).
- F. SSPC-SP 2 Hand Tool Cleaning; 2018.
- G. SSPC-SP 6 Commercial Blast Cleaning; 2007.

1.5 SUBMITTALS

- A. See Section 01 33 00 Submittal Procedures for administrative requirements.
- B. Product Data: Provide complete list of products to be used, with the following information for each:
 - 1. Manufacturer's name, product name and/or catalog number, and general product category (e.g. "alkyd enamel").
 - 2. MPI product number (e.g. MPI #47).
 - 3. Cross-reference to specified paint system(s) product is to be used in; include description of each system.
 - 4. Manufacturer's installation instructions.
 - 5. If proposal of substitutions is allowed under submittal procedures, explanation of substitutions proposed.
- C. Samples: Submit three paper "draw down" samples, 8-1/2 by 11 inches in size, illustrating range of colors available for each finishing product specified.
 - 1. Where sheen is specified, submit samples in only that sheen.

- 2. Where sheen is not specified, discuss sheen options with Architect before preparing samples, to eliminate sheens definitely not required.
- D. Certification: By manufacturer that paints and finishes comply with VOC limits specified.
- E. Manufacturer's Instructions: Indicate special surface preparation procedures.
- F. Maintenance Data: Submit data including finish schedule showing where each product/color/finish was used, product technical data sheets, material safety data sheets (MSDS), care and cleaning instructions, touch-up procedures, repair of painted and finished surfaces, and color samples of each color and finish used.
- G. Maintenance Materials: Furnish the following for District's use in maintenance of project.
 - 1. See Section 01 60 00 Product Requirements, for additional provisions.
 - 2. Extra Paint and Finish Materials: 1 gallon of each color; from the same product run, store where directed.
 - 3. Label each container with color in addition to the manufacturer's label.

1.6 QUALITY ASSURANCE

- A. Manufacturer Qualifications: Company specializing in manufacturing the products specified, with minimum three years documented experience.
- B. Applicator Qualifications: Company specializing in performing the type of work specified with minimum three years documented experience and approved by manufacturer.

1.7 DELIVERY, STORAGE, AND HANDLING

- A. Deliver products to site in sealed and labeled containers; inspect to verify acceptability.
- B. Container Label: Include manufacturer's name, type of paint, brand name, lot number, brand code, coverage, surface preparation, drying time, cleanup requirements, color designation, and instructions for mixing and reducing.
- C. Paint Materials: Store at minimum ambient temperature of 45 degrees F and a maximum of 90 degrees F, in ventilated area, and as required by manufacturer's instructions.

1.8 FIELD CONDITIONS

- A. Do not apply materials when surface and ambient temperatures are outside the temperature ranges required by the paint product manufacturer.
- B. Follow manufacturer's recommended procedures for producing best results, including testing of substrates, moisture in substrates, and humidity and temperature limitations.
- C. Do not apply exterior paint and finishes during rain or snow, or when relative humidity is outside the humidity ranges required by the paint product manufacturer.
- D. Minimum Application Temperatures for Latex Paints: 50 degrees F for exterior; unless required otherwise by manufacturer's instructions.

E. Provide lighting level of 80 ft candles measured mid-height at substrate surface.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

- A. Provide paints and finishes from the same manufacturer to the greatest extent possible.
 - 1. In the event that a single manufacturer cannot provide specified products, minor exceptions will be permitted provided approval by Architect is obtained using the specified procedures for substitutions.
 - 2. Substitution of other products by the same manufacturer is preferred over substitution of products by a different manufacturer.

B. Paints:

- 1. Behr Process Corporation: www.behr.com/#sle.
- 2. Dunn-Edwards Corporation: www.dunnedwards.com,
- 3. PPG Paints: www.ppgpaints.com/#sle.
- 4. Sherwin-Williams Company: www.sherwin-williams.com/#sle.
- 5. Vista Paint: www.vistapaint.com.
- C. Primer Sealers: Same manufacturer as top coats.
- D. Substitutions: See Section 01 60 00 Product Requirements.

2.2 PAINTS AND FINISHES - GENERAL

- A. Paints and Finishes: Ready mixed, unless required to be a field-catalyzed paint.
 - 1. Provide paints and finishes of a soft paste consistency, capable of being readily and uniformly dispersed to a homogeneous coating, with good flow and brushing properties, and capable of drying or curing free of streaks or sags.
 - 2. Provide materials that are compatible with one another and the substrates indicated under conditions of service and application, as demonstrated by manufacturer based on testing and field experience.
 - 3. For opaque finishes, tint each coat including primer coat and intermediate coats, one-half shade lighter than succeeding coat, with final finish coat as base color.
 - 4. Supply each paint material in quantity required to complete entire project's work from a single production run.
 - 5. Do not reduce, thin, or dilute paint or finishes or add materials unless such procedure is specifically described in manufacturer's product instructions.
- B. Volatile Organic Compound (VOC) Content: Comply with Section 01 61 16.

- C. Volatile Organic Compound (VOC) Content:
 - 1. Provide paints and finishes that comply with the most stringent requirements specified in the following:
 - a. AHRI 340/360--National Volatile Organic Compound Emission Standards for Architectural Coatings.
 - b. SCAQMD 1113 Rule.
 - c. CARB (SCM).
 - d. Architectural coatings VOC limits of California.
 - 2. Determination of VOC Content: Testing and calculation in accordance with AHRI 340/360 (EPA Method 24), exclusive of colorants added to a tint base and water added at project site; or other method acceptable to authorities having jurisdiction.
- D. Flammability: Comply with applicable code for surface burning characteristics.
- E. Sheens: Provide the sheens specified; where sheen is not specified, sheen will be selected later by Architect from the manufacturer's full line.
- F. Colors: As indicated on drawings.
 - 1. Extend colors to surface edges; colors may change at any edge as directed by Architect.

2.3 PAINT SYSTEMS - EXTERIOR

- A. Exterior Surfaces to be Painted, Unless Otherwise Indicated: Including concrete masonry units and primed metal.
 - 1. One or two coats to cover and one coat primer.
 - 2. Top Coat(s): Exterior Latex.
 - 3. Top Coat Sheen:
 - a. Flat: MPI gloss level 1; use this sheen at all locations.
 - b. Semi-Gloss: MPI gloss level 5; use this sheen at trim.
 - 4. Primer: As recommended by top coat manufacturer for specific substrate.
- B. Masonry/Concrete and CMU Opaque, Latex, 3 Coat:
 - 1. One coat of latex primer sealer.
 - 2. Low-Sheen-Elastomeric: Two coats of latex-acrylic.
 - 3. Premium Flat: Two coats of latex-acrylic enamel.
- C. Exterior Plaster, Opaque, 100% Acrylic Latex, 3 Coat:
 - 1. One coat of latex primer sealer.
 - 2. Flat: Two coats of latex.
- D. Ferrous Metals, Unprimed, Latex, 3 Coat:
 - 1. One coat of latex primer.
- E. Ferrous Metals, Primed, Latex, 2 Coat:

- 1. Touch-up with rust-inhibitive primer recommended by top coat manufacturer.
- F. Ferrous Metals, Unprimed, High-Performance, 3 Coat:
 - 1. Pre-Treatment: As recommended by manufacturer
 - 2. One coat galvanize primer.
 - 3. Gloss: Two coats of alkyd enamel; Behr Paint, 8200 Premium Direct-To-Metal Gloss Paint

2.4 PRIMERS

- A. Primers: Provide the following unless other primer is required or recommended by manufacturer of top coats.
 - 1. Alkali Resistant Water Based Primer.
 - 2. Interior/Exterior Latex Block Filler.
 - 3. Anti-Corrosive Alkyd Primer for Metal.
 - 4. Interior/Exterior Quick Dry Alkyd Primer for Metal.
 - 5. Alkyd Primer for Galvanized Metal.
 - 6. Water Based Primer for Galvanized Metal.
 - a. Products:
 - 1) Behr Premium Plus Interior/Exterior Multi-Surface Primer and Sealer [No. 436].
 - 2) Substitutions: Section 01 60 00 Product Requirements.
 - 7. Rust-Inhibitive Water Based Primer.
 - 8. Interior/Exterior Quick Dry Primer for Aluminum.
 - 9. Stain Blocking Primer.

2.5 ACCESSORY MATERIALS

- A. Accessory Materials: Provide primers, sealers, cleaning agents, cleaning cloths, sanding materials, and clean-up materials as required for final completion of painted surfaces.
- B. Patching Material: Latex filler.
- C. Fastener Head Cover Material: Latex filler.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Do not begin application of paints and finishes until substrates have been properly prepared.
- B. Verify that surfaces are ready to receive work as instructed by the product manufacturer.
- C. Examine surfaces scheduled to be finished prior to commencement of work. Report any condition that may potentially effect proper application.
- D. Test shop-applied primer for compatibility with subsequent cover materials.
- E. Measure moisture content of surfaces using an electronic moisture meter. Do not apply finishes unless moisture content of surfaces are below the following maximums:
 - 1. Exterior Plaster and Stucco: 12 percent.

2. Masonry, Concrete, and Concrete Masonry Units: 12 percent.

3.2 PREPARATION

- A. Clean surfaces thoroughly and correct defects prior to application.
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.
- C. Remove or repair existing paints or finishes that exhibit surface defects.
- D. Remove or mask surface appurtenances, including electrical plates, hardware, light fixture trim, escutcheons, and fittings, prior to preparing surfaces for finishing.
- E. Seal surfaces that might cause bleed through or staining of topcoat.
- F. Remove mildew from impervious surfaces by scrubbing with solution of tetra-sodium phosphate and bleach. Rinse with clean water and allow surface to dry.
- G. Masonry:
 - 1. Remove efflorescence and chalk. Do not coat surfaces if moisture content or alkalinity of surfaces or if alkalinity of mortar joints exceed that permitted in manufacturer's written instructions. Allow to dry.
 - 2. Prepare surface as recommended by top coat manufacturer.
 - 3. Clean surfaces with pressurized water. Use pressure range of 600 to 1,500 psi at 6 to 12 inches. Allow to dry.
- H. Exterior Plaster: Fill hairline cracks, small holes, and imperfections with exterior patching plaster. Make smooth and flush with adjacent surfaces. Wash and neutralize high alkali surfaces.
- I. Galvanized Surfaces:
 - 1. Remove surface contamination and oils and wash with solvent according to SSPC-SP 1.
 - 2. Prepare surface according to SSPC-SP 2.
- J. Ferrous Metal:
 - 1. Solvent clean according to SSPC-SP 1.
 - 2. Shop-Primed Surfaces: Sand and scrape to remove loose primer and rust. Feather edges to make touch-up patches inconspicuous. Clean surfaces with solvent. Prime bare steel surfaces. Re-prime entire shop-primed item.
 - 3. Remove rust, loose mill scale, and other foreign substances using using methods recommended in writing by paint manufacturer and blast cleaning according to SSPC-SP 6 "Commercial Blast Cleaning". Protect from corrosion until coated.

3.3 APPLICATION

- A. Remove unfinished louvers, grilles, covers, and access panels on mechanical and electrical components and paint separately.
- B. Apply products in accordance with manufacturer's written instructions.
- C. Where adjacent sealant is to be painted, do not apply finish coats until sealant is applied.
- D. Do not apply finishes to surfaces that are not dry. Allow applied coats to dry before next coat is applied.
- E. Apply each coat to uniform appearance.
- F. Dark Colors and Deep Clear Colors: Regardless of number of coats specified, apply additional coats until complete hide is achieved.
- G. Sand metal surfaces lightly between coats to achieve required finish.
- H. Vacuum clean surfaces of loose particles. Use tack cloth to remove dust and particles just prior to applying next coat.
- I. Reinstall electrical cover plates, hardware, light fixture trim, escutcheons, and fittings removed prior to finishing.

3.4 FIELD QUALITY CONTROL

A. See Section 01 40 00 - Quality Requirements, for general requirements for field inspection.

3.5 CLEANING

A. Collect waste material that could constitute a fire hazard, place in closed metal containers, and remove daily from site.

3.6 PROTECTION

- A. Protect finishes until completion of project.
- B. Touch-up damaged finishes after Substantial Completion.

END OF SECTION


THIS PAGE INTENTIONALLY LEFT BLANK

NEW PARKING LOT

GRAND TERRACE ELEMENTARY SCHOOL

COLTON JOINT UNIFIED SCHOOL DISTRICT 12066 VIVIENDA AVENUE, GRAND TERRACE, CA 92313

DSA #04-122929



CORS ID: MLFP NORTHING: 1793388.26

EASTING: 6768598.35

GENERAL NOTES:

THE FIELD TOPOGRAPHY SHOWN HERON WAS COMPILED BY FIELD SURVEY PERFORMED ON 08/23/2022 & 09/06/2022 BY EPIC ENGINEERS.

IN PREPARING THESE PLANS, EPIC ENGINEERS, INC. DID A THOROUGH SEARCH FOR ALL EXISTING PLANS AND COMPILED A FIELD SURVEY OF ALL ABOVE GROUND APPURTENANCES. EPIC ENGINEERS, INC. PROVIDES NO WARRANTY AND ACCEPTS NO RESPONSIBILITY AS TO THE ACTUAL LOCATION OF ANY UNDERGROUND OR ABOVE GROUND UTILITY EITHER INSTALLED BEFORE OR AFTER THE DATE OF PREPARATION OF THESE PLANS. CONTRACTOR TO CONTACT UNDERGROUND SERVICE ALERT @ 811 TO VERIFY LOCATION OF EXISTING UTILITY LOCATIONS AND SHALL CONTACT THE ENGINEER OF RECORD IF THERE IS ANY MATERIAL DISCREPANCY.

BENCHMARK:

VERTICAL CONTROL FOR THIS SURVEY IS NAVD88 GEOID18 AS ESTABLISHED BY STATIC GPS BASED ON THE CORS STATIONS LISTED UNDER THE BASIS OF BEARINGS SHOWN HEREON.

A TEMPORARY BENCHMARK WAS ESTABLISHED AT THE BASE CONTROL POINT NO. 1 REFERENCED ABOVE DESCRIPTION: MN

ELEVATION: 1009.01' (NAVD88)

COMBINATION FACTOR OF: 0.99995636

BASIS OF BEARINGS:

THE BASIS OF BEARINGS FOR THIS SURVEY IS THE CALIFORNIA STATE PLANE COORDINATE SYSTEM: SPC 0405, ZONE V BASED LOCALLY ON CONTINUOUS OPERATING REFERENCE STATIONS (CORS):

"MLFP" "EWPP" AND "CNPP" NAD 83 (2011) EPOCH 2010.00 ALL BEARINGS SHOWN ON THIS MAP ARE GRID. ALL DISTANCES ARE GROUND DISTANCES UNLESS SPECIFIED OTHERWISE. GRID DISTANCES MAY BE OBTAINED BY MULTIPLYING THE GROUND DISTANCE BY A

CALCULATIONS ARE MADE AT THE BASE CONTROL POINT NO. 1 WITH COORDINATES OF: NORTHING: 1836102.38' EASTING: 6767173.74'

ELEVATION: 1009.01' TODOCDADUIC I ECEND.

TOP	OGRAPHIC LEGEN	D:	
AC	ASPHALTIC CONCRETE	①	IRRIGATION CONTROL VALVE
ACB	ASPHALT CONCRETE BERM	lacksquare	WALLE
ADA	AMERICAN DISABILITY ACT	1	
BSG	BACKSIDE GROOVE	•	CONTROL POINT
CB	CATCH BASIN	1	
CFL	CURB FLOWLINE		TREE
CLF	CHAIN LINK FENCE		INLL
CO	CLEANOUT		
COL	COLUMN		DRAIN
COMM	COMMUNICATION		00/10/5 05750700
CONC	CONCRETE		DOUBLE DETECTOR
COR	CORNER		CHECK ASSEMBLY
OF .	DRINKING FOUNTAIN		POST INDICATOR VALVE
DH	DOOR HINGE	\bigcirc	TOST INDICATOR VALVE
DI .	DRAIN INLET		
DIC	DRAIN INLET CORNER		
DR	DIRECT REFLECTION		DOOR
DS .	DOWNSPOUT	U \	
ELEC	ELECTRICITY		
EOB	EDGE OF BRICK	ightharpoonup	FIRE DEPARTMENT CONNECTION
EOC	EDGE OF CONCRETE	\hookrightarrow	
ΞP	EDGE OF PAVEMENT		
ETP	EDGE OF TRAVELED PATH		SIGN
FA	FIRE ACCESS		
FDC	FIRE DEPARTMENT CONNECTION		
FF	FINISHED FLOOR	•	MANHOLE
=H =-	FIRE HYDRANT		
=L	FLOWLINE		
-P	FLAG POLE	\$	LIGHT
FSC	FINISHED SURFACE CONCRETE		
GB	GRADE BREAK	$+\bigcirc+$	FIRE HYDRANT
GL	GUTTER LIP	$\top \bigcirc \top$	THETHUMM
GP 	GOAL POST		
ICV	IRRIGATION CONTROL VALVE		POWER POLE
IE 	INVERT STORM DRAIN	•	, OTTEN OLL
INV	INVERT SEWER		
LT	LIGHT		CURB & GUTTER
MB	MAILBOX		
MN	MAGNAIL		EL 014/1/14/E
NG	NATURAL GROUND		FLOWLINE
PG	PLAYGROUND		
PIV	POST INDICATOR VALVE		EDGE OF CONCRETE / BRICK
PP 	POWER POLE		== == 0. 000
PS	PAINT STRIPE	,	
SCO	SEWER CLEANOUT		EDGE OF PAVEMENT
SDCO	STORM DRAIN CLEAN OUT		
SDMH	STORM DRAIN MAN HOLE		CDADE BREAK
SMH	SEWER MANHOLE		GRADE BREAK
STF	STEEL TUBE FENCE		
TC	TOP OF CURB		WALL
TD	TRUNCATED DOMES		
TH	THRESHOLD		

GRADING DEMOLITION NOTES

WROUGHT IRON FENCE

WHEEL STOP

THRESHOLD TRAFFIC LIGHT TOP OF PIPE TOP OF PAVEMENT TOP OF WALL UTILITY BOX UNKOWN UTILITY UTILITY VAULT VAULT WALL CORNER

1) PROTECT IN PLACE SPECIFIED ITEM

2) SAWCUT, REMOVE AND DISPOSE OF EXISTING ASPHALT 3) SAWCUT, REMOVE AND DISPOSE OF EXISTING CONCRETE CURB, GUTTER, AND/OR SIDEWALK

4) ADJUST EXISTING ITEM TO PROPOSED FINISHED GRADE PER PRECISE GRADING PLAN (5) CUT AND CAP EXISTING SPECIFIED UTILITY LINE 6 REMOVE EXISTING SPECIFIED UTILITY LINE


CONTROL TABLE POINT # NORTHING FASTING FLEVATION DESCRIPTION							CO	NTROL T	ABLE	
POINT#	NORTHING	EASTING	ELEVATION	DESCRIPTION	F	POINT#	NORTHING	EASTING	ELEVATION	DESCRIPTION
1	1836102.3830	6767173.7410	1009.01	MN		31	1836186.2143	6767093.0316	998.44	INV
2	1836089.8240	6767079.1050	1004.42	MN		32	1836020.6862	6767371.8389	996.92	INV
3	1836080.5550	6767195.8370	1008.93	SCORED X		35	1835566.6380	6767238.5410	1005.98	SCORED X
4	1835858.4760	6767317.4340	1007.02	MN		100	1835438.3771	6767147.6402	1002.23	SCORED X
5	1835455.1820	6767235.9770	1003.82	SCORED X		101	1835438.8087	6767202.1280	1002.34	SCORED X
6	1835398.6210	6766953.4570	996.86	FD 1 IP WITH N&T CALTRANS FLUSH		102	1835532.2806	6767232.7639	1005.59	SCORED X
7	1835436.4540	6766829.2400	993.63	SCORED X		103	1835667.2621	6767261.4081	1005.89	SCORED X
8	1835448.5180	6766532.0470	989.16	SCORED X		104	1835947.1874	6767315.0600	1007.70	SCORED X
9	1835643.7030	6766899.2190	995.27	MN		105	1836073.0968	6767252.6054	1009.58	MN
10	1835918.6020	6766899.5300	998.41	SCORED X		106	1836201.0846	6767106.9218	1006.26	MN
11	1835861.4460	6766952.0780	998.67	MN HVC		107	1836103.1963	6767165.9319	1008.79	MN
12	1835691.2440	6766900.7190	995.26	MN HVC		108	1836031.4581	6767233.4686	1007.46	SCORED X
13	1836185.3430	6767097.3660	1006.42	MN HVC		109	1835957.8982	6767190.2594	1004.54	MN
14	1836024.0660	6767383.7010	1009.53	NAIL IN AC HVC		110	1835899.0312	6767212.6008	1005.20	MN
15	1836023.7580	6767385.1520	1009.56	NAIL IN AC TIES		111	1835882.2497	6767161.9812	1005.15	SCORED X
16	1836022.6340	6767383.3810	1009.54	NAIL IN AC TIES		112	1835958.5802	6767127.5588	1003.46	MN
17	1836242.6260	6767428.9150	1013.01	NAIL IN AC TIES		113	1835947.1354	6767078.5410	1002.79	MN
18	1836244.5940	6767428.7780	1013.03	NAIL IN AC TIES		114	1836061.0184	6767045.0532	1003.04	MN
19	1836244.4130	6767426.5910	1013.02	NAIL IN AC TIES		115	1836003.4306	6766947.0938	1000.95	MN
20	1836242.4690	6767426.7430	1013.02	NAIL IN AC TIES		116	1835927.9836	6766973.9337	1000.31	SCORED X
21	1836331.7400	6767445.4980	1012.76	FD 1 IP RCE 3613 DN 0.67		117	1835793.5652	6767107.6005	1000.84	MN
22	1835884.0980	6767386.2470	1007.21	FD GEAR SPIKE LS 5411		118	1835729.0117	6767147.7683	1000.79	60D
23	1835910.7550	6767386.0610	1007.89	FD L&T IN TC		119	1835797.4903	6767209.8279	1005.11	SCORED X
24	1835868.1110	6767435.9590	1008.71	FD SCORED X IN TC		120	1835707.9319	6767043.7779	997.88	60D
25	1835948.5240	6767333.3580	1007.90	FD L&T IN TC		121	1835679.2627	6767253.7601	1005.71	60D
26	1835430.6600	6769626.3900	1063.80	FD 1 IP IN MON WELL DN 0.2		122	1835622.2560	6767173.9291	1000.66	SCORED X
27	1835385.9260	6765381.8650	975.42	FD 1 IP W N&T CALTRANS FLUSH		123	1835558.3480	6767098.5361	999.56	SCORED X
28	1836446.8530	6765594.3880	977.88	FD 1 IP W N&T CALTRANS FLUSH		124	1835564.2174	6766987.1995	999.26	SCORED X
29	1836459.2620	6766631.5740	999.04	FD 1 IP W N&T CALTRANS FLUSH		125	1835643.6879	6766972.2694	998.37	SCORED X
30	1835387.5810	6766197.2740	991.36	FD BRASS CALTRANS 215 CL MON						






CONCRETE HATCH

LIMITS OF REMOVAL







① ① (90.47) √ NG (88.43)
ELEC UTIL
(87.80TC)
(87.31CFL)
(87.40)
GL
(88.07TC)
(87.60CFL)
(87.73)
GL
(88.57)
GL
(88.57)
GL
(88.06)
EDC (87.86) <u>*</u> EOC (88.03) EOC (88.29) EOC (87.95) GL (87.94TC) (87.92CFL) (88.34) EOC **BARTON ROAD**

CORS ID: MLFP NORTHING: 1793388.26

EASTING: 6768598.35

GENERAL NOTES:

THE FIELD TOPOGRAPHY SHOWN HERON WAS COMPILED BY FIELD SURVEY PERFORMED ON 08/23/2022 & 09/06/2022 BY EPIC ENGINEERS.

IN PREPARING THESE PLANS, EPIC ENGINEERS, INC. DID A THOROUGH SEARCH FOR ALL EXISTING PLANS AND COMPILED A FIELD SURVEY OF ALL ABOVE GROUND APPURTENANCES. EPIC ENGINEERS, INC. PROVIDES NO WARRANTY AND ACCEPTS NO RESPONSIBILITY AS TO THE ACTUAL LOCATION OF ANY UNDERGROUND OR ABOVE GROUND UTILITY EITHER INSTALLED BEFORE OR AFTER THE DATE OF PREPARATION OF THESE PLANS. CONTRACTOR TO CONTACT UNDERGROUND SERVICE ALERT @ 811 TO VERIFY LOCATION OF EXISTING UTILITY LOCATIONS AND SHALL CONTACT THE ENGINEER OF RECORD IF THERE IS ANY MATERIAL DISCREPANCY.

BENCHMARK:

VERTICAL CONTROL FOR THIS SURVEY IS NAVD88 GEOID18 AS ESTABLISHED BY STATIC GPS BASED ON THE CORS STATIONS LISTED UNDER THE BASIS OF BEARINGS SHOWN HEREON.

A TEMPORARY BENCHMARK WAS ESTABLISHED AT THE BASE CONTROL POINT NO. 1 REFERENCED ABOVE DESCRIPTION: MN

ELEVATION: 1009.01' (NAVD88)

BASIS OF BEARINGS:

THE BASIS OF BEARINGS FOR THIS SURVEY IS THE CALIFORNIA STATE PLANE COORDINATE SYSTEM: SPC 0405, ZONE V

BASED LOCALLY ON CONTINUOUS OPERATING REFERENCE STATIONS (CORS): "MLFP" "EWPP" AND "CNPP" NAD 83 (2011) EPOCH 2010.00 ALL BEARINGS SHOWN ON THIS MAP ARE GRID. ALL DISTANCES ARE GROUND DISTANCES UNLESS SPECIFIED OTHERWISE. GRID DISTANCES MAY BE OBTAINED BY MULTIPLYING THE GROUND DISTANCE BY A

CALCULATIONS ARE MADE AT THE BASE CONTROL POINT NO. 1 WITH COORDINATES OF: NORTHING: 1836102.38' EASTING: 6767173.74'

ELEVATION: 1009.01' TOPOGRAPHIC LEGEND:

COMBINATION FACTOR OF: 0.99995636

AC	ASPHALTIC CONCRETE	\bigcirc	IRRIGATION CONTROL VALVE
ACB	ASPHALT CONCRETE BERM	\checkmark	nu donnor donnide vileve
ADA	AMERICAN DISABILITY ACT	.(1)	
BSG	BACKSIDE GROOVE	<u> </u>	CONTROL POINT
CB	CATCH BASIN	ı	
CFL	CURB FLOWLINE		TDEE
CLF	CHAIN LINK FENCE		TREE
00	CLEANOUT		
COL	COLUMN		DRAIN
COMM	COMMUNICATION		
CONC	CONCRETE		DOUBLE DETECTOR
COR	CORNER		CHECK ASSEMBLY
)F	DRINKING FOUNTAIN		
DΗ	DOOR HINGE	\bigcirc	POST INDICATOR VALVE
OI .	DRAIN INLET		
DIC	DRAIN INLET CORNER		
OR .	DIRECT REFLECTION		DOOR
os	DOWNSPOUT	\	
ELEC	ELECTRICITY		
OB	EDGE OF BRICK	ightharpoonup	EIDE DEDARTMENT COMMECTIC
:OC	EDGE OF CONCRETE	\mathcal{Q}	FIRE DEPARTMENT CONNECTION
P	EDGE OF PAVEMENT		
TP	EDGE OF TRAVELED PATH	_	SIGN
=A	FIRE ACCESS		SIGN
DC	FIRE DEPARTMENT CONNECTION		
F	FINISHED FLOOR	• •	MANHOLE
Н	FIRE HYDRANT	• •	MANITOLL
-L	FLOWLINE		
P	FLAG POLE	\$	LIGHT
-SC	FINISHED SURFACE CONCRETE	·	
ЭB	GRADE BREAK		
GL	GUTTER LIP	+0+	FIRE HYDRANT
SP .	GOAL POST		
CV	IRRIGATION CONTROL VALVE		
Ē	INVERT STORM DRAIN		POWER POLE
_ NV	INVERT SEWER		
LT	LIGHT		CURD & CUTTER
л ЛВ	MAILBOX		CURB & GUTTER
1N	MAGNAIL		
IG	NATURAL GROUND		FLOWLINE
rG PG	PLAYGROUND		-
PIV	POST INDICATOR VALVE		
PP	POWER POLE		EDGE OF CONCRETE / BRICK
PS	PAINT STRIPE		
SCO	SEWER CLEANOUT		EDGE OF PAVEMENT
SDCO	STORM DRAIN CLEAN OUT		LUCE OF TAVENIENT
SDMH	STORM DRAIN CLEAN OUT STORM DRAIN MAN HOLE		
SMH	SEWER MANHOLE		GRADE BREAK
STF	STEEL TUBE FENCE		
C	TOP OF CURB		14/4/
TD	TRUNCATED DOMES		WALL
υ Ή			
	THRESHOLD	(100)	
L COD	TRAFFIC LIGHT	(99)	CONTOUR
OP D	TOP OF PAYEMENT	199)	
P	TOP OF PAVEMENT		
W	TOP OF WALL		
JB Nur	UTILITY BOX		ASPHALT HATCH
UNK	UNKOWN		

GRADING DEMOLITION NOTES

(6) REMOVE EXISTING SPECIFIED UTILITY LINE

UTILITY UTILITY VAULT

WALL CORNER

WROUGHT IRON FENCE WHEEL STOP

1) PROTECT IN PLACE SPECIFIED ITEM


2 SAWCUT, REMOVE AND DISPOSE OF EXISTING ASPHALT

3 SAWCUT, REMOVE AND DISPOSE OF EXISTING CONCRETE CURB, GUTTER, AND/OR SIDEWALK 4) ADJUST EXISTING ITEM TO PROPOSED FINISHED GRADE PER PRECISE GRADING PLAN (5) CUT AND CAP EXISTING SPECIFIED UTILITY LINE

		CONT	ROL TAI	BLE		CC	NTROL T	ABLE	
POINT#	NORTHING	EASTING	ELEVATION	DESCRIPTION	POINT#	NORTHING	EASTING	ELEVATION	DESCRIPTION
1	1836102.3830	6767173.7410	1009.01	MN	31	1836186.2143	6767093.0316	998.44	INV
2	1836089.8240	6767079.1050	1004.42	MN	32	1836020.6862	6767371.8389	996.92	INV
3	1836080.5550	6767195.8370	1008.93	SCORED X	35	1835566.6380	6767238.5410	1005.98	SCORED X
4	1835858.4760	6767317.4340	1007.02	MN	100	1835438.3771	6767147.6402	1002.23	SCORED X
5	1835455.1820	6767235.9770	1003.82	SCORED X	101	1835438.8087	6767202.1280	1002.34	SCORED X
6	1835398.6210	6766953.4570	996.86	FD 1 IP WITH N&T CALTRANS FLUSH	102	1835532.2806	6767232.7639	1005.59	SCORED X
7	1835436.4540	6766829.2400	993.63	SCORED X	103	1835667.2621	6767261.4081	1005.89	SCORED X
8	1835448.5180	6766532.0470	989.16	SCORED X	104	1835947.1874	6767315.0600	1007.70	SCORED X
9	1835643.7030	6766899.2190	995.27	MN	105	1836073.0968	6767252.6054	1009.58	MN
10	1835918.6020	6766899.5300	998.41	SCORED X	106	1836201.0846	6767106.9218	1006.26	MN
11	1835861.4460	6766952.0780	998.67	MN HVC	107	1836103.1963	6767165.9319	1008.79	MN
12	1835691.2440	6766900.7190	995.26	MN HVC	108	1836031.4581	6767233.4686	1007.46	SCORED X
13	1836185.3430	6767097.3660	1006.42	MN HVC	109	1835957.8982	6767190.2594	1004.54	MN
14	1836024.0660	6767383.7010	1009.53	NAIL IN AC HVC	110	1835899.0312	6767212.6008	1005.20	MN
15	1836023.7580	6767385.1520	1009.56	NAIL IN AC TIES	111	1835882.2497	6767161.9812	1005.15	SCORED X
16	1836022.6340	6767383.3810	1009.54	NAIL IN AC TIES	112	1835958.5802	6767127.5588	1003.46	MN
17	1836242.6260	6767428.9150	1013.01	NAIL IN AC TIES	113	1835947.1354	6767078.5410	1002.79	MN
18	1836244.5940	6767428.7780	1013.03	NAIL IN AC TIES	114	1836061.0184	6767045.0532	1003.04	MN
19	1836244.4130	6767426.5910	1013.02	NAIL IN AC TIES	115	1836003.4306	6766947.0938	1000.95	MN
20	1836242.4690	6767426.7430	1013.02	NAIL IN AC TIES	116	1835927.9836	6766973.9337	1000.31	SCORED X
21	1836331.7400	6767445.4980	1012.76	FD 1 IP RCE 3613 DN 0.67	117	1835793.5652	6767107.6005	1000.84	MN
22	1835884.0980	6767386.2470	1007.21	FD GEAR SPIKE LS 5411	118	1835729.0117	6767147.7683	1000.79	60D
23	1835910.7550	6767386.0610	1007.89	FD L&T IN TC	119	1835797.4903	6767209.8279	1005.11	SCORED X
24	1835868.1110	6767435.9590	1008.71	FD SCORED X IN TC	120	1835707.9319	6767043.7779	997.88	60D
25	1835948.5240	6767333.3580	1007.90	FD L&T IN TC	121	1835679.2627	6767253.7601	1005.71	60D
26	1835430.6600	6769626.3900	1063.80	FD 1 IP IN MON WELL DN 0.2	122	1835622.2560	6767173.9291	1000.66	SCORED X
27	1835385.9260	6765381.8650	975.42	FD 1 IP W N&T CALTRANS FLUSH	123	1835558.3480	6767098.5361	999.56	SCORED X
28	1836446.8530	6765594.3880	977.88	FD 1 IP W N&T CALTRANS FLUSH	124	1835564.2174	6766987.1995	999.26	SCORED X
29	1836459.2620	6766631.5740	999.04	FD 1 IP W N&T CALTRANS FLUSH	125	1835643.6879	6766972.2694	998.37	SCORED X

30 | 1835387.5810 | 6766197.2740 | 991.36 | FD BRASS CALTRANS 215 CL MON






CONCRETE HATCH

LIMITS OF REMOVAL










(06.34TC) (05.89CFL) (00.28EOC) (98.25EOC) (98.29) SEWER UTIL UNK UTIL (98.48) **EXISTING EXISTING EXISTING BUILDING BUILDING BUILDING** $(FF = 99.53\pm)$ $(FF = 98.51\pm)$ (01.20) (98.31) (98.37) EOC (99.38) (99.38) EOC EOC EOC (02.34EQC) (99.55TW) √ NG (97.53EOC STEP) (99.05) EOC 🖈 (00.31EOC) **EXISTING** BUILDING $(FF = 98.20\pm)$ **BUILDING** $(FF = 99.56\pm)$ CONTINUED FUNCTION



GRADING CONSTRUCTION NOTES

(10) PROTECT IN PLACE EXISTING ITEM

(11) ADJUST EXISTING ITEM TO PROPOSED FINISHED GRADE JOIN PROPOSED SURFACE TO EXISTING SURFACE PER DETAIL "A" ON SHEET C-6.1 WITH FLUSH TRANSITION, MATCH GRADE. DOWELING FOR PCC ONLY (13) SEE SITE UTILITY PLAN FOR IDENTIFICATION OF OBJECT

(14) CONSTRUCT 4" AC OVER 5" CRUSHED AGGREGATE BASE COMPACTED TO 95% RELATIVE COMPACTION, AND 12" SUBGRADE COMPACTED TO 95% RELATIVE COMPACTION. FINAL PAVEMENT SECTION SHALL BE BASED UPON R-VALUE TESTING PERFORMED ON A REPRESENTATIVE SOIL SAMPLE COLLECTED WHEN SUB-GRADE ELEVATION IS REACHED. (15) CONSTRUCT 4" AC OVER 9" CRUSHED AGGREGATE BASE COMPACTED TO 95% RELATIVE COMPACTION, AND 12" SUBGRADE COMPACTED TO 95% RELATIVE COMPACTION. FINAL PAVEMENT SECTION SHALL BE BASED UPON R-VALUE TESTING PERFORMED ON A REPRESENTATIVE SOIL SAMPLE COLLECTED WHEN SUB-GRADE ELEVATION IS REACHED. TI = 6.

(16) CONSTRUCT 4" PCC (520-C-2500) OVER 6" CRUSHED AGGREGATE BASE COMPACTED TO 95% RELATIVE COMPACTION, WITH #4 BARS 18" O.C. BOTH WAYS, OVER 18" SUBGRADE COMPACTED TO 90% RELATIVE COMPACTION; WITH THICKENED EDGE PER DETAIL "B" ON SHEET C-6.1. FINAL PAVEMENT SECTION SHALL BE BASED UPON R-VALUE TESTING PERFORMED ON A REPRESENTATIVE SOIL SAMPLE COLLECTED WHEN SUB-GRADE ELEVATION IS REACHED. SCORING PATTERNS, COLOR AND FINISH PER ARCHITECT'S PLANS AND SPECIFICATIONS. (17) CONSTRUCT 6" PCC (560-C-3250) OVER 6" CRUSHED AGGREGATE BASE COMPACTED TO 95%


RELATIVE COMPACTION, WITH #4 BARS 18" O.C. BOTH WAYS, OVER 18" SUBGRADE COMPACTED TO 90% RELATIVE COMPACTION; WITH THICKENED EDGE PER DETAIL "B" ON SHEET C-6.1. FINAL PAVEMENT SECTION SHALL BE BASED UPON R-VALUE TESTING PERFORMED ON A REPRESENTATIVE SOIL SAMPLE COLLECTED WHEN SUB-GRADE ELEVATION IS REACHED. SCORING PATTERNS, COLOR AND FINISH PER ARCHITECT'S PLANS AND SPECIFICATIONS. TI = 6. (CONSTRUCT CURB TYPE A1-6 PER SPPWC STANDARD PLAN 120-2 ON SHEET C-6.2 (CURB HEIGHT PER PLAN)


(19) CONSTRUCT CURB TYPE A2-8 PER SPPWC STANDARD PLAN 120-2 ON SHEET C-6.2 (20) CONSTRUCT 0" PCC (520-C-2500) CURB ONLY PER DETAIL "C" ON SHEET C-6.1 (21) CONSTRUCT 0"- 6" PCC (520-C-2500) CURB TRANSITION PER DETAIL "D" ON SHEET C-6.1 CONSTRUCT CURB AND GUTTER WITH MODIFIED GUTTER HIKE PER DETAIL "E" ON SHEET C-6.1 (CURB HEIGHT PER PLAN)


(23) CONSTRUCT SEATWALL PER ARCHITECT'S PLANS AND SPECIFICATIONS (24) CONSTRUCT ACCESS RAMP PER SPPWC STANDARD PLAN 111-5, CASE A TYPE 1 (25) CONSTRUCT MOWSTRIP PER ARCHITECT'S PLANS AND SPECIFICATIONS FURNISH AND INSTALL SITE FENCING / RAILING / GATES PER ARCHITECT'S PLANS AND SPECIFICATIONS

27) PAINT / APPLY ACCESSIBLE SIGNING / STRIPING / PAVEMENT MARKINGS PER ARCHITECT'S PLANS AND SPECIFICATIONS

(28) CONSTRUCT RETAINING WALL PER ARCHITECT'S PLANS AND SPECIFICATIONS (29) CONSTRUCT WINGED HEADWALL PER CALTRANS STANDARD PLAN D90









GRADING CONSTRUCTION NOTES

(10) PROTECT IN PLACE EXISTING ITEM

(11) ADJUST EXISTING ITEM TO PROPOSED FINISHED GRADE JOIN PROPOSED SURFACE TO EXISTING SURFACE PER DETAIL "A" ON SHEET C-6.1 WITH FLUSH TRANSITION, MATCH GRADE. DOWELING FOR PCC ONLY (13) SEE SITE UTILITY PLAN FOR IDENTIFICATION OF OBJECT

CONSTRUCT 4" AC OVER 5" CRUSHED AGGREGATE BASE COMPACTED TO 95% RELATIVE COMPACTION, AND 12" SUBGRADE COMPACTED TO 95% RELATIVE COMPACTION. FINAL PAVEMENT SECTION SHALL BE BASED UPON R-VALUE TESTING PERFORMED ON A REPRESENTATIVE SOIL SAMPLE COLLECTED WHEN SUB-GRADE ELEVATION IS REACHED. (15) CONSTRUCT 4" AC OVER 9" CRUSHED AGGREGATE BASE COMPACTED TO 95% RELATIVE COMPACTION, AND 12" SUBGRADE COMPACTED TO 95% RELATIVE COMPACTION. FINAL PAVEMENT SECTION SHALL BE BASED UPON R-VALUE TESTING PERFORMED ON A REPRESENTATIVE SOIL SAMPLE COLLECTED WHEN SUB-GRADE ELEVATION IS REACHED. TI = 6. (16) CONSTRUCT 4" PCC (520-C-2500) OVER 6" CRUSHED AGGREGATE BASE COMPACTED TO 95% RELATIVE COMPACTION, WITH #4 BARS 18" O.C. BOTH WAYS, OVER 18" SUBGRADE COMPACTED

TO 90% RELATIVE COMPACTION; WITH THICKENED EDGE PER DETAIL "B" ON SHEET C-6.1. FINAL PAVEMENT SECTION SHALL BE BASED UPON R-VALUE TESTING PERFORMED ON A REPRESENTATIVE SOIL SAMPLE COLLECTED WHEN SUB-GRADE ELEVATION IS REACHED. SCORING PATTERNS, COLOR AND FINISH PER ARCHITECT'S PLANS AND SPECIFICATIONS. (17) CONSTRUCT 6" PCC (560-C-3250) OVER 6" CRUSHED AGGREGATE BASE COMPACTED TO 95% RELATIVE COMPACTION, WITH #4 BARS 18" O.C. BOTH WAYS, OVER 18" SUBGRADE COMPACTED TO 90% RELATIVE COMPACTION; WITH THICKENED EDGE PER DETAIL "B" ON SHEET C-6.1. FINAL

PAVEMENT SECTION SHALL BE BASED UPON R-VALUE TESTING PERFORMED ON A REPRESENTATIVE SOIL SAMPLE COLLECTED WHEN SUB-GRADE ELEVATION IS REACHED. SCORING PATTERNS, COLOR AND FINISH PER ARCHITECT'S PLANS AND SPECIFICATIONS. TI = 6. (CONSTRUCT CURB TYPE A1-6 PER SPPWC STANDARD PLAN 120-2 ON SHEET C-6.2 (CURB HEIGHT PER PLAN)


(19) CONSTRUCT CURB TYPE A2-8 PER SPPWC STANDARD PLAN 120-2 ON SHEET C-6.2 (20) CONSTRUCT 0" PCC (520-C-2500) CURB ONLY PER DETAIL "C" ON SHEET C-6.1 (21) CONSTRUCT 0"- 6" PCC (520-C-2500) CURB TRANSITION PER DETAIL "D" ON SHEET C-6.1 CONSTRUCT CURB AND GUTTER WITH MODIFIED GUTTER HIKE PER DETAIL "E" ON SHEET C-6.1 (CURB HEIGHT PER PLAN)


(23) CONSTRUCT SEATWALL PER ARCHITECT'S PLANS AND SPECIFICATIONS (24) CONSTRUCT ACCESS RAMP PER SPPWC STANDARD PLAN 111-5, CASE A TYPE 1 (25) CONSTRUCT MOWSTRIP PER ARCHITECT'S PLANS AND SPECIFICATIONS FURNISH AND INSTALL SITE FENCING / RAILING / GATES PER ARCHITECT'S PLANS AND SPECIFICATIONS


27) PAINT / APPLY ACCESSIBLE SIGNING / STRIPING / PAVEMENT MARKINGS PER ARCHITECT'S PLANS AND SPECIFICATIONS


(28) CONSTRUCT RETAINING WALL PER ARCHITECT'S PLANS AND SPECIFICATIONS (29) CONSTRUCT WINGED HEADWALL PER CALTRANS STANDARD PLAN D90











UTILITY CONSTRUCTION NOTES

70) CONNECT TO EXISTING WATER LINE

STORM DRAIN 80) FURNISH & INSTALL 4" ACO KLASSIKDRAIN K100 GALV. TRENCH DRAIN WITH TYPE 410D PERFORATED GALVANIZED STEEL GRATE & PER INSTALLATION DRAWING ON SHEET C-6.1. (81) CONSTRUCT PVC STORM DRAIN CLEANOUT PER DETAIL "F" ON SHEET C-6.1


FURNISH & INSTALL 12" X 12" PREFABRICATED CATCH BASIN (J&R CB1212 OR APPROVED EQUAL)
PER DETAIL "G" ON SHEET C-6.1 FURNISH & INSTALL 24" X 24" PREFABRICATED CATCH BASIN (J&R CB2424 OR APPROVED EQUAL)
PER DETAIL "G" ON SHEET C-6.1


(84) FURNISH & INSTALL 4" JAY R. SMITH PLANTING AREA DRAIN 2670, SEE SHEET C-6.1 85) CONSTRUCT STORM DRAIN MANHOLE PER SPPWC 2009 ED. STD. PLAN 321-2 ON SHEET C-6.2


1	WA	TER PARK	ING LOT	LINE DATA TABLE
	NAME	BEARING	LENGTH	DESCRIPTION
	W1	N00° 00′ 00″E	193.53	1.5" SCHEDULE 80 WATER LINE
	W2	N90° 00′ 00″E	108.80	1.5" SCHEDULE 80 WATER LINE
	W3	N00° 00' 00"E	3.00	1.5" SCHEDULE 80 WATER LINE

		W3 N00°	00' 00"E	3.00 1.	5" SCHEDULE 80 WATER LINE
		manufacture of the second of t	madellik maatilikk m	near silling to the same silling to	The state of the s
	•,	STORM DRA	AIN PARK	ING LOT	LINE DATA TABLE
	NAME	BEARING	LENGTH	SLOPE	DESCRIPTION
, Vonesk	D1	N11° 20′ 57″E	8.43	S=0.0226	12" SDR 35 PVC STORM DRAIN PIPE
	D2	N45° 00′ 00″W	10.62	S=0.0304	12" SDR 35 PVC STORM DRAIN PIPE
	D3	N45° 00' 00"W	31.78	S=0.0304	12" SDR 35 PVC STORM DRAIN PIPE
	D4	N90° 00' 00"W	13.97	S=0.0263	12" SDR 35 PVC STORM DRAIN PIPE
<u></u>	D5	N90° 00′ 00″W	22.53	S=0.0191	12" SDR 35 PVC STORM DRAIN PIPE
\	D6	S50° 39′ 46″W	98.24	S=0.0191	12" SDR 35 PVC STORM DRAIN PIPE
	D7	N90° 00' 00"W	349.16	S=0.0191	15" SDR 35 PVC STORM DRAIN PIPE
	D8	N78° 39' 03"W	58.44	S=0.0236	4" SDR 35 PVC STORM DRAIN PIPE
	D9	N78° 39′ 03″W	25.76	S=0.0236	4" SDR 35 PVC STORM DRAIN PIPE
	D10	N11° 20′ 57″E	15.54	S=0.0302	4" SDR 35 PVC STORM DRAIN PIPE
	D11	S45° 00' 00"E	4.25	S=0.0118	4" SDR 35 PVC STORM DRAIN PIPE
	D12	N90° 00′ 00″E	33.96	S=0.0118	4" SDR 35 PVC STORM DRAIN PIPE
	D13	N11° 20′ 57″E	1.58	S=0.0118	4" SDR 35 PVC STORM DRAIN PIPE
	D14	N11° 20′ 57″E	69.15	S=0.0118	6" SDR 35 PVC STORM DRAIN PIPE
	D15	S45° 00′ 00″W	14.02	S=0.0191	6" SDR 35 PVC STORM DRAIN PIPE
	D16	N90° 00' 00"W	17.63	S=0.0191	6" SDR 35 PVC STORM DRAIN PIPE
	D17	S0° 00′ 00″E	17.98	S=0.0364	6" SDR 35 PVC STORM DRAIN PIPE
	D18	S0° 00′ 00″E	6.90	S=0.0364	6" SDR 35 PVC STORM DRAIN PIPE
	D19	N90° 00′ 00″W	22.55	S=0.0191	8" SDR 35 PVC STORM DRAIN PIPE
	D20	N90° 00′ 00″E	4.74	S=0.0200	4" SDR 35 PVC STORM DRAIN PIPE
	D21	S45° 00′ 00″E	7.12	S=0.0200	4" SDR 35 PVC STORM DRAIN PIPE
	D22	S0° 00' 00"W	10.37	S=0.0200	4" SDR 35 PVC STORM DRAIN PIPE
	D23	S45° 00′ 00″W	29.43	S=0.0242	4" SDR 35 PVC STORM DRAIN PIPE
	D24	S45° 00′ 00″W	40.73	S=0.0191	4" SDR 35 PVC STORM DRAIN PIPE
	D25	S45° 00′ 00″W	6.77	S=0.0191	4" SDR 35 PVC STORM DRAIN PIPE
	D26	S45° 00′ 00″E	16.96	S=0.0582	4" SDR 35 PVC STORM DRAIN PIPE
	D27	N45° 00′ 00″W	15.10	S=0.0525	4" SDR 35 PVC STORM DRAIN PIPE
	D28	N90° 00′ 00″W	38.84	S=0.0525	4" SDR 35 PVC STORM DRAIN PIPE
Λ	D29	9 N0° 00' 00"E 3.10 S=0		S=0.9647	4" SDR 35 PVC STORM DRAIN PIPE
	D30	N90° 00' 00"W	19.37	S=0.0263	12" SDR 35 PVC STORM DRAIN PIPE
\wedge	D31	N0° 00' 00"E	2.32	S=1.0822	4" SDR 35 PVC STORM DRAIN PIPE
<u> </u>	D32	N45° 00' 00"W	1.96	S=0.0304	12" SDR 35 PVC STORM DRAIN PIPE
_	D33	N45° 00' 00"E	2.19	S=0.9520	4" SDR 35 PVC STORM DRAIN PIPE
$\angle 1$	D34	N78° 39′ 03″W	28.16	S=0.0304	8" SDR 35 PVC STORM DRAIN PIPE
Manager .	D35	N45° 00′ 00″W	3.09	S=0.0226	12" SDR 35 PVC STORM DRAIN PIPE
	D36	N78° 39' 03"W	4.41	S=0.0304	6" SDR 35 PVC STORM DRAIN PIPE
	D37	N90° 00′ 00″W	15.91	S=0.0525	4" SDR 35 PVC STORM DRAIN PIPE
	D38	N0° 00′ 00″E	11.80	S=0.0200	4" SDR 35 PVC STORM DRAIN PIPE
	D39	S0° 00′ 00″E	22.60	S=0.0191	4" SDR 35 PVC STORM DRAIN PIPE
	D40	S0° 00′ 00″E	8.61	S=0.0191	4" SDR 35 PVC STORM DRAIN PIPE
	D41	N90° 00′ 00″W	22.48	S=0.0191	4" SDR 35 PVC STORM DRAIN PIPE
	D42	S45° 00′ 41″W	12.73	S=0.0191	4" SDR 35 PVC STORM DRAIN PIPE
	D43	S45° 00′ 00″E	6.72	S=0.0200	4" SDR 35 PVC STORM DRAIN PIPE
	D44	S0° 00′ 00″E	5.40	S=0.0191	4" SDR 35 PVC STORM DRAIN PIPE
$\sqrt{1}$	D45	S45° 00' 00"W	11.61	S=0.0093	4" SDR 35 PVC STORM DRAIN PIPE
	D52	S45° 00′ 13″E	4.99	S=0.0199	4" SDR 35 PVC STORM DRAIN PIPE
	D53	S0° 00' 13"E	26.63	S=0.0199	4" SDR 35 PVC STORM DRAIN PIPE











UTILITY CONSTRUCTION NOTES

70) CONNECT TO EXISTING WATER LINE

STORM DRAIN 80) FURNISH & INSTALL 4" ACO KLASSIKDRAIN K100 GALV. TRENCH DRAIN WITH TYPE 410D PERFORATED GALVANIZED STEEL GRATE & PER INSTALLATION DRAWING ON SHEET C-6.1. (81) CONSTRUCT PVC STORM DRAIN CLEANOUT PER DETAIL "F" ON SHEET C-6.1

FURNISH & INSTALL 12" X 12" PREFABRICATED CATCH BASIN (J&R CB1212 OR APPROVED EQUAL)
PER DETAIL "G" ON SHEET C-6.1 FURNISH & INSTALL 24" X 24" PREFABRICATED CATCH BASIN (J&R CB2424 OR APPROVED EQUAL)
PER DETAIL "G" ON SHEET C-6.1

(84) FURNISH & INSTALL 4" JAY R. SMITH PLANTING AREA DRAIN 2670, SEE SHEET C-6.1 85) CONSTRUCT STORM DRAIN MANHOLE PER SPPWC 2009 ED. STD. PLAN 321-2 ON SHEET C-6.2

A STATE OF THE PARTY OF THE PAR	Marine, Same	antino.	Million Marian M
WA	ATER PARK	INĞ LÖT	LINĚ DĂTĂ TĂBLĚ
NAME	BEARING	LENGTH	DESCRIPTION
W1	N00° 00′ 00″E	193.53	1.5" SCHEDULE 80 WATER I
W2	N90° 00′ 00″E	108.80	1.5" SCHEDULE 80 WATER I
W3	N00° 00′ 00″E	3.00	1.5" SCHEDULE 80 WATER I


		W3	NOO" (00' 00"E	antill [®]	3.00	1.	5" SCHEDULE 80 WATER LINE
			-company, "co		~ *******	ecastar "encasta		"" "Negretable" —
	ST	ORN	1 DRA	IN PA	RK	ING LO	DΤ	LINE DATA TABLE
NAN	1E	BEAR	ING	LENG	TH	SLOPI	E	DESCRIPTION
D1	1 1	v11° 20	' 57 " E	8.43		S=0.022	?6	12" SDR 35 PVC STORM DRAIN PIPE
D2	2 N	145° 00'	'00"W	10.62	2	S=0.030)4	12" SDR 35 PVC STORM DRAIN PIPE
D3	3 N	145° 00'	'00"W	31.78	3	S=0.030)4	12" SDR 35 PVC STORM DRAIN PIPE
D 4	1 N	190° 00'	'00"W	13.97	7	S=0.026	33	12" SDR 35 PVC STORM DRAIN PIPE
D5	5 N	190° 00'	'00"W	22.53	3	S=0.019)1	12" SDR 35 PVC STORM DRAIN PIPE
De	S S	50° 39'	46"W	98.24	1	S=0.019)1	12" SDR 35 PVC STORM DRAIN PIPE
D7	7 N	190° 00'	'00"W	349.1	6	S=0.019)1	15" SDR 35 PVC STORM DRAIN PIPE
DE	B N	178° 39	03"W	58.44	1	S=0.023	6	4" SDR 35 PVC STORM DRAIN PIPE
D9) N	178° 39'	'03 "W	25.76	3	S=0.023	86	4" SDR 35 PVC STORM DRAIN PIPE
D1	0 1	V11° 20	′ 57"E	15.54	1	S=0.030)2	4" SDR 35 PVC STORM DRAIN PIPE
D1	1 5	S45° 00	' 00"E	4.25		S=0.011	8	4" SDR 35 PVC STORM DRAIN PIPE
D1.	2 N	v90° 00	' 00"E	33.96	5	S=0.011	8	4" SDR 35 PVC STORM DRAIN PIPE
D1.	3 N	V11° 20	' 57"E	1.58		S=0.011	8	4" SDR 35 PVC STORM DRAIN PIPE
D1-	4N	V11° 20	' 57"E	69.15	5	S=0.011	8	6" SDR 35 PVC STORM DRAIN PIPE
D1:	5 S	345° 00'	00"W	14.02	2	S=0.019)1	6" SDR 35 PVC STORM DRAIN PIPE
D1	6 N	190° 00'	'00"W	17.63	}	S=0.019)1	6" SDR 35 PVC STORM DRAIN PIPE
D1	7	S0° 00′	00"E	17.98	}	S=0.036	64	6" SDR 35 PVC STORM DRAIN PIPE
D1	8	S0° 00′	00"E	6.90		S=0.036	64	6" SDR 35 PVC STORM DRAIN PIPE
D1	9 N	190° 00'	'00"W	22.55	5	S=0.019)1	8" SDR 35 PVC STORM DRAIN PIPE
D2	0 1	v90° 00	' 00"E	4.74		S=0.020	00	4" SDR 35 PVC STORM DRAIN PIPE
D2	1 5	S45° 00	' 00"E	7.12		S=0.020	00	4" SDR 35 PVC STORM DRAIN PIPE
D2.	2 5	S0° 00′	00 "W	10.37	7	S=0.020	00	4" SDR 35 PVC STORM DRAIN PIPE
D2	3 S	645° 00'	00 "W	29.43	3	S=0.024	!2	4" SDR 35 PVC STORM DRAIN PIPE
D2	4 S	345° 00'	00"W	40.73	3	S=0.019)1	4" SDR 35 PVC STORM DRAIN PIPE
D2	5 S	345° 00'	00 "W	6.77		S=0.019)1	4" SDR 35 PVC STORM DRAIN PIPE
D2	6 5	S45° 00	' 00"E	16.96	3	S=0.058	32	4" SDR 35 PVC STORM DRAIN PIPE
D2	7 N	145° 00'	'00"W	15.10)	S=0.052	25	4" SDR 35 PVC STORM DRAIN PIPE
D2	8 N	190° 00'	'00"W	38.84	1	S=0.052	25	4" SDR 35 PVC STORM DRAIN PIPE
D2	9	N0° 00'	00"E	3.10	_ggare,	S=0.964	!7	4" SDR 35 PVC STORM DRAIN PIPE
D3	0 N	190° 00	00"W	19.37	7	S=0.026	3	12" SDR 35 PVC STORM DRAIN PIPE
D3	1	N0° 00'	00"E	2.32	The state of the s	S=1.082	22	4" SDR 35 PVC STORM DRAIN PIPE
D3.	2 N	145° 00'	'00"W	1.96		S=0.030)4	12" SDR 35 PVC STORM DRAIN PIPE
D3.	3 N	V45° 00	' 00"E	2.19	- Carrier Co.	S=0.952	20	4" SDR 35 PVC STORM DRAIN PIPE
<u>1</u> D3	4 N	178° 39'	03"W	28.16	3	S=0.030)4	8" SDR 35 PVC STORM DRAIN PIPE
D3	5 N	145° 00'	00"W	3.09		S=0.022	?6	12" SDR 35 PVC STORM DRAIN PIPE
D3	6 N	178° 39	03"W	4.41		S=0.030)4	6" SDR 35 PVC STORM DRAIN PIPE
D3	7 N	190° 00'	' 00"W	15.91	1	S=0.052	25	4" SDR 35 PVC STORM DRAIN PIPE
D3	8 1	N0° 00'	00"E	11.80)	S=0.020	00	4" SDR 35 PVC STORM DRAIN PIPE
D3	9 .	S0° 00′	00"E	22.60)	S=0.019)1	4" SDR 35 PVC STORM DRAIN PIPE
D4	0	S0° 00′	00"E	8.61		S=0.019)1	4" SDR 35 PVC STORM DRAIN PIPE
D4	1 N	190° 00'	'00"W	22.48	3	S=0.019)1	4" SDR 35 PVC STORM DRAIN PIPE
D4.	2 S	345° 00'	41"W	12.73	}	S=0.019)1	4" SDR 35 PVC STORM DRAIN PIPE
D4	3 5	645° 00	' 00"E	6.72		S=0.020	0	4" SDR 35 PVC STORM DRAIN PIPE
D4	4 .	S0° 00′	00"E	5.40		S=0.019)1	4" SDR 35 PVC STORM DRAIN PIPE
1 D4	5 S	345° 00'	00"W	11.61) (4)	S=0.009	3	4" SDR 35 PVC STORM DRAIN PIPE
D5.	2 5	S45° 00	' 13"E	4.99		S=0.019	9	4" SDR 35 PVC STORM DRAIN PIPE
D5.	3 ,	S0° 00′	13"E	26.63	3	S=0.019	9	4" SDR 35 PVC STORM DRAIN PIPE
















HORIZONTAL CONTROL TABLE									
POINT#	NORTHING	EASTING	DESCRIPTION						
10000	1835638.40	6767114.77	EDGE OF TRENCH DRAIN						
10001	1835579.09	6767166.43	CENTER OF CURB RADIUS						
10002	1835477.15	6767143.42	CENTER OF CURB RADIUS						
10003	1835472.43	6767166.95	CENTER OF CURB RADIUS						
10004	1835468.59	6767194.02	CENTER OF CURB RADIUS						
10005	1835562.52	6767211.90	CENTER OF CURB RADIUS						
10006	1835566.59	6767225.63	CENTER OF CURB RADIUS						
10007	1835572.68	6767180.68	CENTER OF CURB RADIUS						
10008	1835568.07	6767182.79	CENTER OF CURB RADIUS						
10009	1835563.91	6767176.13	CENTER OF CURB RADIUS						
10010	1835486.95	6767158.13	CENTER OF CURB RADIUS						
10011	1835475.16	6767165.03	CENTER OF CURB RADIUS						
10012	1835563.33	6767213.06	CENTER OF CATCH BASIN						
10013	1835455.86	6767190.35	CENTER OF CATCH BASIN						
10014	1835452.12	6767129.99	CENTER OF CATCH BASIN						
10015	1835473.88	6767070.51	CENTER OF CATCH BASIN						
10016	1835522.26	6767129.44	CENTER OF CATCH BASIN						
10017	1835609.77	6767140.90	CENTER OF CATCH BASIN						
10018	1835641.41	6767113.64	CORNER OF SAWCUT						
10019	1835641.48	6767185.21	CORNER OF SAWCUT						
10020	1835651.20	6767185.21	CORNER OF SAWCUT						
10021	1835586.81	6767103.05	CORNER OF SAWCUT						
10022	1835586.81	6767114.11	CORNER OF SAWCUT						
10023	1835569.65	6767038.42	CORNER OF SAWCUT						
10024	1835559.66	6767034.42	CORNER OF SAWCUT						
10025	1835543.83	6767041.13	CORNER OF SAWCUT						
10026	1835543.99	6767053.03	CORNER OF SAWCUT						
10027	1835684.25	6767264.11	CORNER OF SAWCUT						
10028	1835685.00	6767260.18	CORNER OF SAWCUT						
10029	1835672.75	6767221.13	CORNER OF SAWCUT						
10030	1835672.96	6767217.20	CORNER OF SAWCUT						
10031	1835560.99	6767064.20	CENTER OF CATCH BASIN						
10032	1835561.77	6767083.57	CENTER OF CATCH BASIN						
10033	1835561.15	6767097.38	CENTER OF CATCH BASIN						
10034	1835526.31	6767160.85	CENTER OF CATCH BASIN						
10035	1835523.48	6766563.16	BOTTOM OF BASIN						
10036	1835523.48	6766612.03	BOTTOM OF BASIN						
10037	1835570.34	6767115.35	EDGE OF TRENCH DRAIN						
10038	1835629.95	6767180.99	EDGE OF TRENCH DRAIN						
10039	1835629.95	6767207.96	EDGE OF TRENCH DRAIN						
10040	1835593.45	6767134.51	BEGINNING OF CURB						

10041 1835591.60 6767138.61 BEGINNING OF CURB


	DESCRIPTION	EASTING	NORTHING	POINT#
	END OF CURB	6767243.21	1835614.09	10042
	END OF CURB	6767243.21	1835609.59	10043
	RADIUS POINT	6767159.71	1835607.84	10044
	GRADE BREAK	6767159.67	1835638.45	10045
	GRADE BREAK	6767180.96	1835638.47	10046
	RADIUS POINT	6767207.96	1835639.85	10047
	GRADE BREAK	6767219.40	1835651.20	10048
	RADIUS POINT	6767257.89	1835625.03	10049
	CURB RADIUS POINT	6767261.14	1835615.59	10050
_	JOIN OFFSITE CURB	6767270.41	1835611.83	10051
	JOIN OFFSITE CURB	6767262.96	1835574.75	10052
	CURB POINT	6767166.43	1835605.59	10053
_	CURB POINT	6767140.25	1835583.32	10054
_	CURB POINT	6767129.23	1835528.42	10055
_	CURB POINT	6767209.11	1835469.06	10056
_	CURB POINT	6767226.82	1835557.30	10057
_	CURB POINT	6767225.63	1835581.59	10058
	CURB POINT	6767149.01	1835505.00	10059
	CURB POINT	6767148.22	1835501.08	10060
_	CURB RADIUS POINT	6767253.47	1835571.59	10061
	GRADE BREAK	6767126.55	1835586.20	10062
_	GRADE BREAK	6767122.96	1835568.33	10063
	GRADE BREAK	6767103.21	1835552.32	10064
	FLOWLINE	6767119.81	1835552.61	10065
_	CORNER OF FENCE	6767104.76	1835475.08	10066
	RADIUS POINT	6767079.35	1835475.95	10067
_	RADIUS POINT	6767076.82	1835456.18	10068
	RADIUS POINT	6767113.65	1835469.51	10069
	FLOWLINE	6767103.21	1835561.28	10070
_	CURB POINT	6767166.43	1835609.59	10071
_	BOTTOM OF BASIN	6766533.29	1835483.18	10072
	BOTTOM OF BASIN	6766547.72	1835468.99	10073
Sec.	BOTTOM OF BASIN	6766612.56	1835469.71	10074
	CENTER OF HEADWALL	6766615.86	1835501.81	10075
*****	CURB POINT	6767257.65	1835605.59	10076
	CURB END OF CURVE	6767253.47	1835581.59	10077
_	CURB END OF CURVE	6767261.14	1835605.59	10078
L	FACE OF RETAINING WALL	6767150.78	1835450.17	10079
L	FACE OF RETAINING WALL	6767182.89	1835453.17	10080
	CORNER OF SAWCUT	6767038.51	1835563.75	10081
_	CENTER OF MANHOLE	6766965.69	1835501.81	10082

LI	NE DATA TA	4 <i>BLE</i>
Ξ	BEARING	DISTANCE
	S11° 20′ 57.10″W	8.00'
	S11° 20′ 57.10″W	40.00'
	S11° 20′ 57.10″W	8.00'
	N89° 59′ 59.97″W	35.39'
	N89° 59′ 59.97″W	6.00'
	N89° 59′ 59.97″W	29.39'
	N89° 59′ 59.97″W	6.00'
	N79° 09′ 24.25″W	6.00'
	N89° 59′ 59.93″W	35.39'
	N90° 00′ 00.00″W	6.00'
	N90° 00′ 00.00″W	29.39'
	N90° 00′ 00.00″W	6.00'
	N11° 20′ 57.09″E	20.00'
	N89° 59′ 59.97″W	94.71'
	S11° 20′ 57.10″W	1.00'


CURVE DATA TABLE										
CURVE	LENGTH	RADIUS	DELTA	TANGENT						
C1	40.18'	35.00'	65° 46′ 44.60″	22.63'						
C2	35.02'	30.50'	65° 46′ 44.60″	19.72'						
C3	11.86′	10.00'	67° 57′ 32.02″	6.74'						
C5	36.38'	26.50'	78° 39′ 02.94″	21.71'						
C17	37.70'	24.00'	90° 00′ 00.00″	24.00'						
C19	37.70'	24.00'	89° 59′ 57.20″	24.00'						
C21	5.24'	3.30'	90° 53′ 10.12″	3.35'						
C25	3.21'	2.35'	78° 28′ 04.73″	1.92'						
C27	20.59'	15.00'	78° 39′ 02.91″	12.29'						
C29	12.49'	10.00'	71° 34′ 10.25″	7.21'						
	C1 C2 C3 C5 C17 C19 C21 C25 C27	CURVE LENGTH C1 40.18' C2 35.02' C3 11.86' C5 36.38' C17 37.70' C19 37.70' C21 5.24' C25 3.21' C27 20.59'	CURVE LENGTH RADIUS C1 40.18' 35.00' C2 35.02' 30.50' C3 11.86' 10.00' C5 36.38' 26.50' C17 37.70' 24.00' C19 37.70' 24.00' C21 5.24' 3.30' C25 3.21' 2.35' C27 20.59' 15.00'	CURVE LENGTH RADIUS DELTA C1 40.18' 35.00' 65° 46' 44.60" C2 35.02' 30.50' 65° 46' 44.60" C3 11.86' 10.00' 67° 57' 32.02" C5 36.38' 26.50' 78° 39' 02.94" C17 37.70' 24.00' 90° 00' 00.00" C19 37.70' 24.00' 89° 59' 57.20" C21 5.24' 3.30' 90° 53' 10.12" C25 3.21' 2.35' 78° 28' 04.73" C27 20.59' 15.00' 78° 39' 02.91"						

	CUR	/E DA	TA TABLE	
CURVE	LENGTH	RADIUS	DELTA	TANGENT
C30	4.69'	3.00'	89° 36′ 51.34″	2.98'
C32	10.28′	6.27'	93° 58′ 28.05″	6.72'
C34	20.59'	15.00'	78° 39′ 02.91″	12.29'
C39	19.63'	12.50'	90° 00′ 00.00″	12.50'
C40	7.23'	2.30'	179° 56′ 21.85″	4351.86'











Н	ORIZONT	AL CON	TROL TABLE
POINT#	NORTHING	EASTING	DESCRIPTION
10000	1835638.40	6767114.77	EDGE OF TRENCH DRAIN
10001	1835579.09	6767166.43	CENTER OF CURB RADIUS
10002	1835477.15	6767143.42	CENTER OF CURB RADIUS
10003	1835472.43	6767166.95	CENTER OF CURB RADIUS
10004	1835468.59	6767194.02	CENTER OF CURB RADIUS
10005	1835562.52	6767211.90	CENTER OF CURB RADIUS
10006	1835566.59	6767225.63	CENTER OF CURB RADIUS
10007	1835572.68	6767180.68	CENTER OF CURB RADIUS
10008	1835568.07	6767182.79	CENTER OF CURB RADIUS
10009	1835563.91	6767176.13	CENTER OF CURB RADIUS
10010	1835486.95	6767158.13	CENTER OF CURB RADIUS
10011	1835475.16	6767165.03	CENTER OF CURB RADIUS
10012	1835563.33	6767213.06	CENTER OF CATCH BASIN
10013	1835455.86	6767190.35	CENTER OF CATCH BASIN
10014	1835452.12	6767129.99	CENTER OF CATCH BASIN
10015	1835473.88	6767070.51	CENTER OF CATCH BASIN
10016	1835522.26	6767129.44	CENTER OF CATCH BASIN
10017	1835609.77	6767140.90	CENTER OF CATCH BASIN
10018	1835641.41	6767113.64	CORNER OF SAWCUT
10019	1835641.48	6767185.21	CORNER OF SAWCUT
10020	1835651.20	6767185.21	CORNER OF SAWCUT
10021	1835586.81	6767103.05	CORNER OF SAWCUT
10022	1835586.81	6767114.11	CORNER OF SAWCUT
10023	1835569.65	6767038.42	CORNER OF SAWCUT
10024	1835559.66	6767034.42	CORNER OF SAWCUT
10025	1835543.83	6767041.13	CORNER OF SAWCUT
10026	1835543.99	6767053.03	CORNER OF SAWCUT
10027	1835684.25	6767264.11	CORNER OF SAWCUT
10028	1835685.00	6767260.18	CORNER OF SAWCUT
10029	1835672.75	6767221.13	CORNER OF SAWCUT
10030	1835672.96	6767217.20	CORNER OF SAWCUT
10031	1835560.99	6767064.20	CENTER OF CATCH BASIN
10032	1835561.77	6767083.57	CENTER OF CATCH BASIN
10033	1835561.15	6767097.38	CENTER OF CATCH BASIN
10034	1835526.31	6767160.85	CENTER OF CATCH BASIN
10035	1835523.48	6766563.16	BOTTOM OF BASIN
10036	1835523.48	6766612.03	BOTTOM OF BASIN
10037	1835570.34	6767115.35	EDGE OF TRENCH DRAIN
10038	1835629.95	6767180.99	EDGE OF TRENCH DRAIN
10039	1835629.95	6767207.96	EDGE OF TRENCH DRAIN
10040	1835593.45	6767134.51	BEGINNING OF CURB
10041	1835591.60	6767138.61	BEGINNING OF CURB

POINT#	NORTHING	EASTING	DESCRIPTION
10042	1835614.09	6767243.21	END OF CURB
10043	1835609.59	6767243.21	END OF CURB
10044	1835607.84	6767159.71	RADIUS POINT
10045	1835638.45	6767159.67	GRADE BREAK
10046	1835638.47	6767180.96	GRADE BREAK
10047	1835639.85	6767207.96	RADIUS POINT
10048	1835651.20	6767219.40	GRADE BREAK
10049	1835625.03	6767257.89	RADIUS POINT
10050	1835615.59	6767261.14	CURB RADIUS POINT
10051	1835611.83	6767270.41	JOIN OFFSITE CURB
10052	1835574.75	6767262.96	JOIN OFFSITE CURB
10053	1835605.59	6767166.43	CURB POINT
10054	1835583.32	6767140.25	CURB POINT
10055	1835528.42	6767129.23	CURB POINT
10056	1835469.06	6767209.11	CURB POINT
10057	1835557.30	6767226.82	CURB POINT
10058	1835581.59	6767225.63	CURB POINT
10059	1835505.00	6767149.01	CURB POINT
10060	1835501.08	6767148.22	CURB POINT
10061	1835571.59	6767253.47	CURB RADIUS POINT
10062	1835586.20	6767126.55	GRADE BREAK
10063	1835568.33	6767122.96	GRADE BREAK
10064	1835552.32	6767103.21	GRADE BREAK
10065	1835552.61	6767119.81	FLOWLINE
10066	1835475.08	6767104.76	CORNER OF FENCE
10067	1835475.95	6767079.35	RADIUS POINT
10068	1835456.18	6767076.82	RADIUS POINT
10069	1835469.51	6767113.65	RADIUS POINT
10070	1835561.28	6767103.21	FLOWLINE
10071	1835609.59	6767166.43	CURB POINT
10072	1835483.18	6766533.29	BOTTOM OF BASIN
10073	1835468.99	6766547.72	BOTTOM OF BASIN
10074	1835469.71	6766612.56	BOTTOM OF BASIN
10075	1835501.81	6766615.86	CENTER OF HEADWALL
10076	1835605.59	6767257.65	CURB POINT
10077	1835581.59	6767253.47	CURB END OF CURVE
10078	1835605.59	6767261.14	CURB END OF CURVE
10079	1835450.17	6767150.78	FACE OF RETAINING WALL
10079	1835453.17	6767182.89	FACE OF RETAINING WALL
10081	1835563.75	6767038.51	CORNER OF SAWCUT
10081	1835501.81	6766965.69	CENTER OF MANHOLE

LINE DATA TABLE				LINE DATA TABLE			LINE DATA TABLE LINE DATA		NE DATA T	/
LINE	BEARING	DISTANCE	LIN	ΙE	BEARING	DISTANCE		LINE	BEARING	
L1	S11° 20′ 57.10″W	8.00'	L1	6	S11° 20′ 57.10″W	8.00'		L31	N11° 20′ 57.09″E	
L2	S11° 20′ 57.10″W	40.00'	L1	7	S11° 20′ 57.10″W	40.00'		L32	N90° 00' 00.00"E	
L3	S11° 20′ 57.10″W	8.00'	L1	8	S11° 20′ 57.10″W	8.00'		L33	N11° 13′ 44.37″E	
L4	N89° 59′ 59.97″W	35.39'	L1	9	S11° 20′ 57.10″W	4.58'		L34	S90° 00′ 00.00″W	
L5	N89° 59′ 59.97″W	6.00'	L2	0	S11° 20′ 57.10″W	2.83'		L35	S11° 20′ 57.09″W	
L6	N89° 59′ 59.97″W	29.39'	L2	1	S11° 20′ 57.09″W	6.37'		L36	S79° 09′ 24.29″E	I
L7	N89° 59′ 59.97″W	6.00'	L2	2	S11° 20′ 57.10″W	5.50'		L37	N11° 21' 04.18"E	Ī
L8	N79° 09′ 24.25″W	6.00'	L2	3	S11° 20′ 57.10″W	4.00'		L38	N11° 20′ 04.47″E	I
L9	N89° 59′ 59.93″W	35.39'	L2	4	S11° 20′ 57.10″W	5.50'		L39	S11° 20′ 57.09″W	I
L10	N90° 00' 00.00"W	6.00'	L2	5	S11° 20′ 57.10″W	18.70'		L40	N79° 09′ 24.29″W	Ī
L11	N90° 00' 00.00"W	29.39'	L2	6	S78° 39′ 02.91″E	24.00'		L41	S78° 39′ 02.90″E	Ī
L12	N90° 00' 00.00"W	6.00'	L2	7	N11° 20′ 57.09″E	1.37'		L42	N11° 20′ 57.09″E	Ī
L13	N11° 20′ 57.09″E	20.00'	L2	8	S79° 09′ 24.29″E	14.84'		L43	N11° 21' 25.15"E	Ī
L14	N89° 59′ 59.97″W	94.71'	L2	9	N11° 20′ 57.09″E	90.00'		L44	N11° 21' 07.43"E	I
L15	S11° 20′ 57.10″W	1.00'	L3	0	N79° 09′ 35.77″W	15.95']	L45	S79° 09' 24.29"E	T


CURVE DATA TABLE						
CURVE	LENGTH	RADIUS	DELTA	TANGENT		
C1	40.18'	35.00'	65° 46′ 44.60″	22.63'		
C2	35.02'	30.50'	65° 46′ 44.60″	19.72'		
C3	11.86′	10.00'	67° 57′ 32.02″	6.74'		
C5	36.38'	26.50'	78° 39′ 02.94″	21.71'		
C17	37.70'	24.00'	90° 00′ 00.00″	24.00'		
C19	37.70'	24.00'	89° 59′ 57.20″	24.00'		
C21	5.24'	3.30'	90° 53′ 10.12″	3.35'		
C25	3.21'	2.35'	78° 28′ 04.73″	1.92'		
C27	20.59'	15.00'	78° 39′ 02.91″	12.29'		
C29	12.49'	10.00'	71° 34′ 10.25″	7.21'		

CURVE DATA TABLE				
CURVE	LENGTH	RADIUS	DELTA	TANGENT
C30	4.69'	3.00'	89° 36′ 51.34″	2.98'
C32	10.28′	6.27'	93° 58′ 28.05″	6.72'
C34	20.59'	15.00'	78° 39′ 02.91″	12.29'
C39	19.63'	12.50'	90° 00′ 00.00″	12.50'
C40	7.23'	2.30'	179° 56′ 21.85″	4351.86'





SKING LOT




















PANEL SCHEDULE SPECIFIC NOTES:

"F" PROVIDE NEW BREAKER TO MATCH EXISTING IN PANEL.

(E)PARTIAL MAIN SWITCHBOARD "MS" - 1600A, 120/208V- 3ø - 4W (E)75KVA XFMR (LOCATED IN MAIN SWITCHBOARD ROOM TO BE DEMOLISHED) ← (E)2-1/2"C. PROVIDE (E) 3#4/0, #3G. (E)75KVA XFMR (LOCATED IN PARKING LOT TO BE DEMOLISHED) (E)DISTRIBUTION SWITCHBOARD "A" 120/240V, 1Ø, 3W 400A BUS (LOCATED IN PARKING LOT TO BE DEMOLISHED, REFER TO E0.10D) EXISTING BLDG E

SPECIFIC SINGLE LINE NOTES:


- (1) PROVIDE NEW COMPLETE CONNECTION TO EXISTING CIRCUIT BREAKER AS REQUIRED.
- PROVIDE NEW COMPLETE CONNECTION TO EXISTING PANELBOARD AS REQUIRED.
- (3) INTERECEPT EXISTING CONDUIT AND EXTEND AS INDICATED. REFER TO SITE ELECTRICAL PLAN FOR ADDITIONAL INFORMATION.

FEEDER SCHEDULE

			_			
FEEDER	CONDUIT AND CONDUCTORS	LOAD (A)	DISTANCE (ET)		AVAIL.FAULT CURRENT (A)	NOTES
(N) MS-DSG	2°C3#250KČMĬL, #3G.	36	400' TOTAL	1.80	-	BACKFEED TO BUILDING E
>						

GENERAL FEEDER SCHEDULE NOTES:

- FEEDERS SHOWN, UNLESS SPECIFICALLY NOTED OTHERWISE, ARE PRESUMED TO BE ROUTED IN METAL RACEWAYS. IF P.V.C. CONDUITS ARE UTILIZED, THE CONTRACTOR SHALL PROVIDE AN EQUIPMENT GROUND PER NEC, OR CEC WHERE ADOPTED, TABLE 250.122 OR, WHERE REQUIRED, PROVIDE A MAIN BONDING JUMPER PER TABLE 250.66 AND INCREASE THE CONDUIT SIZE ACCORDINGLY.
- 2. LOADS INDICATED WITH "() " REPRESENT WORST CASE LOAD IN AMPS.
- 3. DISTANCE SHOWN IS FOR DESIGN PURPOSES ONLY. IT IS NOT A MATERIAL TAKEOFF.
- 4. VOLTAGE DROP VALUE INDICATED IS AT THE END OF THE FEEDER.
- 5. AVAILABLE FAULT CURRENT VALUE AT THE END OF THE FEEDER INDICATED. CALCULATIONS ARE BASED UPON INITIAL VALUES RECEIVED FROM THE SERVING UTILITY AND THE LENGTH AND IMPEDANCE OF THE FEEDER. THE SHORT CIRCUIT CURRENT RATING, EQUIPMENT BUS BRACING, AND/OR AMP INTERRUPTING CURRENT OF EQUIPMENT CONNECTED ON THE LOAD SIDE OF THE FEEDER SHALL BE GREATER THAN THE AVAILABLE FAULT CURRENT.



PLAN NOTES:

- PROVIDE IN-GRADE, CODE SIZED, TRAFFIC RATED PULLBOX ENGRAVED "POWER". 2 NOT USED.
 - N ROUTE CONDUIT FROM BELOW GRADE EXPOSED ON BUILDING EXTERIOR TO AN ELEVATION ABOVE THE ACCESSIBLE CEILING SPACE. PROVIDE A WEATHERPROOF "LB" FITTING AND SEALED PENETRATION THROUGH THE BUILDING EXTERIOR AS REQUIRED TO PERFORM WORK INDICATED. PAINT
 - CONDUIT TO MATCH THE SURROUNDING SURFACE. 4 ROUTE CONDUIT UNDER CANOPY AS REQUIRED. PROVIDE MINIMUM 4" SEPARATION BETWEEN CONDUITS. PROVIDE SEALED PENETRATION THROUGH THE BUILDING EXTERIOR AS REQUIRED TO PERFORM WORK INDICATED. PAINT
 - CONDUIT TO MATCH THE SURROUNDING SURFACE. 5 PROVIDE COMPLETE CONNECTION TO NEW MARQUEE SIGN PER $^{ extstyle d}$ MANUFACTURERS REQUIREMENTS. PROVIDE GROUNDING OF SIGN/LEGS AS
 - 6 PROVIDE IN-GRADE, CODE SIZED, TRAFFIC RATED PULLBOX ENGRAVED
 - ROUTE CONDUIT AND WIRING TO NEAREST 120V PANELBOARD WITH SPARE CAPACITY TO ACCOMMODATE NEW MARQUEE SIGN. PROVIDE (1) 20A-1P CIRCUIT. CONTRACTOR TO PROVIDE CORRECT WIRE SIZES PER CODE AND PER VOLTAGE DROP CALCULATIONS. VERIFY EXACT ROUTING WITH ARCHITECT PRIOR TO
 - 8 EXISTING POST TOP FIXTURE. PROVIDE NEW CONDUIT AND CONDUCTORS AS INDICATED. VERIFY EXACT LOCATION IN FIELD.
 - PROVIDE RELAY AND TIMECLOCK/PHOTOCELL AS REQUIRED FOR CONTROL OF EXTERIOR LIGHTING BY PHOTOCELL ON/TIMECLOCK OFF. MOUNT RELAY IN SEPARATE BARRIERED COMPARTMENT OF PANELBOARD.
 - PROVIDE IN-GRADE, CODE SIZED, TRAFFIC RATED PULLBOX ENGRAVED
 - [11] EXISTING 2-1/2" POWER CONDUITS AND CONDUCTORS ROUTED ON CANOPY TO REMAIN PROTECTED IN PLACE. PROVIDE NEW 3#250KCMIL. #3G. CONDUCTORS IN EXISTING CONDUIT. VERIFY LOCATION IN FIELD.
 - PROVIDE IN-GRADE, CODE SIZED, TRAFFIC RATED PULLBOX ENGRAVED "EV
 - EXISTING POWER PULLBOX LOCATED ON TOP OF CANOPY TO REMAIN PROTECTED IN PLACE. VERIFY EXACT LOCATION IN FIELD. > 14 NOT USED.
 - EXISTING 2-1/2" POWER UNDERGROUND CONDUITS TO REMAIN PROTECTED IN PLACE. PROVIDE NEW 3#250KCMIL, #3G. CONDUCTORS IN EXISTING CONDUIT.
 - VERIFY ROUTING IN FIELD. (16) NOT USED.

17) NOT USED.

- 18 INTERCEPT AND EXTEND EXISTING CONDUIT AS INDICATED. PROVIDE NEW $^{ extstyle 2}$ INTERCEPT TYPE PULLBOX PER CODE SIZING REQUIREMENTS AND LOCATE ON
- PROVIDE NEW CONNECTION TO EXISTING CIRCUIT BREAKER. REFER TO SINGLE LINE DIAGRAM FOR ADDITIONAL INFORMATION.
- (20) PROVIDE NEW CONDUIT AND CONDUCTORS LOCATED ON TOP OF CANOPY. PROVIDE RAINTITE FLEX CONDUIT AS REQUIRED WHERE THERE IS A GAP BETWEEN BUILDING CANOPIES. REFER TO SINGLE LINE DIAGRAM FOR ADDITIONAL INFORMATION.
- PROVIDE SEALED PENETRATION INTO BUILDING ACCESSIBLE CEILING SPACE FROM TOP OF CANOPY. ROUTE CONDUIT ABOVE CEILING TO PANELBOARD AND CONNECT AS REQUIRED. REFER TO SINGLE LINE DIAGRAM FOR ADDITIONAL INFORMATION.

SITE PLAN GENERAL NOTES:

- CONTRACTOR SHALL EXERCISE EXTREME CAUTION IN EXCAVATING AND TRENCHING ON THIS SITE TO AVOID EXISTING DUCTS. PIPING OR CONDUITS. ETC., AND TO PREVENT HAZARDS TO PERSONNEL AND/OR DAMAGE TO EXISTING UNDERGROUND UTILITIES OR STRUCTURES WHETHER OR NOT SHOWN AND FOR THE LOCATION OF UNDERGROUND UTILITIES OR STRUCTURES WHETHER OR NOT SHOWN OR DETAILED AND INSTALLED BY ANY OTHER CONTRACTS. THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE ENGINEER SHOULD SUCH UNIDENTIFIED CONDITIONS BE DISCOVERED. THESE DRAWINGS AND SPECIFICATIONS DO NOT INCLUDE THE NECESSARY ELEMENTS FOR
- CONSTRUCTION SAFETY. CALL UNDERGROUND SERVICE ALERT (USA) AT 1 (800) 422-4133 OR APPLICABLE STATE AND LOCAL DIG SAFE OR UNDERGROUND ALERT HOTLINES PRIOR TO CONSTRUCTION START.
- 3. MINIMUM CONDUIT SIZE SHALL BE 3/4" U.O.N.
- 4. MINIMUM CONDUCTOR SIZE SHALL BE #10 AWG. U.O.N.
- ALL SITE BRANCH CIRCUITS SHALL INCLUDE AN EQUIPMENT GROUND CONDUCTOR THAT, AT MINIMUM, MATCHES THE SIZE OF THE ASSOCIATED BRANCH CIRCUIT CONDUCTOR. WHERE MULTIPLE BRANCH CIRCUITS ARE ROUTED/GROUPED TOGETHER, THE EQUIPMENT GROUNDING CONDUCTOR SHALL MATCH THE SIZE OF THE LARGEST BRANCH CIRCUIT CONDUCTOR IN THE
- 6. ALL ELECTRICAL EQUIPMENT MOUNTED OUTDOORS SHALL BE WEATHERPROOF
- 7. ALL CONDUIT ONLY SHALL BE PROVIDED WITH A NYLON PULL STRING.
- SEE ARCHITECTURAL/LANDSCAPE ARCHITECTURAL PLANS FOR EXACT LOCATIONS OF FIXTURES, PULLBOXES, MANHOLES, OTHER ELECTRICAL DEVICES, ETC. COORDINATE ALL UNDERGROUND STRUCTURES AND CONDUIT ROUTING WITH LANDSCAPE ARCHITECT PRIOR TO ROUGH-IN TO ENSURE THAT SUCH ITEMS ARE NOT PLACED IN CRITICAL LANDSCAPE PLANTING/HARDSCAPE
- 9. UNLESS SPECIFICALLY SHOWN AS (E), (R), (ER), (D), EXISTING OR NON-BOLD, ALL ELECTRICAL DEVICES SHOWN ARE NEW.


GENERAL SINGLE LINE DIAGRAM NOTES:

- ALL OVERCURRENT DEVICES IN AN INDIVIDUAL PIECE OF EQUIPMENT SHALL HAVE AN AIC RATING EQUAL TO THE OVERALL RATING OF THE EQUIPMENT-SERIES RATING OF DEVICES WITHIN A PIECE OF EQUIPMENT IS NOT ALLOWED. SEE SPECIFICATIONS FOR MORE INFORMATION. SERIES RATED DEVICES SHALL HAVE BEEN INVESTIGATED BY U.L. IN COMBINATION WITH THE END USE EQUIPMENT AND IN THE EQUIPMENT IN WHICH THESE DEVICES ARE USED AND SHALL BE MARKED WITH A SERIES RATING. ALL EQUIPMENT SHALL BE MARKED IN ACCORDANCE WITH NEC (OR CEC-WHERE ADOPTED) REQUIREMENTS. SEE SPECIFICATIONS FOR MORE INFORMATION WHERE SERIES RATINGS ARE ALLOWED, THE EQUIPMENT SHALL BE LEGIBLY MARKED IN THE FIELD TO INDICATE A SERIES COMBINATION RATING WHICH SHALL BE READILY VISIBLE.
- 3. ALL TERMINATIONS AND ENCLOSURES SHALL BE RATED FOR USE WITH 75 DEGREE CELSIUS CONDUCTORS.
- PROVIDE CIRCUIT BREAKER ARC ENERGY REDUCTION MAINTENANCE SWITCHING PER NEC, OR CEC WHERE ADPOPTED, 240.87(B)(3) FOR ANY CIRCUIT BREAKER, 1200A FRAME AND LARGER. SEE SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS.
- 5. ALL SWITCHBOARDS AND DISTRIBUTION BOARDS SHALL HAVE:
- a. TIN-PLATED ALUMINUM BUSSING WITH RECTANGULAR CROSS SECTION. HORIZONTAL AND VERTICAL BUSSING SHALL BE FULL LENGTH AND SHALL HAVE PROVISIONS FOR FUTURE EXTENSIONS. ALL BUSSING SHALL HAVE MINIMUM WITHSTAND RATING EQUAL TO THE AVAILABLE FAULT CURRENT INDICATED. ALI VERTICAL AND HORIZONTAL BUSSING SHALL BE RATED AT FULL CAPACITY IN AL SWITCHBOARD AND DISTRIBUTION BOARD SECTIONS. PROVIDE 100% NEUTRAL BUSSING MINIMUM UNLESS OTHERWISE NOTED. PROVIDE FULL LENGTH GROUND BUS AND, WHERE INDICATED ON PLANS, ISOLATED GROUND BUSSING. PROVIDE REAR WIRE WAY IN ALL SWITCHBOARD SECTIONS.
- b. LUGS SUITABLE FOR USE WITH COPPER OR ALUMINUM CONDUCTORS LISTED FOR USE WITH 75 DEGREE CELSIUS AMPACITY CONDUCTORS.
- c. PERMANENT PLACARD(S) MARKED PER THE SPECIFICATIONS AND PER NEC (OR CEC-WHERE ADOPTED) SECTIONS 225.37, 230.2(E), 690.56, 692.56, 700.7, 701.7, 702.7, AND 705.10 AND IFC (OR CFC - WHERE ADOPTED) SECTION 608.2.6.1. DENOTING THE PRESENCE OF ADDITIONAL SERVICES, PHOTOVOLTAIC SYSTEMS, FUEL CELLS, EMERGENCY, STATIONARY BATTERY STORAGE SYSTEMS, OR
- STAND-BY POWER SOURCES AS APPLICABLE. UNLESS SPECIFICALLY SHOWN AS (E), (R), (ER), (D), EXISTING OR NON-BOLD, ALL ELECTRICAL DEVICES SHOWN ARE NEW.
- WHERE REQUIRED BY THE LOCAL AUTHORITY HAVING JURISDICTION OR WHERE A NEW GROUND FAULT PROTECTIVE DEVICE IS BEING INSTALLED, A GROUND FAULT SYSTEM TEST SHALL BE CONDUCTED BY AN INDEPENDENT TESTING AGENCY PER NEC (OR CEC-WHERE ADOPTED) 230.95(C). THE GROUND FAULT SYSTEM TEST SHALL BE PERFORMED IN THE PRESENCE OF THE LOCAL AUTHORITY HAVING JURISDICTION. VERIFICATION OF DEVICE SETTINGS PER THE POWER SYSTEMS STUDY SPECIFICATION SHALL BE PERFORMED BY THE SAME INDEPENDENT TESTING AGENCY. THE GROUND FAULT TEST RESULTS SHALL BE DELIVERED TO THE ENGINEER OF RECORD. DURING THE CONSTRUCTION PHASE OF THE PROJECT, ALL NEW GROUND FAULT RELAYS SHALL BE SET AT THE LOWEST AVAILABLE TIME DELAY AND PICK-UP SETTINGS.

COLLABORATIVE 11870 Pierce Street, Suite 160 Riverside, California 92505 951.299.4160 www.tk1sc.com Project Leader - Bill Voller

Electrical Lead - Andrea Lawson tk1sc Job #: B2305008





PIPING MATERIALS

1. GAS PIPING BELOW GROUND: DRISCOPLEX PE2406 POLYETHYLENE PIPING SYSTEMS WITH ELECTRIC FUSION SOCKET JOINTS. PROVIDE #12 ELECTRIC TRACER COPPER WIRE, SPIRAL WRAPPED AROUND PIPE. UNDERGROUND STEEL PIPING AND FITTINGS SHALL BE AS FOR ABOVE GROUND. PIPING SHALL BE WRAPPED AND CATHODICALLY PROTECTED

PER THE SOILS ENGINEER DIRECTION.

2. GAS PIPING ABOVE GROUND:

SCHEDULE 40 BLACK STEEL WITH MALLEABLE IRON SCREWED OR WELDED JOINTS.

NOTE:
ALL PIPE, FITTINGS, FIXTURES, ETC. THAT CONTACT POTABLE WATER FOR HUMAN CONSUMPTION SHALL
SHOW APPROVAL TO NSF 61, ANNEX "G". EFFECTIVE JANUARY 1, 2010, THE LEAD CONTENT OF THE WETTED SURFACE AREA OF THE PIPES, FITTINGS AND FIXTURES CONVEYING POTABLE WATER FOR HUMAN CONSUMPTION, OF NOT MORE THAN 0.25%, SHALL BE DETERMINED PURSUANT TO A PRESCRIBED FORMULA AS DETERMINED BY THIRD PARTY CERTIFIERS TO NSF STANDARD 61, ANNEX "G". REFERENCE SECTION 604.2, CALIFORNIA PLUMBING CODE, 2022 EDITION, AND HEALTH &

CALIFORNIA GREEN BUILDING STANDARD TABLE 5.303.3 STANDARDS FOR PLUMBING FIXTURES AND FIXTURE FITTINGS

REQUIRED STANDARDS

WATER CLOSETS (TOILETS) — FLUSHOMETER VALVE TYPE SINGLE FLUSH, MAXIMUM FLUSH VOLUME	ASME A 112.19.2/ CSA B45.1 - 1.28 GAL
WATER CLOSETS (TOILETS) — FLUSHOMETER VALVE TYPE DUAL FLUSH, MAXIMUM FLUSH VOLUME	ASME A 112.19.14 AND USEPA WATERSENSE TANK — TYPE HIGH-EFFICIENCY TOILET SPECIFICATION — 1.28 GAL
URINALS, MAXIMUM FLUSH VOLUME	ASME A 112.19.2/ CSA B45.1 — 0.125 GAL
PUBLIC LAVATORY FAUCETS: MAXIMUM FLOW RATE — 0.5 GPM	ASME A 112.18.1/ CSA B125.1
PUBLIC METERING SELF—CLOSING FAUCETS: MAXIMUM WATER USE — 0.20 GAL PER METERING CYCLE	ASME A 112.18.1/ CSA B125.1
SHOWERHEADS MAXIMUM FLOW RATE — 1.8 GPM	ENERGY POLICY ACT OF 1992 ASME A112.18.1 / CSA B125.1

PLUMBING GENERAL NOTES

1. COORDINATE ALL LOCATIONS, SIZES AND ELEVATIONS OF ALL SLEEVES THROUGH BEAMS, SLABS AND FOOTINGS WITH STRUCTURAL AND ARCHITECTURAL DRAWINGS. 2. COORDINATE AND VERIFY EXACT LOCATION, SIZE, POINTS OF CONNECTION AND INVERT ELEVATIONS OF UTILITY SERVICE PIPING BEFORE TRENCHING OR INSTALLATION. 3. COORDINATE WITH ARCHITECTURAL DRAWINGS FOR WALL AND PARTITION CONSTRUCTION AND THICKNESS WHERE PLUMBING PIPING OR EQUIPMENT IS

4. THE LOCATION AND ELEVATION OF ALL PLUMBING PIPING SHALL BE VERIFIED AND COORDINATED WITH ALL OTHER TRADES, STRUCTURAL CONDITIONS AND BUILDING CONSTRUCTION PRIOR TO START OF INSTALLATION.

5. ALL VALVES AND COCKS SHALL BE LOCATED TO BE READILY ACCESSIBLE. WHERE VALVES ARE INSTALLED WITHIN OR BEHIND WALLS, PARTITIONS OR CEILINGS, AN ACCESS PANEL SHALL BE INSTALLED.

6. ALL WALL MOUNTED ACCESS PANELS AND WALL CLEANOUTS SHALL BE MOUNTED AS LOW AS POSSIBLE UNLESS NOTED OTHERWISE OR AS INDICATED IN ARCHITECTURAL PLANS OR AS REQUIRED. CONTRACTOR SHALL GET ARCHITECT AND ENGINEER APPROVAL FOR ALL LOCATIONS PRIOR TO INSTALLATION OF WALL GYPSUM

7. THESE DRAWINGS ARE DIAGRAMMATIC. THE LOCATION & ELEVATION OF ALL PLUMBING PIPING IS APPROXIMATE AND SHALL BE VERIFIED AND COORDINATED WITH ALL OTHER TRADES, STRUCTURAL CONDITIONS AND BUILDING CONSTRUCTION PRIOR TO START OF INSTALLATION.

8. PENETRATIONS OF PIPES, ETC, IN WALLS REQUIRING PROTECTED OPENINGS SHALL BE FIRE STOPPED. FIRE STOP MATERIAL SHALL BE A TESTED ASSEMBLY APPROVED BY THE STATE FIRE MARSHAL.

SYMBOL	ABBR.	DESCRIPTION
	S OR W	SOIL OR WASTE ABOVE FLOOR OR GRADE
	S OR W	SOIL OR WASTE BELOW FLOOR OR GRADE
AW	AW	ACID WASTE ABOVE FLOOR OR GRADE
AW	AW	ACID WASTE BELOW FLOOR OR GRADE
SD	SD	STORM DRAIN ABOVE FLOOR OR GRADE
- — SD — —	SD	STORM DRAIN BELOW FLOOR OR GRADE
OD	OD	OVERFLOW DRAIN ABOVE FLOOR OR GRADE
OD	OD	OVERFLOW DRAIN BELOW FLOOR OR GRADE
	V	SANITARY VENT
	CW	
IOW		COLD WATER
ICW	ICW	INDUSTRIAL COLD WATER
	HW	HOT WATER
	HWR	HOT WATER RETURN
— F ——	F	FIRE MAIN
D	D	INDIRECT DRAIN LINE
CD	CD	CONDENSATE DRAIN
SCD	SCD	SECONDARY CONDENSATE DRAIN
—— PCD ———	PCD	PUMPED CONDENSATE DRAIN
	G	DEMO GAS PIPE
G	G	FUEL/GAS GAS
MPG	MPG	MEDIUM PRESSURE FUEL GAS, 5 PSI
TP	TP	TRAP PRIMER
RTP	RTP	RECYCLED WATER TRAP PRIMER
	IXII	DIRECTION OF FLOW
. 9	D.C.	
	P.G.	PRESSURE GAUGE W/PETE COCK
—————————————————————————————————————	G.C.	GAS COCK
	P.R.V.	PRESSURE REDUCING VALVE
	G.V.	GATE VALVE
	L.B.V.	LOCKING BALL VALVE
φ	FC0	FLOOR CLEANOUT
 1	WCO	WALL CLEANOUT
		DOWN
O		RISE
——————————————————————————————————————		UNION
1 % →		SLOPE IN DIRECTION OF FLOW
<u> </u>	W.H.A.	WATER HAMMER ARRESTOR
•	P.O.C.	POINT OF CONNECTION
	RPBP	REDUCED PRESSURE BACKFLOW PREVENTER
(E)	EXIST. (E)	EXISTING
(L)	ABV.	ABOVE
	A.F.F. A.P.	ABOVE FINISHED FLOOR ACCESS PANEL
	ASS'Y BEH.	ASSEMBLY BEHIND
	BEL. BLDG.	BELOW BUILDING
	BMCS	BUILDING MANAGEMENT AND CONTROL SYSTEM
	C.I. CLG.	CAST IRON CEILING
	COTG CO.	CLEANOUT TO GRADE CLEAN OUT
	CONT. FFE	CONTINUATION FINISHED FLOOR ELEVATION
	DET. DN	DETAIL DOWN
	DWG'S EA	DRAWINGS EACH
	ELEC. EQUIP	ELECTRIC EQUIPMENT
	FH FIN	FIRE HYDRANT FINISHED
	FU	FIXTURE UNIT
	FLR FR.	FLOOR FROM
	GPF GPM	GALLONS PER FLUSH GALLONS PER MINUTE
	GR HDR	GRADE HEADER
	I.E. MECH	INVERT ELEVATION MECHANICAL
	TYP U/G	TYPICAL UNDERGROUND
	VTR	VENT THROUGH ROOF

LEGEND

LEGEND

2022 CALIFORNIA BUILDING CODE (CBC: PART 2 , TITLE 24 , CCR) (BASED ON 2021 INTERNATIONAL BUILDING CODE)

2022 CALIFORNIA ELECTRICAL CODE (CEC: PART 3 , TITLE 24 , CCR) (BASED ON 2020 NATIONAL ELECTRICAL CODE)

MECHANICAL CODE) 2022 CALIFORNIA PLUMBING CODE (CPC: PART 5 , TITLE 24 , CCR) (BASED ON 2021 UNIFORM PLUMBING CODE)

2022 CALIFORNIA FIRE CODE (CFC: PART 9, TITLE 24, CCR.) (BASED ON 2021 INTERNATIONAL FIRE 2022 CALIFORNIA ENERGY CODE.

2022 CALIFORNIA MECHANICAL CODE (CMC: PART 4 , TITLE 24 , CCR) (BASED ON 2021 UNIFORM

COLLABORATIVE

11870 Pierce Street, Suite 160

Riverside, California 92505


951.299.4160 www.tk1sc.com

Project Leader - Bill Voller

Electrical Lead - Andrea Lawson

tk1sc Job #: B2305008









2022 CALIFORNIA GREEN BUILDING CODE.


APPLICABLE CODES


NOTES













STREET IMPROVEMENT PLAN GRAND TERRACE ELEMENTARY SCHOOL

APN NO. 027-523-213 CITY OF GRAND TERRACE COUNTY OF SAN BERNARDINO





UTILITIES

SOUTHERN CALIFORNIA EDISON COMPANY 287 TENNESSEE STREET REDLANDS, CALIFORNIA 92373 (909) 307-6759 CONTACT: KEVIN PURTY

SOUTHERN CALIFORNIA GAS COMPANY 1981 WEST LUGONIA AVENUE REDLANDS, CALIFORNIA 92374 (900) 335-7772 CONTACT: DEVERY JENNINGS

1980 ORANGE STREET LANE SUITE 100 REDLANDS, CA 92374 (909) 748-6663 CONTACT: FRANK MURPHY

RIVERSIDE HIGHLAND WATER CO 12374 MICHIGAN STREET GRAND TERRACE, CA 92313 (909) 825-4128

CITY OF COLTON WASTEWATER 106 S 10TH STREET COLTON, CA 92324 (909) 370-6131

NOTES TO CONTRACTOR

- 1. CONTRACTOR TO IDENTIFY AND PROTECT IN PLACE ALL UTILITY MANHOLES, VALVES ETC. (WHETHER SHOWN ON PLAN OR NOT) AND ADJUST TO GRADE AS NECESSARY. 2. CONTRACTOR TO PROTECT IN PLACE ALL SURVEY MONUMENTS AND REPLACE AT OWN
- EXPENSE ANY MONUMENTS THAT ARE DAMAGED DURING CONSTRUCTION. 3. CONTRACTOR TO INSTALL BLUE FIRE HYDRANT MARKERS FOR ALL EXISTING FIRE HYDRANTS FOR THIS PROJECT.

UTILITY LOCATION

TRAFFIC CONTROL AT ALL TIMES.

GENERAL NOTES

BIDDING ON ANY ITEM.

DRAWINGS OR DETAILS.

COATED WITH AN ASPHALTIC EMULSION.

1. ALL WORK SHALL BE IN ACCORDANCE WITH THESE PLANS, THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS

2. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO FAMILIARIZE HIMSELF WITH THE JOB SITE AND THE

4. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO CALL THE CITY ENGINEER'S OFFICE AT (909) 825-6621 FOR

6. THE CONTRACTOR SHALL SATISFY HIMSELF THAT THE ESTIMATED QUANTITIES SHOWN ARE CORRECT BEFORE

9. AT ALL LOCATIONS WHERE NEW PAVEMENT JOINS EXISTING, THE EXISTING PAVEMENT SHALL BE CLEANED AND

10. THE CONTRACTOR IS RESPONSIBLE FOR THE PROTECTION OF ALL UTILITY VALVES, BOXES, COVERS, AND ADJUSTING

12. THE CONTRACTOR SHALL CALL IN A LOCATION REQUEST TO UNDERGROUND SERVICE ALERT (U.S.A.), PHONE NUMBER 1 (800) 227-2600, TWO WORKING DAYS BEFORE DIGGING. NO INSPECTION WILL BE PROVIDED BY THE CITY ENGINEER'S

UNDERGROUND FACILITIES WILL BE VALID UNLESS THE APPLICANT HAS BEEN PROVIDED AN INQUIRY IDENTIFICATION

OFFICE, AND NO CONSTRUCTION PERMIT ISSUED BY THE PUBLIC WORKS DEPT. INVOLVING EXCAVATION FOR

13. OBSERVANCE OF THE CONTRACTOR'S WORK BY REPRESENTATIVES OF THE CITY ENGINEER'S OFFICE SHALL NOT RELIEVE THE CONTRACTOR OF THE FINAL AND ULTIMATE RESPONSIBILITY FOR THE CONTRACTOR OF THE IMPROVEMENTS IN ACCORDANCE WITH THESE PLANS AND ANY REFERENCED SPECIFICATIONS, STANDARD

14. ALL EXPOSED CONCRETE SHALL CONFORM IN GRADE, COLOR AND FINISH TO ALL ADJOINING CURBS AND SIDEWALKS.

INCLUDING, BUT NOT LIMITED TO, GAS, TELEPHONE, ELECTRICAL, LIGHTING, TELEVISION CABLE, LANDSCAPING, LANDSCAPING IRRIGATION, DOMESTIC WATER, RECLAIMED WATER, SEWER, STORM DRAINAGE, FLOOD CONTROL

16. CONTRACTOR IS INSTRUCTED TO REFER TO THESE PLANS AND THE SPECIFICATIONS, AND WHERE THERE IS OR MAY

STOP AND THE ENGINEER NOTIFIED IMMEDIATELY. A NO FEE CONSTRUCTION PERMIT SHALL BE OBTAINED FROM THE

17. IF EXISTING UTILITIES OR ANY OTHER FACILITIES CONFLICT WITH THE PROPOSED IMPROVEMENTS, WORK SHALL

18. CONTRACTOR IS TO PROTECT PERMANENT MONUMENTS IN PLACE, PERMANENT MONUMENTS DESTROYED BY THE CONTRACTOR, SHALL BE RESET BY THE CONTRACTORS SURVEYOR AND CORNER RECORDS FILED WITH THE COUNTY

1. ALL WORK, MATERIALS AND EQUIPMENT FOR TRAFFIC SIGNING AND STRIPING SHALL CONFORM TO THESE PLANS AND STANDARDS SPECIFICATIONS FOR THE CITY OF LOMA LINDA AND THE STANDARD SPECIFICATIONS OF THE STATE OF

4. ALL STRIPING AND PAVEMENT MARKINGS SHALL BE ALKYD TYPE THERMOPLASTIC, 90 MILS MIN. FOR LANE LINES AND

SPECIFICATIONS SHEETS. SIGN CODES SHOWN HEREON ARE TO CONFORM TO CALTRANS SPECIFICATION SHEET

7. CONTROL POINTS OR "CAT-TRACKING" TO BE APPROVED BY THE ENGINEER 24 HOURS PRIOR TO PAVEMENT STRIPING

6. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO MAINTAIN BARRICADES, DELINEATORS OR OTHER

2. PAVEMENT MARKERS AND TRAFFIC STRIPING DIMENSIONS SHALL CONFORM TO CALTRANS STANDARD PLANS,

3. PAVEMENT MARKERS AND LEGENDS SHALL CONFORM TO THE CITY OF LOMA LINDA STANDARD STENCILS.

5. TRAFFIC SIGN DIMENSION, COLOR AND LETTERING SHALL CONFORM TO THE LATEST CALTRANS SIGN

CODES. TRAFFIC SIGN SIZE SHALL BE STANDARD UNLESS OTHERWISE SHOWN ON THE PLANS.

120 MILS MIN. FOR PAVEMENT MARKINGS, CROSSWALKS, ARROWS AND LEGENDS.

15. THE CONTRACTOR(S) SHALL COORDINATE CONSTRUCTION WITH ALL UTILITIES AND OTHER IMPROVEMENTS

BE A CONFLICT SHALL IMMEDIATELY REPORT SAID CONFLICT OR POSSIBLE CONFLICT TO THE CITY.

CITY OF LOMA LINDA ENGINEERING DIVISION PRIOR TO START OF ANY WORK WITHIN THE CITY LIMITS.

OF SAN BERNARDINO SURVEYOR AT NO ADDITIONAL COST TO THE CITY.

SIGNING AND STRIPING GENERAL NOTES

8. CROSSWALKS SHALL HAVE 10' BETWEEN CENTERLINES OF 12" STRIPES.

8. ALL EXISTING PAVEMENT TO BE REMOVED SHALL BE SAWCUT AND REMOVED TO CLEAN STRAIGHT LINES.

TERRACE NOR THE ENGINEER WILL BE RESPONSIBLE FOR ANY DAMAGE TO UNDERGROUND FACILITIES.

3. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN ALL NECESSARY PERMITS.

7. THE CONTRACTOR SHALL MAINTAIN DUST CONTROL AT ALL TIMES.

OF ALL CITY WATER VALVE BOXES AND COVERS TO FINISH GRADE.

SHALL BE REJECTED AND SHALL BE REMOVED SOLELY AT THE CONTRACTOR'S EXPENSE.

11. THE CONTRACTOR SHALL RESET MANHOLE RINGS TO SURROUNDING A.C. PAVEMENT GRADE.

CONSTRUCTION (LATEST EDITION), WITH SUPPLEMENTS, AND THE STANDARD PLANS AND SPECIFICATIONS OF THE

LOCATION OF UNDERGROUND FACILITIES SHOWN OR NOT SHOWN ON THESE PLANS. NEITHER THE CITY OF GRAND

INSPECTION 24 HOURS PRIOR TO PERFORMING ANY WORK. WORK PREFORMED WITHOUT CALLING FOR INSPECTION

5. UTILITY CONTRACTORS SHALL BE RESPONSIBLE FOR OBTAINING COMPACTION TESTS OF ALL TRENCH BACK FILL AND

SUBMITTING THEM TO THE CITY ENGINEER FOR APPROVAL. NOTIFY CITY ENGINEER'S OFFICE AT (909) 825-6621 24

THE MANHOLES AND VALVES SHOWN ON THESE PLANS ARE APPROXIMATE IN LOCATION AND ARE FOR INFORMATION PURPOSES ONLY. THE CONTRACTOR IS RESPONSIBLE FOR TYING OUT THE EXACT LOCATION OF SAID FACILITIES.

NOTE:

CONTRACTOR TO VERIFY LOCATION AND DEPTH OF EXISTING UTILITIES PRIOR TO BEGINNING

REVISIONS BENCHMARK: VERTICAL CONTROL FOR THIS SURVEY IS NAVD88 GEOID18 AS ESTABLISHED BY STATIC GPS BASED ON THE CORS STATIONS LISTED UNDER THE BASIS OF BEARINGS SHOWN HEREON. A TEMPORARY BENCHMARK WAS ESTABLISHED AT THE BASE CONTROL POINT NO. 1 REFERENCED ABOVE DESCRIPTION: MN

ELEVATION: 1009.01' (NAVD88)

_ 2024 APPROVED_ CITY ENGINEER - KAMRAN DADBEH REGISTERED CIVIL ENGINEER NO. 52185 EXP 12/31/25 DRAWN BY: ZEC CHECKED BY: ACB

RECOMMENDED BY:

CITY OF GRAND TERRACE STREET IMPROVEMENT PLAN


FOR CITY USE ONLY: FILE NO.

 \sim 1 of 2


DRAWING


CONSTRUCTION May 21, 2024


VIVIENDA AVE STA 00+71.35 TO STA 02+13.33




CONSTRUCTION NOTES & QUANTITY ESTIMATES






















TROY D MOLAUG R.C.E. 591/18

DATE

NOTE: CONTRACTOR TO VERIFY LOCATION AND DEPTH OF EXISTING UTILITIES PRIOR TO BEGINNING CONSTRUCTION

APPROV					
AFFROV					
CITY ENGINE	DATE	APPRV.	BY	REVISIONS	MARK
EXP 12/31/25	GPS	D BY STATIC	ABLISHEL	RK: VERTICAL CONTROL FOR THIS SURVEY IS NAVD88 GEOID18 AS ESTA	BENCHMA
1	'AN		11100011		

BASED ON THE CORS STATIONS LISTED UNDER THE BASIS OF BEARINGS SHOWN HEREON. A TEMPORARY BENCHMARK WAS ESTABLISHED AT THE BASE CONTROL POINT NO. 1 REFERENCED ABOVE DESCRIPTION: MN ELEVATION: 1009.01' (NAVD88)

APPROVED2024	CITY OF GRAND TERRACE
CITY ENGINEER - KAMRAN DADBEH REGISTERED CIVIL ENGINEER NO. 52185 EXP 12/31/25	STREET IMPROVEMENT PLAN VIVIENDA AVE
DRAWN BY: ZEC	STA 00+71.35 TO STA 02+13.33
CHECKED BY: ACB	

FOR CITY USE ONLY: FILE NO.

RECOMMENDED BY:


ROVEMENT PLAN ENDA AVE

DRAWING \sim

2 of 2

A PUBLIC SERVICE BY UNDERGROUND SERVICE ALERT

May 21, 2024



PARKING LOT
TERRACE ELEMENTARY SCHOOL

N JOINT UNIFIED SCHOOL DISTRICT
IVIENDA AVENUE, GRAND TERRACE, CA 9231

COMMUNICATION

SGILL

PROJECT NUMBER: 22-12105-04
PROJECT STATUS: BIDDING
PROJECT ISSUED: 04/08/2024
REVISION: DATE: DESCRIPTION:

A0.11

Grand Terrace Elementary School

UTIL-LOCATE SUBSURFACE UTILITY MAP

NOTE: POTHOLING IS "HIGHLY" RECOMMENDED, THE EXPOSURE OF THE UTILITY LINE WILL ACCURATELY VERIFY EXACT, DEPTH, DIRECTION, SIZE AND MATERIAL OF THE UTILITY PIPE OR LINE.

FOR AN ESTIMATE-PLEASE CALL OFFICE.



SUBSURFACE UTILITY MAP

1136 E. Valencia Dr, Fullerton, CA 92831
Toll free: 888.885.6228 Office: 714.521.5393 Cell: 714.296.9680
Email: arts@util-locate.com Web: www.util-locate.com

	SUBSURFACE UTILITY MAP SYMBOLS						
Ī	Symbols	Description					
	0	MANHOLE					
		GREASE INTERCEPTOR					
	0	HANDHOLE					
	Ф	SEWER / STORM DRAIN CLEAN OUT (C/O)					
	0	COMMUNICATION DROP / GAS DROP / ELECTRICAL DROP / WATER DROP					
	✡	STANDARD & PROPERTY LIGHT / YARD-LIGHT STANDARDS					
	Ø	UTILITY POLE / POWER POLE					
	ф — О	PARKING LOT LIGHTS / STREET LIGHTS					
	— о	PIPE TURNS UP / RISER / SPIGOT					
		STORM-GRATE / STORM DRAIN					

CURB SIDE DRAIN

FLOOR DRAIN

ELECTRICAL PANEL / SERVICE BOX / COMMUNICATION PANEL

TELEPHONE / PLUE CODE EMERGENCY PHONE

ELECTRICAL TRANSFORMER OR PAD MOUNTED TRANSFORMER (E.P.M.T)

ELECT. BOX / COM. BOX / VAULTS / PULL BOX / J-BOX / CONTROL BOX

FIRE HYDRANT / POST INDICATOR VALVE

FDC (FIRE DEPARTMENT CONNECTION)

END OF SIGNAL / BLOCKED PASS THIS POINT

BACKFLOW PREVENTER

LITHETY LINE CUT

S UTILITY LINE CUT
 ∴ CAPPED UTILITY LIN
 ⊕ POTHOLE LOCATING

ı ∟ CAPF		PED UTILITY LINE			
→ POTH		IOLE LOCATING			
	ABB	REVIATION	ABE	ABBREVIATION	
Abı	٢V	Description	Abrv	Description	
CV		Communication Vault	MTY	Empty	
EV		Electrical Vault	TW	Tracer Wire	
NC		Nonconductive	BFP	Backflow Preveter	
MH PB CNO		Mandhole	N/A	Not Accessible	
		Pull Box	UNK-I	Unknown Induction	
		Can not open	UNK-G	Unknown GPR	
WV		Water Valve	CU	Copper	
GV		Gas Valve	RC	Reclaim Water	
D PL		D Depth ±		Post Indicator Valve	
		Plastic (Conduit or Pipe)	JT	Joint Trench	
СМТ	Γ	Cement	TOP	Top Of Pipe	
CI		Cast Iron	∧CD	Ashastas Coment Pine	

PREPARED FOR


Epic Engineers

PROJECT ADDRESS

DATE	REVISION		
09-09-22	Initial Drawing		
11-07-22	Revision A (New Area)		
01-27-23	Revision B (Zone V)		
DRAWN BY:	G.E		
CHECKED BY:	A.S		







SUBSURFACE UTILITY MAP

1136 E. Valencia Dr, Fullerton, CA 92831
Toll free: 888.885.6228 Office: 714.521.5393 Cell: 714.296.9680
Email: arts@util-locate.com Web: www.util-locate.com

SUBSURFACE UTILITY MAP SYMBOLS

ymbols Description O MANHOLE © GREASE INTERCEPTOR □ HANDHOLE Φ SEWER / STORM DRAIN CLEAN OUT (C/O) COMMUNICATION DROP / GAS DROP / ELECTRICAL DROP / WATER DROP

STANDARD & PROPERTY LIGHT / YARD-LIGHT STANDARDS

UTILITY POLE / POWER POLE

→ PARKING LOT LIGHTS / STREET LIGHTS

→ PIPE TURNS UP / RISER / SPIGOT

STORM-GRATE / STORM DRAIN

CURB SIDE DRAIN

FLOOR DRAIN

ELECTRICAL PANEL / SERVICE BOX / COMMUNICATION PANEL

△ TELEPHONE / BLUE CODE EMERGENCY PHONE○ GAS METER / WATER METER

GAS VALVE / WATER VALVE / CONTROL VALVE

ELECTRICAL TRANSFORMER OR PAD MOUNTED TRANSFORMER (E.P.M.T)

ELECT. BOX / COM. BOX / VAULTS / PULL BOX / J-BOX / CONTROL BOX

FIRE HYDRANT / POST INDICATOR VALVE

FDC (FIRE DEPARTMENT CONNECTION)

END OF SIGNAL / BLOCKED PASS THIS POINT

BACKEL OW PREVENTER

BACKFLOW PREVENTER

S UTILITY LINE CUT

POTHOLE LOCATING ABBREVIATION ABBREVIATION Description EV Electrical Vault Tracer Wire NC Nonconductive Backflow Preveter Not Accessible MH Mandhole N/A CNO Can not open UNK-G Unknown GPR Water Valve CU Copper

 WV
 Water Valve
 CO
 Copper

 GV
 Gas Valve
 RC
 Reclaim Water

 D
 Depth ±
 PIV
 Post Indicator Valve

 PL
 Plastic (Conduit or Pipe)
 JT
 Joint Trench

 CMT
 Cement
 TOP
 Top Of Pipe

 CI
 Cast Iron
 ACP
 Asbestos Cement Pipe

 MTL
 Metal
 VCP
 Vertrified Clay Pipe


PREPARED FOR

Epic Engineers

PROJECT ADDRESS

09-09-22	Initial Drawing
11-07-22	Revision A (New Area)
01-27-23	Revision B (Zone V)
DRAWN BY:	G.E
CHECKED BY:	A.S





GRAPHIC SCALE 1" = 20

UTILITY LEGEND LAYERS

UTILITY LEGEND LAYERS				
Linetype	Linetype Descriptions			
EM	Electrical Main line			
	Electrical Duct Bank			
<u></u>	Electrical Brackets (multiple lines)			
———Е———	Electrical line / Conduit lines / Property lines			
SL	Street Light Electrical lines			
TS	Traffic Signal Electrical lines			
CM	Communication Main line			
	Communication Duct Bank			
COM	Communication Brackets (multiple lines)			
COM	Communication line / Conduit lines / Property lines			
F0	Fiber Optic lines			
———FA ———	Fire Alarm lines			
T	Telephone Main line			
т	Telephone lines			
CTVM-	Cable TV Main line			
CTV	Cable TV lines			
————PA———	Public Annoucements			
GM	Gas Main line			
G	Gas lines			
OIL	Oil lines			
STM	Steam lines			
	Water Main line			
W	Water lines			
FWM	Fire water Main line			
FW	Fire water lines			
CW	Chill water lines			
HW	Hot water lines			
	Irrigation Main line			
IRR	Irrigation water lines Reclaimed Main line			
RWM	Reclaimed Main line Reclaimed water lines			
SD	Storm Drainage			
SEW	Sewer lines			
OL W	Halana Para / Alanda Para			

Unknown lines / Abandon lines



SUBSURFACE UTILITY MAP

1136 E. Valencia Dr, Fullerton, CA 92831
Toll free: 888.885.6228 Office: 714.521.5393 Cell: 714.296.9680
Email: arts@util-locate.com Web: www.util-locate.com

0					
Symbols	NAANII		scription		
0	MANH				
0		SE INTERCEPTOR			
	HAND		NIT (0(0)		
Ф		ER / STORM DRAIN CLEAN C	• •		
0		MUNICATION DROP / GAS D			
<i>\\</i>		DARD & PROPERTY LIGHT	YARD-LIGHT STAN	IDARDS	
α		TY POLE / POWER POLE			
ф О		ING LOT LIGHTS / STREET I			
— ○	PIPE '	TURNS UP / RISER / SPIGOT	Γ		
	STOR	M-GRATE / STORM DRAIN			
Ø	CURB	SIDE DRAIN			
Ø		R DRAIN			
×	ELEC	TRICAL PANEL / SERVICE B	OX / COMMUNICA	TION PANEL	
Δ	TELEI	PHONE / BLUE CODE EMERGENCY PHONE			
0	GAS N	METER / WATER METER			
	GAS \	VALVE / WATER VALVE / CONTROL VALVE			
		TRICAL TRANSFORMER OR		, ,	
	ELEC	T. BOX / COM. BOX / VAULTS / PULL BOX / J-BOX / CONTROL BOX			
\mathbb{A}	FIRE	HYDRANT / POST INDICATO	R VALVE		
বিচ	FDC (IRE DEPARTMENT CONNECTION)			
\mathbb{S}	END (OF SIGNAL / BLOCKED PASS THIS POINT			
\bowtie	BACK	KFLOW PREVENTER			
5	UTILI	TY LINE CUT			
山	CAPP	ED UTILITY LINE			
Φ	POTH	OLE LOCATING			
	ABBF	REVIATION	ABE	BREVIATION	
Abr	V	Description	Abrv	Description	
CV		Communication Vault	MTY	Empty	
EV		Electrical Vault	TW	Tracer Wire	
NC		Nonconductive	BFP	Backflow Preveter	
MH		Mandhole	N/A	Not Accessible	
PB		Pull Box	UNK-I	Unknown Induction	
CNC)	Can not open	UNK-G	Unknown GPR	
WV		Water Valve	CU	Copper	
GV		Gas Valve	RC	Reclaim Water	
			I	1	

PREPARED FOR

Asbestos Cement Pipe

Vertrified Clay Pipe


Plastic (Conduit or Pipe)

Epic Engineers

PROJECT ADDRESS

REVISION Initial Drawing Revision A (New Area) Revision B (Zone V)
Revision A (New Area)
·
Revision B (Zone V)
` ,
G.E
A.S
TEET No:
11110





GRAPHIC SCALE 1" = 20'

ш	ITV I		IAVEDO
ΙL	. 1 1 1 1	_EGENU	LAYERS

UTILITY LEGEND LAYERS					
Linetype	Linetype Descriptions				
ЕМ-	Electrical Main line				
	Electrical Duct Bank				
= = = = = = = = = = = = = = = = = = =	Electrical Brackets (multiple lines)				
Е	Electrical line / Conduit lines / Property lines				
SL	Street Light Electrical lines				
TS	Traffic Signal Electrical lines				
CM	Communication Main line				
C C C C C C C C C C C C C C C C C C C	Communication Duct Bank				
COM	Communication Brackets (multiple lines)				
СОМ	Communication line / Conduit lines / Property lines				
F0	Fiber Optic lines				
FA	Fire Alarm lines				
T	Telephone Main line				
Т ——	Telephone lines				
CTVM	Cable TV Main line				
CTV	Cable TV lines				
PA	Public Annoucements				
GM	Gas Main line				
G	Gas lines				
OIL	Oil lines				
STM	Steam lines				
	Water Main line				
w	Water lines				
FWM	Fire water Main line				
FW	Fire water lines				
cw	Chill water lines				
Н₩	Hot water lines				
IRM —	Irrigation Main line				
RWM	Irrigation water lines Reclaimed Main line				
	Reclaimed water lines				
SD	Storm Drainage				
1	l 🚬 🎽				

Sewer lines

Unknown lines / Abandon lines



SUBSURFACE UTILITY MAP

1136 E. Valencia Dr, Fullerton, CA 92831 Toll free: 888.885.6228 Office: 714.521.5393 Cell: 714.296.9680 Email: arts@util-locate.com Web: www.util-locate.com

SUBSURFACE UTILITY MAP SYMBOLS

MANHOLE GREASE INTERCEPTOR HANDHOLE SEWER / STORM DRAIN CLEAN OUT (C/O) COMMUNICATION DROP / GAS DROP / ELECTRICAL DROP / WATER DROP

STANDARD & PROPERTY LIGHT / YARD-LIGHT STANDARDS

UTILITY POLE / POWER POLE PARKING LOT LIGHTS / STREET LIGHTS

PIPE TURNS UP / RISER / SPIGOT STORM-GRATE / STORM DRAIN CURB SIDE DRAIN

FLOOR DRAIN ELECTRICAL PANEL / SERVICE BOX / COMMUNICATION PANEL TELEPHONE / BLUE CODE EMERGENCY PHONE

GAS METER / WATER METER GAS VALVE / WATER VALVE / CONTROL VALVE

ELECTRICAL TRANSFORMER OR PAD MOUNTED TRANSFORMER (E.P.M.T) ELECT. BOX / COM. BOX / VAULTS / PULL BOX / J-BOX / CONTROL BOX

FIRE HYDRANT / POST INDICATOR VALVE

FDC (FIRE DEPARTMENT CONNECTION) END OF SIGNAL / BLOCKED PASS THIS POINT

BACKFLOW PREVENTER

UTILITY LINE CUT

CAPPED UTILITY LINE

POTHOLE LOCATING ABBREVIATION ABBREVIATION Description Communication Vault

Description Electrical Vault **Backflow Preveter** Mandhole Not Accessible Can not open Unknown GPR Water Valve Depth ± Post Indicator Valve Plastic (Conduit or Pipe) Joint Trench Top Of Pipe Asbestos Cement Pipe

PREPARED FOR

Vertrified Clay Pipe

Epic Engineers

PROJECT ADDRESS

DATE	REVISION
09-09-22	Initial Drawing
11-07-22	Revision A (New Area)
01-27-23	Revision B (Zone V)
DRAWN BY:	G.E
CHECKED BY:	A.S
\sim	SHEET No:
<u> </u>	SUM-3
>	

2023 Summer Exterior Paint Remodel at Grand Terrace Elementary School








Maintenance & Operations Department (909)580-5008 / 7:30am - 4:00pm (M-F) 1313 Valley Boulevard, Colton, CA 92324

Project Address

Grand Terrace Elementary School 12066 Vivienda Ave. Grand Terrace, CA 92313





Typical exterior paint remodel (complete) to include minor cosmetic repairs. (as-noted) Color change to include but not limited to painting of administration buildings, classroom buildings, MPR buildings, covered walkways & portable classrooms'. **i.e. building coping, main walls, accent walls, columns, doors & window frames.** Refer to pages 1-10 for more information.

- All exposed aluminum window framing to remain clean & unpainted. (N.I.C.)
- All unfinished surfaces / concrete to remain clean & unpainted, unless otherwise noted. Coordinate with CJUSD, Maintenance Department.
- All door hardware, windows, flooring, landscape & roofing to remain clean & clear of any overspray.
- All galvanized railing, chain link fencing & gates to remain clean & unpainted. Unless otherwise noted.
- All areas in which work is done shall be left clean and in good repair. Any damage done to the existing and/or new work by the contactor or any of his subcontarctors or employees shall be repaired at no cost to the satisfaction of the district.
- Apply all primers and paints according to manufacturer's written instructions & recommendations.



Colton Joint Unified School District Maintenance & Operations Department (909)580-5008 / 7:30am - 4:00pm

			No.	1 01
Title	Site Plan w/			
Location	Grand Terra	ce Elementary S	chool	یا
Drawn	4/24/2023			
Revised		Approved by		2
				- (1

All rights reserved. This document is the product of intensive creative efforts and contains confidential trade secret information belonging to Labeld Ink incorporate No disclosure, distribution or reproduction of this material may be made without prior written authorization from Labeld Ink Incorporated. Unauthorized use, disclosure, dissemination or duplication of any of the information contained herein may result in liability under applicable laws.



Grand Terrace Elementary School 12066 Vivienda Ave, Grand Terrace, CA 92313


Location




& rendered trim









Project Notes

- All exterior doors to be primed & painted (_ unless otherwise noted. 2 All building exposed metal coping to be painted (_ unless otherwise noted.
- 3 All painted door & window framing to be painted (_ unless otherwise noted.
- 4 Building main walls to be painted (___ _), unless otherwise noted.
- **5** Building accent walls, as noted (rendered) to be painted (unless otherwise noted.
- 6 Building cornice moldings & accents, as noted (rendered) to be painted (____ _), unless otherwise noted.

General Notes

- All exposed aluminum framing to remain clean & unpainted. (N.I.C.)
- All unfinished surfaces / concrete to remain clean & unpainted, unless otherwise noted. Coordinate with CJUSD, Maintenance Department.
- All door hardware, windows, flooring, landscape & roofing to remain clean and clear of any overspray.
- All galvanized railing, chain link fencing & gates to remain clean & unpainted. Unless otherwise noted.
- All exposed light fixtures, cameras & fire alarm equipment to remain clean and clear of any overspray. (Exposed electrical conduit and intercom trim plates to be painted noted exterior color, coordinate w/ CJUSD.)
- Existing signage to be removed & replace, unless otherwise noted. Coordinate with CJUSD, Maintenance Department.

Potential Mural Not In Contract

No. 2 of 10



Colton Joint Unified School District Maintenance & Operations Department (909)580-5008 / 7:30am - 4:00pm

Administration, Library & MPR Building Grand Terrace Elementary School Location 4/24/2023 Reviewed by Drawn Labeld Revised Approved by

All rights reserved. This document is the product of intensive creative efforts and contains confidential trade secret information belonging to Labeld Ink incorporate No disclosure, distribution or reproduction of this material may be made without prior written authorization from Labeld Ink Incorporated. Unauthorized use, disclosure, dissemination or duplication of any of the information contained herein may result in liability under applicable laws.

This Document is for REFERENCE PURPOSES ONLY, is the responsibly of the appointe ractor to establish final & full so k. Contact CJUSD, Maintainance [



ADMINISTRATION & MPR BLDG.

Propos

Existin

Proposed Proposed Proposed









Existing



Existing



Existing

COLTON JOINT UNIFIED SCHOOL DISTRICT

023 Summer Exterior Paint Remodel at Grand Terrace Elementary School

Grand Terrace Elementary School 12066 Vivienda Ave, Grand Terrace, CA 92313



& rendered trim





accent walls, window trim. covered ceilings bldg. coping &

All exterior doors to be primed & painted (unless otherwise noted.

- 2 All building exposed metal coping to be painted unless otherwise noted. 3 All painted door & window framing to be painted
- unless otherwise noted. 4 Building main walls to be painted (_ otherwise noted.
- 6 Building accent walls, as noted (rendered) to be painted (_ _), unless otherwise noted.
- 6 Building cornice moldings and accents, as noted (rendered) to be painted), unless otherwise noted.

• All exposed aluminum framing to remain clean & unpainted. (N.I.C.)

- All unfinished surfaces / concrete to remain clean & unpainted, unless otherwise noted. Coordinate with CJUSD, Maintenance Dept.
- All door hardware, windows, flooring, landscape & roofing to remain clean and clear of any overspray.
- All galvanized railing, chain link fencing & gates to remain clean and unpainted, unless otherwise noted.
- All exposed light fixtures, cameras & fire alarm equipment to remain clean and clear of any overspray. (Exposed electrical conduit and intercom trim plates to be painted noted color, coordinate w/ CJUSD.)
- Existing signage to be removed & replace, unless otherwise noted. Coordinate with CJUSD, Maintenance Department.

**Addition of building identification signage/lettering recommended.

Potential Mural Not In Contract



Colton Joint Unified School District Maintenance & Operations Department (909)580-5008 / 7:30am - 4:00pm

Title	Administration, Library & MPR Building					
Location	Grand Terrace Elementary School					
Drawn	4/24/2023 Reviewed by					
Revised		Approved by				

All rights reserved. This document is the product of intensive creative efforts and contains confidential trade secret information belonging to Labeld Ink incorporate No disclosure, distribution or reproduction of this material may be made without prior written authorization from Labeld Ink Incorporated. Unauthorized use, disclosure, dissemination or duplication of any of the information contained herein may result in liability under applicable laws.

Review Set: April 28, 2023

No. 3 of 10



↑ CJUSD 2024-2025 Academic Calendar

July 2024							
Su	М	Tu	W	Th	F	Sa	
	1	2	3	4	5	6	
7	8	9	10	11	12	13	
14	15	16	17	18	19	20	
21	22	23	24	25	26	27	
28	29	30	31				

	August 2024					
Su	М	Tu	W	Th	F	Sa
				1	2	3
4	5	6	7	8	9	10
11	12	13	14	15	16	17
18	19	20	21	22	23	24
25	26	27	28	29	30	31

	September 2024						
Su	М	Tu	W	Th	F	Sa	
1	2	3	4	5	6	7	
8	9	10	11	12	13	14	
15	16	17	18	19	20	21	
22	23	24	25	26	27	28	
29	30						

	October 2024					
Su	М	Tu	W	Th	F	Sa
		1	2	3	4	5
6	7	8	9	10	11	12
13	14	15	16	17	18	19
20	21	22	23	24	25	26
27	28	29	30	31		

	November 2024					
Su	М	Tu	W	Th	F	Sa
					1	2
3	4	5	6	7	8	9
10	11	12	13	14	15	16
17	18	19	20	21	22	23
24	25	26	27	28	29	30

	December 2024					
Su	М	Tu	W	Th	F	Sa
1	2	3	4	5	6	7
8	9	10	11	12	13	14
15	16	17	18	19	20	21
22	23	24	25	26	27	28
29	30	31				

	J	anu	ary	202	5	
Su	М	Tu	W	Th	F	Sa
			1	2	3	4
5	6	7	8	9	10	11
12	13	14	15	16	17	18
19	20	21	22	23	24	25
26	27	28	29	30	31	

February 2025							
Su	М	Tu	W	Th	F	Sa	
						1	
2	3	4	5	6	7	8	
9	10	11	12	13	14	15	
16	17	18	19	20	21	22	
23	24	25	26	27	28		

		March 2025						
а	Su	М	Tu	W	Th	F	Sa	
1							1	
3	2	3	4	5	6	7	8	
5	9	10	11	12	13	14	15	
2	16	17	18	19	20	21	22	
	23	24	25	26	27	28	29	
	30	31						

	April 2025						
Su	М	Tu	W	Th	F	Sa	
		1	2	3	4	5	
6	7	8	9	10	11	12	
13	14	15	16	17	18	19	
20	21	22	23	24	25	26	
27	28	29	30				

	May 2025							
Su	М	Tu	W	Th	F	Sa		
				1	2	3		
4	5	6	7	8	9	10		
11	12	13	14	15	16	17		
18	19	20	21	22	23	24		
25	26	27	28	29	30	31		

	June 2025							
Su	М	Tu	W	Th	F	Sa		
1	2	3	4	5	6	7		
8	9	10	11	12	13	14		
15	16	17	18	19	20	21		
22	23	24	25	26	27	28		
29	30	7/1						

	2
In 100	Staff Days
Jul 29	Teacher PREP Day (Non-student day)
Jul 30	Teacher COLLAB Day (Non-student day)
Jul 31	Teacher PREP Day (Non-student day)
Dec 13	Teacher PREP Day (Non-student day)
Jan 06	Teachers Return from Winter Break and Collab Day
	Quarter/Semester Days
Aug 01	CJUSD First Day of School / Semester 1 Begins
Oct 04	1st Qtr Ends (46 days)
Dec 12	Semester 1 (89 days) / 2nd Qtr ends (43 days)
Jan 07	Students Return from Winter Break / Semester 2 Begins
Mar 14	3rd Qtr ends (47 days)
Mar 31	CJUSD Returns from Spring Break
Jun 02	Last Day of School / 4th Qtr ends (44 days)
	Minimum Days
Oct 07 - Oct 11	Minimum Days - Parent Teacher Conferences (TK -6)
Dec 10 - Dec 12	Minimum Days - Grades 7-12 FINALS
Mar 11 - Mar 14	Minimum Days - Parent Teacher Conferences (TK -6)
May 28 - May 30	Minimum Days - Grades 7-12 FINALS
Jun 02	Minimum Day - Last Day of School
	Holidays/Recess Breaks
Jul 04	Holiday - Independence Day
Sep 02	Holiday - Labor Day
Nov 11	Holiday - Veteran's Day
Nov 25-29	Thanksgiving Break
Nov 28-29	Holiday - Thanksgiving Day and
	Day after Thanksgiving (Observed)
Dec 16-Jan 7	Winter Break - Students
Dec 17-Jan 6	Winter Break - Teachers
Dec 24/Dec 25	Holiday - Christimas Eve / Christmas Day
Dec 31/ Jan 01	Holiday - New Year's Eve / New Year's Day
Jan 20	Holiday - Martin Luther King Jr. Day
Feb 10	Holiday - Lincoln's Birthday (CJUSD Observed)
Feb 17	Holiday - President's Day
Mar 17 - Mar 28	Spring Break
May 26	Halliday, Massacial Day
	Holiday - Memorial Day